

IMATION CORP (A 3M SPIN OFF COMPANY) -- 3M BRAND CD-5 DEVELOPER -- 6750-01-428-1366
===== Product Identification =====

Product ID:3M BRAND CD-5 DEVELOPER

MSDS Date:10/03/1996

FSC:6750

NIIN:01-428-1366

MSDS Number: CFYHR

=== Responsible Party ===

Company Name:IMATION CORP (A 3M SPIN OFF COMPANY)

Address:1 IMATION PL

City:SAINT PAUL

State:MN

ZIP:55128

Country:US

Info Phone Num:612-733-1341

Emergency Phone Num:612-733-1341

CAGE:06ZQ1

=== Contractor Identification ===

Company Name:IMATION CORP (A 3M SPIN OFF COMPANY)

Address:1 IMATION PL

Box:City:SAINT PAUL

State:MN

ZIP:55128

Country:US

Phone:612-733-1341

CAGE:06ZQ1

Company Name:IMATION ENTERPRISES CORP

Address:1 IMATION PLACE

Box:City:OAKDALE

State:MN

ZIP:55128-3414

Country:US

Phone:888-466-3456

CAGE:39711

Company Name:MINNESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS
DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:612-737-4114

CAGE:1BY21

=====

Composition/Information on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 80-90%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SULFITE
CAS:7757-83-7
RTECS #:WE2150000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM HYDROXIDE (CERCLA)
CAS:1310-73-2
RTECS #:WB4900000
Fraction by Wt: 1-3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:C 2 MG/M3; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:HYDROQUINONE (SARA 302/313) (CERCLA)
CAS:123-31-9
RTECS #:MX3500000
Fraction by Wt: 1-3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9596
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:POTASSIUM BROMIDE
CAS:7758-02-3
RTECS #:TS7650000
Fraction by Wt: 0.1-1.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:1-PHENYL-3-PYRAZOLIDONE
CAS:92-43-3
RTECS #:UQ8750000
Fraction by Wt: 4.0

===== Physical/Chemical Properties =====

HCC:B1
Boiling Pt:>1

00.C, 212.F
Melt/Freeze Pt:M.P/F.P Text:N/D
Vapor Pres:N/D
Vapor Density:N/D
Spec Gravity:1, H2O=1
pH:11.8
Viscosity:N/D
Evaporation Rate & Reference:N/D
Solubility in Water:COMPLETE
Appearance and Odor:ESSENTIALLY COLORLESS AND ODORLESS LIQUID.
Percent Volatiles by Volume:80-90
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous D
ecomposition Products:NOT DETERMINED

===== Disposal Considerations =====

Waste Disposal Methods:CHEM SUBJ TO REPORT REQMTS SEC 313 TITLE III
EPCRA/40CFR372:HYDROQUINONE.UNUSE DVLPR GENERALLY DISCHARE TO
WASTEH2O TREAT SYS.REGS VARY CONSULT LOC SEWER AUTHOR PRIOR TO
DISPO.SPENT DVLPR COMBINE W/FI XER WASTE,CONSIDERE HAZ WASTE-SILVER
CONTENT(SUP)

Disclaimer (provided with this information by the compiling agencies):
This information is formulate
d for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.