

P-T TECHNOLOGIES INC -- REMOVE-HP -- 6850-01-446-8063

===== Product Identification =====

Product ID:REMOVE-HP

MSDS Date:04/29/1997

FSC:6850

NIIN:01-446-8063

MSDS Number: CFYJW

=== Responsible Party ===

Company Name:P-T TECHNOLOGIES INC

Address:108 4TH AVENUE, SOUTH

City:SAFETY HARBOR

State:FL

ZIP:34695

Country:US

Info Phone Num:800-441-7874/813-726-4644

Emergency Phone Num:813-726-4644

CAGE:0JVH6

=== Contractor Identification ===

Company Name:P-T TECHNOLOGIES INC

Address:108 4TH AVENUE, SOUTH

Box:City:SAFETY HARBOR

State:FL

ZIP:34695

Country:US

Phone:813-726-4644

CAGE:0JVH6

===== Composition/Information on Ingredients =====

Ingred Name:HEAVY AROMATIC NAPHTHA (SOLVENT NAPHTHA)

CAS:64742-94-5

RTECS #:WF3100000

Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYL LACTATE

CAS:97-64-3

RTECS #:OD5075000

Other REC Limits:NONE RECOMMENDED

===== Hazards Ident

ification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE-MAY CAUSE IRRITATION. SKIN-MAY
CAUSE DEFATTING OR DRYNESS OF SKIN. CONTINUED DRYNESS MAY CAUSE
DERMATITIS. INHALATION-CAN CAUSE IRRITATION OF THE RESPIRATORY
TRACT. INGESTION-MAY CAUSE GASTROINTES TINAL IRRITATION.
Explanation of Carcinogenicity:NOT CARCINOGENIC.
Effects of Overexposure:EYE-TEARING AND RED
NESS. INHALATION-NAUSEA,
DIZZINESS OR HEADACHE. INGESTION-NAUSEA AND VOMITING.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE-FLUSH WITH WATER FOR 15 MIN. IF IRRITATION PERSISTS,
CONTACT PHYSICIAN. SKIN-WASH THOROUGHLY WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHING. INHALATION-IF AFFECTED BY VAPOR, GET TO
FRESH AIR. I F BREATHING IS DIFFICULT, SEE PHYSICIAN.INGESTION-DO

NOT INDUCE VOMITING. PRODUCT CONTAINS HYDROCARBONS. CONSULT
PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:133F,56C
Autoignition Temp:Autoignition Temp Text:410F
Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY
CHEMICAL. CLASS B FIRE PROCEDURES.
Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM COMBUSTIBLE
MIXTURES AT OR ABOVE FLASH POINT.
Unusual Fire/Explosion Hazard:NONE KNOWN.

=====

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. CONTAIN THE SPILL.
RECOVER FREE PRODUCT. ABSORB WITH SUITABLE CHEMICAL ABSORBENT FOR
DISPOSAL VIA INCINERATION OR BURIAL IN APPROVED LANDFILL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AMBIENT.
Other Precautions:KEEP AWAY FROM HEAT SOURCES, OPEN FLAMES, AND OTHER
IGNIT

ION SOURCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.

Ventilation:NORMAL ROOM VENTILATION IS USUALLY ADEQUATE. USE FANS OR
OTHER MECHANICAL VENTILATION IN ENCLOSED AREAS.

Protective Gloves:SOLVENT RESISTANT GLOVES RECOMMENDED.

Eye Protection:SAFETY GLASSES RECOMMENDED.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Hea

lth

RCRA HAZARD CLASS: NOT HAZARDOUS. KEEP OUT OF REACH OF CHILDREN.

===== Physical/Chemical Properties =====

HCC:F4

Vapor Pres:1

Spec Gravity:.9631

Solubility in Water: