View NSN Online: https://aerobasegroup.es/nsn/6520-01-394-5421

MINNESOTA MINING MFG CO DENTAL PROD DIV -- 5905WS SCOTCHBOND MULTIPURPOSE PRIMER -- 6520-01-394-5421

============= Product Identification ========================

Product ID:5905WS SCOTCHBOND MULTIPURPOSE PRIMER

MSDS Date:02/26/1997

FSC:6520

NIIN:01-394-5421

Kit Part:Y

MSDS Number: CGKYQ === Responsible Party ===

Company Name: MINNESOTA MINING MFG CO DENTAL PROD DIV

Address:3M CENTER

City:ST PAUL State:MN

ZIP:55144-1000

Coun try:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-1110

CAGE:76381

=== Contractor Identification ===

Company Name: MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000 Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

Company Name: MINNESOTA MINING AND MFG CO DENTAL PRODUCTS DIV

Address:3M CENTER Box:City:SAINT PAUL

State:MN

ZIP:55144-1000 Country:US

Phone:800-364-3577/651-737-6501

CAGE:0K0U5

====== Composition

| Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 43% |
|--|
| Ingred Name:HYDROXYETHYL METHACRYLATE, ETHYLENE GLYCOL METHACRYLATE CAS:868-77-9 RTECS #:OZ4725000 Fraction by Wt: 35-40% |
| Ingred Name:POLYCARBOXYLIC ACID COPOLYMER Fraction by Wt: 10-15% |
| ====================================== |
| Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards A cute and Chronic:EYES: SEVERE IRRITATION. SKIN: ALLERGIC REACTION & MILD IRRITATION. INHALATION: UPPER RESPIRATORY IRRITATION. INGESTION: GI IRRITATION TISSUES & IRRITATION OF THE ORAL MUCOSA. VEHICLES CAN ALTER SKIN ABSORPTION. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION, REDNESS, SWELLING, PAIN, TEARING, CLOUDYNESS, IMPAIRED VISION, BLISTERING, ITCHING, SORENESS, COUGHING, SNEEZING, VOMITING, ABDOMINAL TENDERNESS, NAUSEA, BLOOD IN VOMITUS & B LOOD IN FECES, BLEEDING. |
| ====================================== |
| First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. SKIN: FLUSH W/LARGE AMOUNTS OF WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DRINK 2 GLASSES OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES. |
| ============= Fire Fighting Measures ============= |
| Flash Point:207F |
| ======== Accidental Release Measures ========== |
| Spill Release Procedures:V |
| |

/Information on Ingredients =======

| ENTILATE AREA. COVER W/ABSORBENT MATERIAL. PLACE IN METAL CONTAINER. |
|---|
| ====================================== |
| Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. STORE IN A COOL PLACE. USE W/ADEQUATE VENTILATION. WEAR APPROPRIATE GLOVES WHEN HANDLING THIS MATERIAL. Other Precautions:AVOID EYE/SKIN CONTACT. AVOID PROLONGED BREATHING OF VAPORS. DON'T INGEST. ACRYLATE MAY PENETRATE GLOVES. IF PRIMER CONTACTS GLOVE, REMOVE & DISCARD. WASH HANDS W/SOAP & WATER & THEN RE-GLOVE. |
| ====== Exposure Controls/Personal Protection ======== |
| Protective Gloves:RECOMMENDED Supplemental Safety and Health |
| ========= Physical/Chemical Properties ========== |
| Boiling Pt:B.P. Text:>95F Vapor Pres: |
| |