

R & D METALS & CHEMICALS INC -- WELDING FLUX,SOLDERING LIQUID FORM FLUX --
3439-01-044-4144

===== Product Identification =====

Product ID:WELDING FLUX,SOLDERING LIQUID FORM FLUX

MSDS Date:02/20/1998

FSC:3439

NIIN:01-044-4144

MSDS Number: CGLTN

=== Responsible Party ===

Company Name:R & D METALS & CHEMICALS INC

Address:75 SHEER PLAZA

City:PLAINVIEW

State:NY

ZIP:11803-4205

Country:US

Info Phone Num:

516-694-0920

Emergency Phone Num:516-694-0920

CAGE:56406

=== Contractor Identification ===

Company Name:R & D METALS & CHEMICALS, INC

Address:201C PERIMETER PARK

Box:22533

City:KNOXVILLE

State:TN

ZIP:37922-2233

Country:US

Phone:423-531-6065 / FAX: 423-531-2044

CAGE:56406

===== Composition/Information on Ingredients =====

Ingred Name:HYDROGEN CHLORIDE (HYDROCHLORIC ACID) (SARA 302/313)
(CERCLA)

CAS:7647-01-0

RTECS #:MW4025000

Fraction by Wt: 30 - 45%

Other REC Limits:NONE

RECOMMENDED
OSHA PEL:C 5 PPM
ACGIH TLV:C 5 PPM; 9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ZINC CHLORIDE (SARA 313) (CERCLA)
CAS:7646-85-7
RTECS #:ZH1400000
Fraction by Wt: 15 - 25%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1MG/M3/2STEL(FUME)96
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETIC ACID (CERCLA)
CAS:64-19-7
RTECS #:AF1225000
Fraction by Wt: 2 - 4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9596
EPA Rpt
Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS UNKNOWN.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY
AND GASTROINTESTINAL TRACTS. ACUTE- CORROSIVE. ZINC CHLORIDE CAN
BURN GASTROINTESTINAL TRACT IF INGESTED. MAY CAUSE BURNS IF EYE
CONTACT OCCURS. MAY CAUSE EY
E DAM GE. CAN CAUSE SKIN BURNS. MAY
CAUSE PULMONARY EDEMA IF INHALED. CHRONIC- UNKNOWN.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, BURNS, PAIN, VOMITING, NAUSEA,
BLINDNESS
Medical Cond Aggravated by Exposure:UNKNOWN.

===== First Aid Measures =====

First Aid:CALL A DOCTOR IF SYMPTOMS PERSIST. EYE:IMMEDIATELY FLUSH WITH
WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SEE A DOCTOR.
SKIN:IMMEDIATELY WASH WITH PLENTY OF WAT

ER. INHALED:REMOVE TO FRESH
AIR. PROVIDE CP R/OXYGEN IF NEEDED. ORAL:IF CONSCIOUS, DRINK WATER
OR MILK. GET MEDICAL ATTENTION IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE CARBON DIOXIDE, FOAM OR DRY CHEMICAL. USE WATER
SPRAY TO COOL FIRE EXPOSED CONTAINERS.
Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:WILL RELEAS
E HYDROCHLORIC ACID FUMES UPON
DECOMPOSITION.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. NEUTRALIZE WITH
SODA ASH OR SODIUM BICARBONATE. VENTILATE AREA. TRANSFER TO PROPER
CONTAINER FOR DISPOSAL. WASH SPILL SITE WITH WATER.
Neutralizing Agent:SODIUM BICARBONATE, SODA ASH

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT AND STORE IN

PLASTIC OR GLASS CONTAINERS, AWAY FROM INCOMPATIBLES.
Other Precautions:WASH THOROUGHLY AFTER HANDLING. KEEP OUT OF REACH OF
CHILDREN. AVOID CONTACT WITH EYES AND SKIN. DO NOT BREATHE FUMES.
WASH CLOTHING BEFORE RE-USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHERE ADEQUATE VENTILATION
CONDITIONS EXIST. IF AIRBORNE CONCENTRATION IS HIGH, WEAR A
NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.
Ventilation:USE
ADEQUATE GENERAL OR LOCAL EXHAUST VENTILATION.
Protective Gloves:RUBBER
Eye Protection:CHEMICAL SAFETY GOGGLES
Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER, UNIFORM
Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING,
DRINKING/SMOKING.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:C1
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:B.P. Text:220F,104C

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Vapor Pres:UNKNOWN.

Vapor Density:UNKNOWN.

Spec Gravity:1.34

pH:ACID

Evaporation Rate & Reference:0.7 (N-BUTYL ACETATE=1)

Solubility in Water:UNLIMITED

Appearance and Odor:YELLOW/GREEN LIQUID - PUNGENT ODOR

Percent Volatiles by Volume:64

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALIES, METALS, OXIDIZING OR REDUCING MATERIALS, CYANIDES OR
COMBUSTIBLE MATERIALS

Stability Condit

ion to Avoid:EXCESSIVE HEAT AND COLD

Hazardous Decomposition Products:HYDROCHLORIC ACID, ZINC CHLORIDE
FUMES, ZINC OXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. REUSING OR RECYCLING IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United State

s of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.