View NSN Online: https://aerobasegroup.es/nsn/6830-00-985-7281

AIR PRODUCTS AND CHEMICALS INC. -- ARGON, COMPRESSED -- 6830-00-985-7281

Product ID:ARGON, COMPRESSED

MSDS Date:08/01/1997

FSC:6830

NIIN:00-985-7281

MSDS Number: CGMHH === Responsible Party ===

Company Name: AIR PRODUCTS AND CHEMICALS INC.

Address:7201 HAMILTON BLVD

City:ALLENTOWN

State:PA

ZIP:18195-1501 Country:US

Info Phone Num:800-752-1597 Emergency Phone Num:8 00-523-9374 610-481-7711

CAGE:00742

=== Contractor Identification ===

Company Name: AIR PRODUCTS AND CHEMICALS INC

Address:7201 HAMILTON BLVD

Box:City:ALLENTOWN

State:PA

ZIP:18195-1501 Country:US

Phone:800-345-3148/800-752-1597

CAGE:00742

Company Name: AIR PRODUCTS AND CHEMICALS INC

Address:411 ROTARY STREET

Box:City:HAMPTON

State:VA ZIP:23661 Country:US

Phone:804-826-5430

CAGE:1A996

======= Composition/Information on Ingredients ========

Ingred Name: ARGON

CAS:7440-37-1 Fraction by

Wt: >99.9%
Other REC Limits:NONE
======================================
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ARGON IS NONTOXIC, BUT MAY PRODUCE
SUFFOCATION BY DILUTING OXYGEN IN AIR BELOW LEVELS NECESSARY TO SUPPORT LIFE. OXYGEN LEVELS SHOULD NOT FALL BELOW 19.5%. EXTENSIVE
TISSUE DAMAGE OR BURNS CAN RESULT FROM EXPOSURE TO LIQUID ARGON OR
COLD
ARGON VAPORS.
Explanation of Carcinogenicity:NOT APPLICABLE.
Effects of Overexposure:LOSS OF BALANCE, DIZZINESS, NAUSEA, VOMITING,
UNCONSCIOUSNESS AND DEATH. NOTE! ARGON ASPHYXIATION MAY OCCUR WITHOUT WARNING.
Medical Cond Aggravated by Exposure:NONE KNOWN.
55 to 100 to
======================================
First Aid:INHALATION:REMOVE TO FRESH AIR. GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED. GET PROMPT QUALIFIED MEDICAL HELP.
======================================
hting Measures ====================================
Flash Point:NON-FLAMMABLE
Extinguishing Media:NONFLAMMABLE, INERT GAS. USE APPROPRIATE MEDIA FOR SURROUNDING FIRE.
Fire Fighting Procedures: EVACUATE PERSONNEL. USE WATER SPRAY TO COOL
FIRE EXPOSED CYLINDERS.HMIS SUGGESTS ALWAYS USING A SELF-CONTAINED
BREATHING APPARATUS WHEN FIGHTING A CHEMICAL FIRE.
Unusual Fire/Explosion Hazard:CONTAINER MAY RUPTURE FROM HEAT.
========= Accidental Release Measures ===========
Spill Release P
rocedures:EVACUATE ALL PERSONNEL FROM AFFECTED AREA. USE

rocedures:EVACUATE ALL PERSONNEL FROM AFFECTED AREA. USE APPROPRIATE PROTECTIVE EQUIP.IF LEAK IS IN CONTAINER VALVE, CONTACT YOUR CLOSEST SUPPLIER OR CALL 800-424-9300(CHEMTREC). Neutralizing Agent:NONE.

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED AREA. KEEP CYLINDERS UPRIGHT & SECURED. SEGREGATE FULL/EMPTY CYL. KEEP CYLINDERS AWAY FROM HEAT SOURCES.

Other Precautions: COMPRESSED GAS CYL

INDERS SHOULD NOT BE REFILLED EXCEPT BY QUALIFIED PRODUCERS OF COMPRESSED GASES. USE A CHECK VALVE OR TRAP IN THE DISCHARGE LINE TO PREVENT HAZARDOUS BACK FLOW INTO THE CYLINDER. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: USE SELF-CONTAINED BREATHING APPARATUS IN OXYGEN- DEFICIENT ATMOSPHERE, CAUTION! RESPIRATORS WILL NOT FUNCTION. USE MAY RESULT IN ASPHYXIATION. Ventilation:MECHANICAL Protective Gloves:LEATHER WORK GLOVES Eye Protection: SAFETY GOGGLES OR GLASSES Other Protective Equipment: SAFETY SHOES Work Hygienic Practices: USE IN A WELL VENTILATED AREA. Supplemental Safety and Health NONE ======== Physical/Chemical Properties =========== HCC:G3 Boiling Pt:B.P. Text:-302F/-185C Vapor Density:0.104 @68F Spec Gravity:1.38 Evaporation Rate & Deference: GAS Solubility in Water:SLIGHT Appearance and Odor:BOTH GAS AND LIQUID ARE COLORLESS AND ODORLESS. Percent Volatiles by Volume:100 ==== Stability and Reactivity Data ======== Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid: NONE

NONE

Hazardous Decomposition Products: NONE

======= Disposal Considerations ===========

Waste Disposal Methods: DO NOT ATTEMPT TO DISPOSE OF WASTE OR UNUSED QUANTITIES. RETURN IN THE SHIPPING CONTAINER PROPERLY LABELED, WITH VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE TO YOUR SUPPLIER. CALL SUPPLIER FOR

## EMERGENCY DISPOSAL ASSISTANCE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.