

CASTROL NORTH AMERICA -- BRAYCOTE 120 -- 8030-00-281-2338

===== Product Identification =====

Product ID:BRAYCOTE 120

MSDS Date:05/01/1994

FSC:8030

NIIN:00-281-2338

MSDS Number: CGNDR

=== Responsible Party ===

Company Name:CASTROL NORTH AMERICA

Address:16715 VON KARMAN AVE. SUITE 230

City:LOVINE

State:CA

ZIP:92714

Country:US

Info Phone Num:714-660-9414

Emergency Phone Num:714-660-9414

Preparer's Na

me:RICHARD DEVICARIIS

CAGE:2R128

=== Contractor Identification ===

Company Name:CASTROL INDUSTRIAL NORTH AMERICA INC SPECIALTY PRODUCTS
DIV

Address:1001 WEST 31ST STREET

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-1280

Country:US

Phone:800-621-2661/ FAX: 630-241-4140

CAGE:2R128

Company Name:CASTROL INDUSTRIAL NORTH AMERICA INC.

Address:5511 DISTRICT BLVD

Box:City:LOS ANGELES

State:CA

ZIP:90040

Country:US

Phone:213-890-4420

CAGE:98308

===== Composition/Information on Ingredients =====

=====

Ingred Name:2-AMINO-2-METHYL-1-PROPANOL

CAS:124-68-5

RTECS #:UA5950000

Fraction by Wt: 100F,>38C

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM & WATER.

Fire Fighting Procedures:USE WATER AS FOG OR SPRAY TO COOL FIRE EXPOSED CONTAINERS. USE SCBA IN CONFINED AREA. WARNING: COMBUSTIBLE MATERIAL.

Unusual Fire/Explosion Hazard:EMPTY CONTAINERS RETAIN RESIDUE/VAPORS WHICH CAN IGNITE EXPLOSIVELY. DONT CUT, DRILL, WELD ON OR NEAR FULL OR EMPTY CONTAINERS.

=====

===== Accidental Release Measures =====

Spill Release Procedures:DONT PERMIT PRODUCT TO ENTER SEWERS, STREAMS OR WATERWAYS. REMOVE IGNITS. DIKE SPILL. STOP LEAK. ABSORB W/DRY INERT MATERIAL. STORE IN CLOSED CONTAINER UNTIL DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:MAINTAIN AMBIENT TEMPERATURES. KEEP CONTAINERS TIGHTLY CLOSED. DONT STORE NEAR HEAT OR STRONG OXIDANTS. MAINTAIN ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR OR SUPPLIED-AIR RESPIRATOR EQUIPMENT AS REQUIRED.

Ventilation:MECHANICAL, GENERAL AND/OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV >60 13/MIN RECOMMENDED.

Protective Gloves:NEOPRENE

Eye Protection:CHEMICAL SPLASH GOGGLES/SAFETY GLASSES

Other Protective Equipment:IMPERVIOUS GARMENTS AS REQUIRED

Work Hygienic Practices:WASH CONTAM CLOTHES BEFORE REUSE OR DISCARD.

DONT EAT, SMOKE WHILE IN CONTACT W/PRODUCT. WASH THOROUGHLY AFTER USE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:270F,132C

Vapor Density:3.5

Spec Gravity:0.87

Evaporation Rate & Reference:0.33

Solubility in Water:COMPLETE

Appearance and Odor:AMBER LIQUID, CHARACTERISTIC SOLVENT ODOR.

Percent Volatiles by Volume:65.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: TOXIC MATERIAL, CO, CO₂ & VARIOUS HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods: ALL RECOVERED MATERIAL SHOULD BE PACKED, LABELED, TRANSPORTED & DISPOSED OF OR RECLAIMED IN CONFORMANCE W/GOOD ENGINEERING PRACTICES. DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.