

SAFETY COATING -- TT-P-115 F TYPE II CLASS I LEAD-FREE YELLOW -- 8010-00-900-3650

===== Product Identification =====

Product ID:TT-P-115 F TYPE II CLASS I LEAD-FREE YELLOW

MSDS Date:06/24/1997

FSC:8010

NIIN:00-900-3650

MSDS Number: CGNHG

=== Responsible Party ===

Company Name:SAFETY COATING

Address:HIGHWAY 59 NORTH

Box:399

City:FOLEY

State:AL

ZIP:36536

Country:US

Info Phone Num:334-943-1638

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:KO024

=== Contractor

Identification ===

Company Name:SAFETY COATING

Address:HIGHWAY 59 NORTH

Box:399

City:FOLEY

State:AL

ZIP:36536

Country:US

Phone:334-943-1638

CAGE:KO024

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM NAPHTHA (SARA 313)

CAS:64742-89-8

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:100 PPM

Ingred Name:TOLUENE (TOLUOL) (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 4-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:CALCIUM CARBONATE
CAS:1317-65-3
RTECS #:EV9580000
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:10 MG/M3

Ingred Name:PERCHLOROETHYLENE (CERCLA)
CAS:127-18-4
RTECS #:KX3850000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:25 PPM
ACGIH TLV:25 PPM
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name
:ACETONE (SARA 313) (CERCLA)
CAS:67-64-1
RTECS #:AL3150000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:750 PPM
ACGIH TLV:750 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ORGANO MONTMORILLIONITE (NON-HAZARDOUS INGREDIENTS)
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

Ingred Name:SHORT OIL RESIN SOLIDS (NON-HAZARDOUS INGREDIENTS)
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

Ingred Name:HANSA YELLOW X (NON-HAZARDOUS

INGREDIENT)
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: STINGING, TEARING, REDNESS,
SWELLING. SKIN: DRYNESS, IRRIT. INHAL: NASAL AND RESPIRATORY IRRIT,
DIZZY, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUS, DEATH.
INGEST: GI IRRIT,
NAUSEA, VOMIT. AS PIRATION INTO LUNGS CAN CAUSE
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. CHRONIC: INHAL:
LIVER/KIDNEY/BRAI DAMAGE.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER. SKIN: WASH W/SOAP AND WATER. WASH CLOTHES
BEFORE REUSE. INHAL: REMOVE TO FRESH AIR. INGEST: DONT INDUCE
VOMIT. GET MED AID.

===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:30 TO 40F
Lower Limits
:1.0
Upper Limits:7.0
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL AND HALON.
Fire Fighting Procedures:USE SCBA W/FULL-FACE PIECE OPERATED IN
PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE.
Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT SOURCES. VAPORS ARE
HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND. EMPTY CONTAINERS
(W/RESIDUE) ARE FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP W/ABSORBENT MATERIAL AND

DEPOSIT IN A
SAFE CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DONT PUT EMPTY OR FULL CONTAINERS NEAR
ANY HEAT SOURCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED SCBA.
Ventilation:LOCAL EXHAUST OR MECHANICAL (GENERAL)
Protective Gloves:REQUIRED
Eye Protection:REQUIRED
Other Protective Equipment:IMPERVIOUS CLOTHES AND SHOES
Work Hygienic Practices:WASH HA
NDS THOROUGHLY AFTER USE.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:200 TO 210F
Melt/Freeze Pt:M.P/F.P Text:LIQUID
Vapor Pres:60 TO 70
Vapor Density:3.00-4.00
Spec Gravity:1.45 TO 1.55
Evaporation Rate & Reference:2-3 (BUAC)=1
Solubility in Water:NEGLIGIBLE
Appearance and Odor:YELLOW, PETROLEUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:Y
ES
WATER
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:IN POSTED TOXIC LANDFILL ACCORDING TO STATE,
LOCAL AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants thi

s information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.