

ANDPAK-EMA INC ZIP-CHEM PRODUCTS INC DIV -- MOLY OIL SPRAY,D-5330 NS,63 2060 --
9150-00-163-9036

===== Product Identification =====

Product ID:MOLY OIL SPRAY,D-5330 NS,63 2060

MSDS Date:03/28/1996

FSC:9150

NIIN:00-163-9036

MSDS Number: CGWZK

=== Responsible Party ===

Company Name:ANDPAK-EMA INC ZIP-CHEM PRODUCTS INC DIV

Address:1860 DOBBIN DR

City:SAN JOSE

State:CA

ZIP:95133

Country:US

Info Phone Num:408-729-0291

Emergency Phone Num:408-729-0291/800-424-93

00(CHEMTREC)

Preparer's Name:JASON SMITH

CAGE:EO371

=== Contractor Identification ===

Company Name:ANDPAK-EMA INC ZIP-CHEM PRODUCTS INC DIV

Address:1860 DOBBIN DR

Box:City:SAN JOSE

State:CA

ZIP:95133

Country:US

Phone:408-729-0291/272-8007

CAGE:EO371

Company Name:ANDPAK-EMA INC, ZIP-CHEM PRODUCTS DIV

Address:400 JARVIS DR

Box:City:MORGAN HILL

State:CA

ZIP:95037

Country:US

Phone:408-782-2500/ 800-646-2661

CAGE:8E913

===== Composition/Information on Ingredients =====

Ingred Na

me:1,1-DIFLUOROETHANE/ETHANE, 1,1-DIFLUORO

CAS:75-37-6

RTECS #:K11410000

Fraction by Wt: 35%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYL ETHER

CAS:115-10-6

RTECS #:PM4780000

Fraction by Wt: 55%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS, LUNG,
HEART &

GI TRACT. ACUTE- MAY CAUSE EYE IRRITATION. HARMFUL IF
INHALED. HIGH CONCENTRATIONS MAY CAUSE HEART IRREGULARITIES,
UNCONSCIOUSNESS, EVEN DEATH. SKIN CONTACT WITH LIQUID CAUSES
FROSTBITE. HARMFUL IF SWALLOWED. MAY CAUSE LIVER EFFECTS. CHRONIC-
UNKNOWN.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, DROWSINESS, DIZZINESS, NAUSEA,
VOMITING, HEADACHE, WEAKNESS, ABDOMINAL DISCOMFORT, DRYNESS OF
SKIN, ABDOMINAL PAIN, TEARING, BLURRED VISION, UNCONSCIOUSNESS,
DEATH

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING
DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT, HEART, CNS MAY HAVE
INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:FLUSH WITH
WATER. TREAT FOR FROSTBITE IF NEEDED. EYE:IMMEDIATELY FLUSH WITH
WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. INHALED:REMOVE TO FRESH
AIR. PROVIDE OXYGEN/CPR IF NEEDED. ORAL:NOT CONSIDERED A POTENTIAL
ROUTE OF EXPOSURE. CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:FLAMMABLE AEROSOL

Lower Limits:3.4%

Upper Limits:18.0%

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, SAND, ALCOHOL FOAM,
DRY CHEMICAL. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY.

Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA
WITHOUT PROPER PROTECTIVE EQUIPMENT AND

NIOSH-APPROVED
SELF-CONTAINED BREATHING APPARATUS (PRESSURE DEMAND).
Unusual Fire/Explosion Hazard:AEROSOL CANS UNDER PRESSURE AND CONTAINS
FLAMMABLE GAS. CANS MAY RUPTURE OR EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES
OF IGNITION. VENTILATE AREA. REMOVE LEAKING CONTAINER OUTDOOR/UNDER
THE HOOD. SOAK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND,
VERMICULITE. PLACE I
N CONTAINER. PREVENT LIQUID FROM ENTERING
SEWERS.
Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, VENTILATED AREA AWAY
FROM IGNITION SOURCES & INCOMPATIBLES. KEEP OUT OF REACH OF
CHILDREN. DO NOT STORE ABOVE 120F/IN DIRECT SUNLIGHT.
Other Precautions:FLAMMABLE. EMPTY CONTAINERS RETAIN RESIDUE. FOLLOW
ALL PRECAUTIONS. DO NOT GET IN EYES. DO NOT BREATHE VAPOR OR MIST.
AVOID PR
OLONGED OR REPEATED SKIN CONTACT. WASH THOROUGHLY AFTER
HANDLING. DO NOT T AKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF WORKING IN CONFINED AREAS, IF EXCESSIVE
MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES EXCEED RECOMMENDED
PERMISSIBLE EXPOSURE LIMITS (PEL), WEAR NIOSH-APPROVED
SELF-CONTAINED BREATHING APPARATUS.
Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF)
VENTILATION TO MAINTAIN E
XPOSURE BELOW TLV(S).
Protective Gloves:BUTYL IF REPEATED CONTACT POSSIBLE
Eye Protection:SAFETY GLASSES/GOGGLES RECOMMENDED
Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER,
INDUSTRIAL-TYPE WORK CLOTHING, APRON
Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING,
DRINKING/SMOKING.
Supplemental Safety and Health
FLAMMABLE AEROSOL AS DETERMINED BY THE FLAME PROJECTION TEST. CONTAINS
MORE THAN 45% BY

WEIGHT FLAMMABLE COMPONENTS.

===== Physical/Chemical Properties =====

HCC:V3

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:=-25.C, -13.F

Vapor Density:>1

Spec Gravity:0.8

VOC Pounds/Gallon:405

VOC Grams/Liter:3.38

Viscosity:NOT KNOWN

Evaporation Rate & Reference:>1 (ETHER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS LIQUID - ETHEREAL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:Y

ES

ALKALI OR ALKALINE EARTH METALS-POWDERED ALUMINUM, ZN, BE, ETC.

Stability Condition to Avoid:HEAT, SPARKS, FLAMES, RED HOT SURFACES AND
OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:HYDROCHLORIC AND HYDROFLUORIC ACIDS
AND POSSIBLY CARBONYL HALIDES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE IN ACCORDANCE WITH ALL LOCAL,
STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.
WATER RUNO
FF CAN CAUSE ENVIRONMENTAL DAMAGE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this info

rmation to their
particular situation.