CORROSION TECHNOLOGIES CORP. -- CORROSION X MARINE -- 8030-01-437-5687

Product ID: CORROSION X MARINE

MSDS Date:12/13/1996

FSC:8030

NIIN:01-437-5687

MSDS Number: CGXWY === Responsible Party ===

Company Name: CORROSION TECHNOLOGIES CORP.

Box:551625 City:DALLAS State:TX

ZIP:75355-1625 Country:US

Info Phone Num:972-271-7361 FAX 972-278-9721

Emergency Phone Num:972-271-7361

CAGE:0VJ14

=== Contractor Identification ===

Company Name

:CORROSION TECHNOLOGIES CORP.

Box:551625 City:DALLAS State:TX

ZIP:75355-1625 Country:US

Phone:972-271-7361 FAX 972-278-9721

CAGE:0VJ14

======= Composition/Information on Ingredients ========

Ingred Name:BASE STOCK

CAS:72623-85-9 Fraction by Wt: 72.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3

Ingred Name: HYDROCARBON SOLVENT

CAS:72623-83-7 Fraction by Wt: 9.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM

Ingred Name: ZINC DINONYLNAPHTHALENE SULFONATE

CAS:8008-20-6

R

TECS #:OA5500000				
Fraction by Wt: 1.0% Other REC Limits:NONE RECOMMENDED				
Other NEO Elithis. NOINE NEOOIVIIVIENDED				
======================================				
LD50 LC50 Mixture:(SEE HEALTH HAZARDS) Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRIT, RED, WATERY. SKIN: LD50 IS 2000 MG/KG. DEFATTING, DERMATITIS, DRYING, CHAPPED. INHAL: LC50 = 5000 PPM RAT. NOSE/THROAT/UPPER RESPIRATORY TRACT IRRIT, DIZZY				
HEADACHE, NAUSEA. INGEST: LD50 1400 MG/KG (RAT ORAL). SLIGHTLY TOXIC, HARMFUL, FATAL, MOUTH/THROAT/ESPHAGUS IRRIT, NAUSEA, VOMIT, GI UPSET, DIARRHEA.				
======================================				
First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, LIFTING LIDS. SKIN: REMOVE EXCESS BY WIPING, THEN WASH W/SOAP & WATER. WASH SOILED CLOTHES & SHOES W/DETERGENT. INHAL: REMOVE TO FRESH AIR. CPR IF NEEDED. INGEST: DO NT INDUCE VOMIT. DRINK 1/2 PINT OF MILK. CALL DR. IN ALL CASES, GET MED AID.				
======================================				
Flash Point Method:COC Flash Point:>285F,>141C Lower Limits:1.0 Upper Limits:6.0 Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER SPRAY. Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT W/SCBA. COVER W/EXTINGUISHING AGENT. DONT SPRAY W/WATER USING DIRECT STREAM INTO BURNING LIQIUD, MAY SPREAD FIRE. Unusual Fire/Explosion Hazard:TREAT AS A COMBUSTIBLE LIQUID. DONT FLAME C UT, DRILL, WELD EMPTY CONTAINERS. USE WATER SPRAY/MIST TO COOL THE FIRE.				
======== Accidental Release Measures =========				
Spill Release Procedures:ELIMINATE IGNITS. STOP FLOW BY MEANS OF DIKE OR BARRICADE. ABSORB SMALL SPILLS BY USING DRY CLAY OR COMMERCIAL ABSORBENT. COLLECT RESIDUE IN SUITABLE CONTAINER FOR DISPOSAL.				
MATERIAL MAY BE WASHED IN STEEL FLOOR DRAINS EQUIPPED W/OIL INTERCEPTOR.				

Respiratory Protection: USE APPROVED ORGANIC MIST RESPIRATOR.

Ventilation: SUFFICIENT VENTILATION BY GENERAL OR MECHANICAL MEANS TO INSURE THAT LEVELS ARE KEPT BELOW COMBUSTIBLE LIMITS.

Eye Protection: FACE MASK OR GOGGLES

Other Protective Equipment: APPLY MILD HAND CREAM IF HANDS BECOME DRY OR CHAPPED.

Work Hygienic Practices: WASH FACE & HANDS W/SOAP & WATER AFTER USE & BEFORE EATING, SMOKING, USING RESTROOM.

Supplemental Safety and Health

NK

=======	=======	Physical/Chemical
Properties	========	=======

Boiling Pt:B.P. Text:>212F,>100C Melt/Freeze Pt:M.P/F.P Text:NA Vapor Pres:8 @ 25C

Vapor Pres:8 @ 25C
Vapor Density:>1 (AIR=1)
Spec Gravity:0.877 (WATER=1)

Evaporation Rate & Dr. Reference: 91.0

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS SUCH AS LIQUIDS, COMPRESSED OXYGEN, PEROXIDES OR CHLORINES.

Hazardous Decomposition Products:BURNING PRODUCTS NORMALLY BI-PRODUCTS OF COMBUSTION INCLUD

E: CARBON MONOXIDE, PHENOLS OR PETROLEUM PRODUCTS.

	Disposal Considerations	
--	--------------------------------	--

Waste Disposal Methods:DISPOSE OF IN APPROVED LANDFILL SITE OR INCINERATE AT A LICENSED WASTE RECLAIMMING FACILITY. LIQUID WASTE MAY BE REMOVED BY MEANS OF LICENSED RECLAIMER UNDER USED OIL CLASSIFICATION. FOLLOW ALL FEDERA L, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for

use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.