

CSD INC -- A-A-857-B -- 8010-00-160-5788

=====
Product Identification
=====

Product ID:A-A-857-B
MSDS Date:12/04/1996
FSC:8010
NIIN:00-160-5788
MSDS Number: CHKGF
=== Responsible Party ===
Company Name:CSD INC
Address:5 HACKBURRY LANE
Box:3087
City:CONROE
State:TX
ZIP:77305
Country:US
Info Phone Num:409-756-1065
Emergency Phone Num:409-756-1065
CAGE:4N760

==== Contractor Identification ===

Company
Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC
Address:2210 HACKBERRY LN
Box:687
City:CONROE
State:TX
ZIP:77305
Country:US
Phone:409-756-1065
CAGE:4N760

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ACETATE (CERCLA)(SARA 313)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: NA
Other REC Limits:NONE RECOMMENDED
OSHA PEL:150 PPM
ACGIH TLV:20 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA 313) (CERCLA)
CAS:108-88-3
RTECS #:XS525000

0
Fraction by Wt: 17.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LIGHT ALIPHATIC SOLVENT NAPHTHA (SARA 313)
CAS:64742-89-8
Fraction by Wt: NA
Other REC Limits:NONE RECOMMENDED
OSHA PEL:500 PPM
ACGIH TLV:300 PPM

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 12.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM/STEL 300
ACGIH TLV:200 PPM/STEL
300
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: NA
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM/STEL 500
ACGIH TLV:400 PPM/STEL 500

Ingred Name:N-BUTYL ALCOHOL (SARA 313) (CERCLA)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 9.0%
Other REC Limits:50 PPM CEILING
OSHA PEL:100 PPM SKIN
ACGIH TLV:50 PPM SKIN
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE/SKIN: IRRITATION, DEFATTING,
DERMATITIS, ABSORPTION THROUGH SKIN, REDNESS, TEARING, BLURRED
VISION, BURNS. INHAL: ANESTHETIC, IRRITANT, SERIOUS CNS DEPRESSION,
KIDNEY, BLOOD, NERVES, LUNG DAMAGE. INGEST; HARMFUL OR FATAL,
ABDOMINAL IRRIT, NAUSEA, VOMITING, DIARRHEA.
Medical Cond Aggravated by Exposure:SEVERE SKIN, LIVER O
R KIDNEY
PROBLEMS.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER 15 MINUTES. GET MED AID. SKIN: REMOVE
CONTAM CLOTHES. WASH W/SOAP & WATER. WASH CLOTHES BEFORE REUSE.
DISCARD SHOES. INHAL: GET FRESH AIR. GIVE OXYGEN. GIVE ARTIFICIAL
RESPIRATION. GET IMMEDIATE MED AID. INGEST: GET IMMEDIATE MED AID.
DONT INDUCE VOMITING. KEEP PERSON LYING DOWN/WARM. VOMITING MAY
LEAD TO PNEUMONITIS WHICH CAN BE FATAL.

=====

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:19.4F,-7.0C
Autoignition Temp:Autoignition Temp Text:290C
Lower Limits:1.6
Extinguishing Media:NFPA CLASS B EXTINGUISHERS, CO2/FOAM. FOR CLASS I B
LIQUID FIRES.
Fire Fighting Procedures:WATER SPRAY INEFFECTIVE, BUT EFFECTIVE TO COOL
CONTAINERS. USE FOG NOZZLES IF WATER IS USED. DONT ENTER FIRE SPACE
W/O FULL BUNKER GEAR. POSITIVE PRESSURE SCBA.
Unusual Fire/Explosion Hazard:VAPORS CAN CAUSE FLASH
FIRE. CLOSED
CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT. EMPTY CONTAINER
VERY HAZARDOUS.

===== Accidental Release Measures =====

Spill Release Procedures:STOP SPILL AT SOURCE. DIKE/CONTAIN. USE
ABSORBENT. MOP/DISPOSE. EVACUATE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM IGNITS/OXIDIZERS. USE
ADEQUATE VENT. AVOID VAPOR/MIST. NO SKIN/EYE CONTACT. AVOID FREE
FALL LIQ. GROU

ND CONTAINERS WHEN TRANSFERING.

Other Precautions:DONT FLAME CUT/SAW/DRILL/BRAZE/WELD ON CNTNR. EMPTY CNTNR HAZARDOUS! VAPORS MAY IGNITE EXPLOSIVELY. PREVENT VAPOR BUILD-UP. DONT STORE >49C. STORE LG AMTS IN STRUCTURES PER OSHA CLASS 1B LIQUIDS. KEEP TIGHTLY CLOSED/UPRIGHT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF >25PPM USE NIOSH APPROVED POSITIVE PRESSURE SCBA.

Ventilation:LOCAL EXHAUST, MECHANICAL (GENERAL)

Protective Glo

ves:YES

Eye Protection:STANDARD GOGGLES OR FACE SHIELD

Other Protective Equipment:APRON, IMPERVIOUS FOOTWARE.

Supplemental Safety and Health

NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:173 TO 262F

Vapor Pres:28.2

Vapor Density:3.0 AIR=1

Spec Gravity:0.824

VOC Grams/Liter:6.86

Solubility in Water:APPRECIABLE

Appearance and Odor:LIQUID, WATER - WHITE, KETONE ODOR

=====
===== Stability and Reactivity Data =====

Stability Indic

ator/Materials to Avoid:YES

STRONG OXIDIZERS (PERMANGANATES, CHROMATES, PEROXIDES)

Stability Condition to Avoid:KEEP FROM IGNITABLES

Hazardous Decomposition Products:CO, CO2.

=====
===== Disposal Considerations =====

Waste Disposal Methods:RECYCLE/DISPOSE PER FEDERAL, STATE, LOCAL REGULATIONS.

=====
===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated

for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.