

AMERICAN SAFETY TECHNOLOGIES INC -- MS-7C/MS-10C HARDENER COMPONENT --
8010-01-397-3986

===== Product Identification =====

Product ID:MS-7C/MS-10C HARDENER COMPONENT

MSDS Date:06/14/1996

FSC:8010

NIIN:01-397-3986

Kit Part:Y

MSDS Number: CHMGN

=== Responsible Party ===

Company Name:AMERICAN SAFETY TECHNOLOGIES INC

Address:565 EAGLE ROCK AVE

City:ROSELAND

State:NJ

ZIP:07068

Country:US

Info Phone Num

:201-403-2600

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:J HERMELE

CAGE:AMSAT

=== Contractor Identification ===

Company Name:AMERICAN SAFETY TECHNOLOGIES INC

Address:565 EAGLE ROCK AVE

Box:City:ROSELAND

State:NJ

ZIP:07068

Country:US

Phone:973-403-2600

CAGE:88444

Company Name:AMERICAN SAFETY TECHNOLOGIES INC.

Address:565 EAGLE ROCK AVENUE

City:ROSELAND

State:NJ

ZIP:07068

Country:US

Phone:800-424-9300

CAGE:AMSAT

===== Composition/Information on Ingredients =====

Ingred Name:POLYAMIDE/EPOXY ADDUCT
CAS:68424-41-9
Fraction by Wt: 60-80%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:N-BUTYL ALCOHOL (SARA 313) (CERCLA)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 20-35%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:AMIDOAMINE RESIN
CAS:68443-08-3
Fraction by Wt: 5-10%
OSHA PEL:N/K
ACGIH TLV:N/K

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: CAUSES SEVERE IRRITATION OR BURNS. MAY CAUSE PERMANENT VISUAL IMPAIRMENT. SKIN: CAUSES SEVERE IRRITATION OR BURNS. MAY BE ABSORBED THROUGH SKIN IN HARMFUL AMOUNTS. INHAL: MAY CAUSE UPPER RESPIRATORY TRACT IRRITATION. INGEST: MAY CAUSE BURNS OF MOUTH AND THROAT. CONTAINS MATERIAL THAT MAY BE SLIGHTLY TOXIC.

Explanation

of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:IRRITATION, SENSITIZATION AND DERMATITIS.

Medical Cond Aggravated by Exposure:ALLERGY, ECZEMA AND OTHER SKIN CONDITIONS.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH CONTACT AREA WITH MILD SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST

CONSULT A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE LARGE QUANTITIES OF WATER TO DILUTE. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>100F,>38C

Lower Limits:2.0%

Upper Limits:12.0%

Extinguishing Media:DRY CHEMICAL, CHEMICAL FOAM, CARBON DIOXIDE OR WATER.

Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . REMOVE ALL SOURCES OF IGNITION.

Unusual F

ire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE TOXIC.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. DIKE SPILL. ABSORB WITH INERT MATERIAL AND COLLECT FOR DISPOSAL. FLUSH CONTAMINATED AREA WITH DILUTE (5%) ACETIC ACID AND COLLECT RINSATE FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling an

d Storage Precautions:AVOID ALL PERSONAL CONTACT. DO NOT EXCEED 110F/43C IN STORAGE AREA. GROUND AND BOUND METAL CONTAINERS FOR LIQUID TRANSFER TO AVOID STATIC SPARKS.

Other Precautions:A SAFETY SHOWER AND EYE WASH FACILITY SHOULD BE AVAILABLE TO EMPLOYEES. IMMEDIATELY REMOVE AND THOROUGHLY LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRI

DGE IF REQUIRED.

Ventilation:EXPLOSION-PROOF MECH VENT & LOC EXHST ARE REC. MECH EXHST IS NOT REC AS SOLE MEANS OF CONTROLLING EMPLOYEE EXPOSURE.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS(SUPDAT)

Other Protective Equipment:ANSI APPRVD EMER EYE WASH & DELUGE SHOWER . IN OPERATIONS WHERE CONTACT MAY OCCUR, COVERALLS, APRON AND (SUPDAT)

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

OTHER PROT EQUIP: IMPE

RVIOUS FOOT COVERING ARE RECOMMENDED. EYE PROT: AND FULL LENGTH FACESHIELD .

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>240F,>116C

Vapor Pres:4.3

Vapor Density:2.6

Spec Gravity:0.96

Evaporation Rate & Reference:0.45 (BUTYL ACETATE = 1)

Solubility in Water:PARTIALLY SOLUBLE

Appearance and Odor:AMBER LIQUID, SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG

OXIDIZING AGENTS.

Stability Condition to Avoid:EXCESSIVE HEAT.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES AND OXIDES OF NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:THIS PRODUCT, IF DISPOSED AS SHIPPED, MEETS EPA CRITERIA OF A HAZARDOUS WASTE AS SPECIFIED IN 40 CFR 261 ON THE BASIS OF IT'S IGNITABILITY. DISPOSE OF IN A LICENSED HAZARDOUS WASTE FACILITY IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their part

icular situation.