TEXACO REFINING AND MARKETING INC. -- 26412 URSA SUPER PLUS MOTOR OILS 02112 SAE 30 -- 9150-00-189-6729

============= Product Identification ========================

Product ID:26412 URSA SUPER PLUS MOTOR OILS 02112 SAE 30

MSDS Date:12/16/1997

FSC:9150

NIIN:00-189-6729

MSDS Number: CHQGW === Responsible Party ===

Company Name: TEXACO REFINING AND MARKETING INC.

Address:1111 RUSK STREET

City:HOUSTON

State:TX

ZIP:77002-3310 Country:US

Info Phone Num:800-782-7852 Emergency Phone Num:914-831 -3400, CHEMTREC 800-424-9300

CAGE:2R503

=== Contractor Identification ===

Company Name: TEXACO INC CORPORATE HQ

Address:2000 WESTCHESTER AVE

City:WHITE PLAINS

State:NY ZIP:10604 Country:US

Phone:914-253-4000

CAGE:59595

Company Name: TEXACO LUBRICANTS

CAGE:TEXLU

Company Name: TEXACO REFINING AND MARKETING INC

Address:1111 RUSK ST Box:City:HOUSTON

State:TX

ZIP:77002-3310 Country:US

Phone:713-650-5206

CAGE:2R503

====== Composition/Information on Ingredients ========

Ingred Name:MINERAL

OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED (MILD), HEAVY PARAFFINIC

CAS:64742-65-0

RTECS #:PY8038500 Fraction by Wt: 65-80.9%

Other REC Limits:5 MG/M3 (OIL MIST)

Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED

(MILD), HEAVY PARAFFINIC

CAS:64742-54-7 RTECS #:PY8035500 Fraction by Wt: 20-35%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name: HYDROTREATED MIDDLE PETROLEUM DISTILLATE

CAS:64742-46-7 RTECS #:JN9379645

Fraction b y Wt: 3-10%

Other REC Limits: NONE RECOMMENDED

Ingred Name: DISPERSANT MODIFIED POLYOLEFIN AMIDE ALKYLENEAMINE

Fraction by Wt: 1-3%

Other REC Limits: NONE RECOMMENDED

Ingred Name: SOLVENT REFINED HYDROTREATED RESIDUAL OIL

CAS:64742-57-0 Fraction by Wt: 1-3%

Other REC Limits: NONE RECOMMENDED

========== Hazards Identification ================

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5000 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO

IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION OF VERY LARGE
CONCENTRATIONS OF VAPORS/MISTS MAY CAUSE IRRITATION OF NOSE/THROAT
& CNS EFFECTS. CONTACT MAY CAUSE SKIN & EYE IRRITATION. IF MORE
THAN SEVERAL MOUTHFULS ARE SWALLOWED, GI TRA CT IRRITATION MAY

OCCUR. CHRONIC: NO ADVERSE EFFECTS HAVE BEEN REPORTED.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexpo

sure:INHALED-IRRITATION OF NOSE & THROAT, HEADACHE,
NAUSEA, DROWSINESS. EYES-IRRITATION, DISCOMFORT. SKIN-IRRITATION,
DISCOMFORT, LOCAL REDNESS, SWELLING. INGESTED-ABDOMINAL DISCOMFORT,
NAUSEA, DIARRHEA. E XPOSURE TO HYDROGEN SULFIDE-IRRITATION OF EYES
& RESPIRATORY TRACT, HEADACHE, DIZZINESS, NAUSEA, VOMITING,
DIARRHEA.

Medical Cond Aggravated by Exposure:REPEATED SKIN CONTACT MAY AGGRAVATE EXISTING DERMATITIS.

 First Aid Measures	

First Aid:IN ALL CASES GET MEDICAL ATTENTION. EYES- FLUSH WITH WATER FOR 15 MINUTES. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH MILD SOAP & WATER. INHALED-REMOVE TO FRESH AIR. ADMINISTER OXYGEN OR ARTIFICIAL R ESPIRATION AS NEEDED. INGESTED-IF MORE THAN SEVERAL MOUTHFULS ARE SWALLOWED, GIVE 2 GLASSES OF WATER.

Flash Point Method:COC Flash Point:>400F,>204C Lower Limits:NOT GIVEN Upper Limits:NOT GI

VEN

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM. WATER MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER. Unusual Fire/Explosion Hazard:HYDROGEN SULFIDE MAY BE RELEASED IF OVERHEATED.

======== Accidental Release Measures =============

Spill Release Procedures: VENTILATE AREA. AVOID BREATHING VAPOR. WEAR APPROPRIATE PERSONAL PROTECTIVE GEAR.

CONTAIN SPILL. WIPE UP OR

ABSORB WITH INERT MATERIAL AND SHOVEL UP. PREVENT ENTRY INTO WATERWAYS & SEWERS. AVOID CONTA CT WITH SKIN & CLOTHES.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

============ Handling and Storage ==============

Handling and Storage Precautions:WATER CONTAMINATION SHOULD BE AVOIDED.
MINIMIZE TIME OF EXPOSURE TO HIGH TEMPERATURES. STORE IN A COOL,
DRY PLACE AWAY FROM STRONG OXIDIZING AGENTS.

Other Precautions: MINIMIUM FEASIBLE HA

NDLING TEMPERATURES SHOULD BE MAINTAINED.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION AS REQUIRED TO MAINTAIN EXPOSURE LEVELS.

Protective Gloves:NITRI

LE IF REQUIRED.

Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices: WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

DRY CLEANING OF CONTAMINATED CLOTHING MAY BE MORE EFFECTIVE THAN NORMAL LAUNDERING. INFORM INDIVIDUALS

RESPONSIBLE FOR CLEANING OF

POTENTIAL HAZARDS ASSOCIATED WITH HANDLING CONTAMINATED CLOTHING.

======== Physical/Chemical Properties ==========

HCC:V6

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Decomp Temp:Decomp Text:NOT GIVEN

Vapor Pres:NOT GIVEN Vapor Density:NOT GIVEN Spec Gravity:0.88 - 0.91 Viscosity:45-215 CST

Evaporation Rate & Dr. Reference: NOT GIVEN

Solubility in Water: NOT GIVEN

Appearance and Odor:BRIGHT & CLEAR LIQUID, ODOR NOT SPEC

IFIED

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:UNDER EXTREME TEMPERATURES OR EXTENDED STORAGE PERIODS, HYDROGEN SULFIDE GAS MAY ACCUMULATE IN HEADSPACE OF CONTAINER.

Hazardous Decomposition Products:HYDROGEN SUFIDE, TOXIC LEVELS OF CARBON MONOXIDE & CARBON DIOXIDE, IRRITATING ALDEHYDES & KETONES, SULFUR COMPOUNDS.

Conditions to Avoid Polymerization: WILL NO

	_	_	_	 _
_	\sim	C	\sim	R
	()			 ĸ

====== Disposal Considerations ===========

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

xpressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.