

DUPONT E I DE NEMOURS & CO, INC, POLYMER PRODUCTS -- FREON 114 -- 6830-00-290-4379

===== Product Identification =====

Product ID:FREON 114

MSDS Date:10/07/1991

FSC:6830

NIIN:00-290-4379

MSDS Number: CHQHY

=== Responsible Party ===

Company Name:DUPONT E I DE NEMOURS & CO, INC, POLYMER PRODUCTS

Address:1007 N MARKET ST

City:WILMINGTON

State:DE

ZIP:19898

Country:US

Info Phone Num:800-441-7515/800-523-0372

Emergency Phone Num:800-441-3637/CHEMTREC 800-424-9300

Pre

parer's Name:W. J. BROCK

CAGE:9V583

=== Contractor Identification ===

Company Name:DUPONT E I DE NEMOURS AND CO INC, POLYMER PRODUCT-TEFLON
CO.

Address:1007 MARKET ST

Box:City:WILMINGTON

State:DE

ZIP:19898

Country:US

Phone:800-523-0372/346-4748

CAGE:9V583

===== Composition/Information on Ingredients =====

Ingred Name:DICHLOROTETRAFLUOROETHANE (SARA III)

CAS:76-14-2

RTECS #:KI1101000

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 P

PM; 9293

Ozone Depleting Chemical:1

===== Hazards Identification =====

LD50 LC50 Mixture:TLV: 1,000 PPM, 6,990 MG/M3-8 HR TWA

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION OF HIGH CONCENTRATIONS OF VAPOR IS HARMFUL & MAY CAUSE HEART IRREGULARITIES, UNCONSCIOUSNESS OR DEATH. INTENTIONAL MISUSE OR DELIBERATE INHALATION MAY CAUSE DEATH WITHOUT WA

RNING. VAPOR RED UCES OXYGEN AVAILABLE FOR BREATHING & IS HEAVIER THAN AIR. LIQUID CONTACT MAY CAUSE FROSTBITE.

Explanation of Carcinogenicity:NONE OF THE COMPONENTS IN THIS MATERIAL IS LISTED BY IARC, NTP, OSHA OR ACGIH AS A CARCINOGEN.

Effects of Overexposure:OVEREXPOSURE BY SKIN OR EYE CONTACT MAY INCLUDE SKIN IRRITATION WITH DISCOMFORT OR RASH; OR EYE IRRITATION WITH DISCOMFORT, TEARING, OR BLURRING OF VISION. CONTACT WITH LIQUID MAY CAUSE FROSTBITE. OVE REXPOSURE BY

INHALATION OF VAPORS MAY CAUSE NAUSEA, HEADACHE, OR WEAKNESS.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PREEXISTING DISEASE OF THE CENTRAL NERVOUS OR CARDIOVASULAR SYSTEM MAY HAVE INCREASED SUSCEPITIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURE.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR. KEEP PERSON CALM. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHY
SICIAN. SKIN:FLUSH WITH WATER. TREAT FOR FROSTBITE IF NEE DED. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. EYE- FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MIN. CALL A PHYSICIAN. INGESTION-INGESTION IS NOT CONSIDERED A POTENTIAL ROUTE OF EXPOSURE.

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:WILL NOT BURN

Extinguishing Media:AS APPROPATE FOR COMBUSTIBLES IN AREA.

Fire Fighting Procedures:SELF-CONTAINED BREATHING

APPARATUS IS REQUIRED

IF CYLINDERS RUPTURE OR RELEASE CONTENTS UNDER FIRE CONDITIONS. USE WATER SPRAY OR FOG TO COOL CONTAINERS.

Unusual Fire/Explosion Hazard:CYLINDERS ARE EQUIPPED WITH PRESSURE AND TEMPERATURE RELIEF DEVICES BUT STILL MAY RUPTURE UNDER FIRE CONDITIONS. DECOMPOSITION MAY OCCUR.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA, ESPECIALLY LOW PLACES WHERE HEAVY VAPORS MIGHT COLLECT. REMOVE OPEN FLAM

ES. USE SELF-CONTAINED

BREATHING APPARATUS IN CASE OF LARGE SPILLS. COMPLY WITH FEDERAL, STATE AND LOCAL REGULATIONS ON REPORTING RELEASES.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:CLEAN, DRY AREA. DO NOT HEAT ABOVE 125F.

Other Precautions:AVOID BREATHING VAPORS AND CONTACT OF LIQUID WITH SKIN OR EYES. USE WITH SUFFICIENT VENTILATION TO KEEP EMPLOYEE EXPOSURE BELOW RECOMMENDED LIMITS.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:UNDER NORMAL MANUFACTURING CONDITIONS, NO RESPIRATORY PROTECTION IS REQUIRED WHEN USING THIS PRODUCT. USE A SELF CONTAINED BREATHING APPARATUS IF A LARGE RELEASE OCCURS.

Ventilation:LOCAL EXHAUST-FOR LARGE AMOUNTS RELEASED.GENERAL MECHANICAL- FOR LOW OR ENCLOSED PLACES.

Protective Gloves:IMPERVIOUS GLOVES FOR LIQUID CONTACT.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:NONE

SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NOTES TO PHYSICIAN: BECAUSE OF POSSIBLE DISTURBANCES OF CARDIAC RHYTHM, CATECHOLAMINE DRUGS, SUCH AS EPINEPHRINE, SHOULD BE USED WITH SPECIAL CAUTION IN SITUATIONS OF EMERGENCY LIFE SUPPORT.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:39.2F,4.0C

Decomp Temp:Decomp Text:1099F,593C

Vapor Pres:31 PSIA

Vapor Density:6.2

Spec G

ravity:1.46

Evaporation Rate & Reference:GREATER THAN 1

Solubility in Water:0.013 WT% AT 25C

Appearance and Odor:LIQUIFIED GAS, CLEAR, COLORLESS, SLIGHT ETHEREAL
ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

INCOMPATIBLE WITH ALKALI OR ALKALINE EARTH METALS- POWDERED ALUMINUM,
ZINC, BERYLLIUM, ETC.

Stability Condition to Avoid:MATERIAL IS STABLE. HOWEVER, AVOID OPEN
FLAMES AND

HIGH TEMPERATURES.

Hazardous Decomposition Products:DECOMPOSITION PRODUCTS ARE HAZARDOUS.

FORMING HYDROCHLORIC & HYDROFLUORIC ACID, & POSSIBLY CARBONYL
HALIDES.

===== Disposal Considerations =====

Waste Disposal Methods:COMPLY WITH FEDERAL, STATE AND LOCAL

REGULATIONS. RECLAIM BY DISTILLATION OR REMOVE TO A LICENSED WASTE
DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated f

or use by elements of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.