

CLIFTON ADHESIVE INC -- CS 5338 -- 8030-00-272-8530

=====
Product Identification
=====

Product ID:CS 5338
MSDS Date:01/19/1995
FSC:8030
NIIN:00-272-8530
Status Code:A
MSDS Number: CHXRM
=== Responsible Party ===
Company Name:CLIFTON ADHESIVE INC
Address:BURGESS PL
Box:282
City:WAYNE
State:NJ
ZIP:07474-0282
Country:US
Info Phone Num:201-694-0845
Emergency Phone Num:201-694-0845
CAGE:79833
=== Contr
actor Identification ===
Company Name:CLIFTON ADHESIVE INC
Address:BURGESS PL
Box:City:WAYNE
State:NJ
ZIP:07470
Country:US
Phone:201-694-0845; 973-694-0845
CAGE:79833
Company Name:DUNBAR SALES CORP
Address:39 AVENUE C
Box:City:BAYONNE
State:NJ
ZIP:07002-3417
Country:US
Phone:201-437-6500
CAGE:2G164

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLATUM
CAS:8009-03-8
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

===== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP AND WATER; GET MED AID. EYES: FLUSH WITH MUCH WATER; GET MED AID. INGEST: TREAT SYMPTOMATICALLY; GET MED AID.

===== Fire Fighting Measures =====

Extinguishing Media:FOR DRY FILM: CO2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:NIOSH/MSHA AP
PROVED SCUBA; DRY FILM WILL BURN;
COOL EXPOSED SURFACES WITH WATER SPRAY

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB IN SAND, EARTH, VERMICULITE, OIL-DRI,
OR SOL-SPEED-DRI. SHOVEL ABSORBED MATERIAL INTO STEEL CONTAINER AND COVER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT AND HOT SURFACES;
DO NOT STORE BELOW 40F OR ABOVE 90F

===== Exposure Controls/Personal Protection =====

Ventilation:AS SPECIFIED - LOCAL EXHAUST; MECHANICAL EXHAUST (EXPLOSION PROOF EQUIPMENT)
Protective Gloves:REQUIRED
Eye Protection:SAFETY GLASSES
Work Hygienic Practices:KEEP AREA CLEAN; CLEAN UP SPILLS IMMEDIATELY;
PRACTICE GOOD PERSONAL HYGEINE
Supplemental Safety and Health
EXPOSURE LIMITS ARE FOR AIR LEVELS ONLY. WHEN SKIN CONTACT OCCURS, OVEREXPOSURE MAY RESULT THOUGH AIR LEVELS ARE LESS THAN LIMITS LISTED UNDER INGREDIENTS.

===== Physical/Chemical Properties =====

Spec Gravity:920

Appearance and Odor:SOLID AT ROOM TEMP; MILD BLAND ODOR

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:KEEP FROM OXIDIZING AGENTS

Hazardous Decomposition Products:OXIDES OF CARBON

===== Disposal Considerations =====

Waste Dispos

al Methods:PER FED, STATE, AND LOCAL CHEMICAL AND SOLVENT
REGS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility
for the suitability of this information to their
particular situation.