View NSN Online: https://aerobasegroup.es/nsn/6850-01-377-1809

Product ID:ISOPARAFFINIC PETROLEUM SOLVENT

MSDS Date:05/22/1991

FSC:6850

NIIN:01-377-1809

Status Code:A

MSDS Number: CJDFF === Responsible Party === Company Name:CSD, INC

Box:687

City:CONROE

State:TX ZIP:77305 Country:US

Info Phone Num:409-756-1065/713-797-0395(MEDICAL)

Emergency Phone Num:713-923-66 41/800-424-9300(CHEMTREC)

CAGE:0LWP6

=== Contractor Identification ===

Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX ZIP:77305 Country:US

Phone: 409-756-1065

CAGE:4N760

Company Name: CSD, INC

Box:687

City:CONROE

State:TX ZIP:77305 Country:US

Phone:800-424-9300

CAGE:0LWP6

====== Composition/Information on Ingredients ========

Ingred Name: ISOPARAFFINIC PETROLEUM SOLVENT

Fraction by Wt: 100%

Other REC Limits: NONE SPECIFIED

============= Hazards Identification ========================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-EYES:SLIGHT IRRITATION(NO INJURY). SKIN:PROLONGED/REPEATED CONTACT MAY IRRITATE & CAUSE DERMATITIS.INHALATION: HIGH VAPOR MAY CAUSE RESPIRATORY TRACT IRRITATION,HEADACHE,DIZZINESS, ANESTHESIA,DR

OWSINESS, UNCONSCIOUSNESS, DEATH. INGESTION: MINIMAL TOXICITY. ASPIRA

TION MAY LEAD TO PULMONARY INJURY & DEATH.

Explanation of Carcinogenicity:HEALTH STUDIES HAVE SHOWN THAT MANY PETROLEUM HYDROCARBONS POSE POTENTIAL HEALTH RISKS WHICH VARY FROM PERSON TO PERSON.

Effects of Overexposure:CHRONIC-LABORATORY ANIMAL STUDIES HAVE SHOWN THAT PROLONGED & REPEATED INHALATION EXPOSURE TO LIGHT HYDROCARBON VAPORS IN THE SAME NAPHTHA BOILING RANGE AS THIS PRODUCT CAN PRODUCE ADVERSE KIDNEY EFFE CTS IN MALE RATS.IN A NUMBER OF HUMAN STUDIES,NO SUCH EF

FECTS AT NORMAL OCCUPATIONAL LEVELS.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDER (DERMATITIS) MAY BE AGGRAVATED BY THIS MATERIAL.

First Aid:GET MEDICAL AID.INHALATION:MOVE TO FRESH AIR.GIVE CPR IF NEEDED.KEEP AT REST.EYES:FLUSH WITH WATER FOR 15 MINUTES. SKIN:WASH WITH SOAP & WATER.INGESTION:DO NOT INDUCE VOMITING.KEEP AT REST. GET PROMPT MEDICAL ATTENTION.

========	========	Fire	Figh	٦t	
ing Measures	========	====	===	==	==


Flash Point Method:TCC Flash Point:239F,115C

Autoignition Temp: Autoignition Temp Text: 594F

Lower Limits:0.6 Upper Limits:7.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. AVOID SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS (BOIL OVER).

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.



Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN,

STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGET SODIUM OR CALCIUM HYPOCHLORITE

Stability Condition to Avaidablica HEAT, OPEN FLAMES AND OTHER SOURCES

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:NONE

======= Disposal Considerations ===========

Waste Disposal Methods:DIS
POSE IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. DO NOT FLUSH TO
DRAIN/SEWER. CONTACT THE AUTHORIZED DISPOSAL SERVICE.AVOID
LANDFILLING OF LIQUIDS. RECLAIM WHER E POSSIBLE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.