

SHERWIN-WILLIAMS CO KRYLON/SPRAY ON INDUSTRIAL PRODUCTS -- FLUORESCENT SPRAY  
PAINTS, 3104 LEMON YELLOW -- 8010-00-560-0547

=====  
Product Identification  
=====

Product ID:FLUORESCENT SPRAY PAINTS, 3104 LEMON YELLOW

MSDS Date:09/01/1996

FSC:8010

NIIN:00-560-0547

Status Code:A

MSDS Number: CJDWB

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO KRYLON/SPRAY ON INDUSTRIAL PRODUCTS

Address:31

500 SOLON ROAD

City:SOLON

State:OH

ZIP:44139

Country:US

Info Phone Num:(800) 777-2966

Emergency Phone Num:(215) 566-2917

Resp. Party Other MSDS Num.:(800) 247-3266

CAGE:09800

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

Contract Num:N00406-98-M-N931

CAGE:6F266

Company Name:KRYLON PRODUCTS

Address:31500 SOLON ROAD

Box:City:SOLON

State:OH

ZIP:44139

Country:US

Phone:800-832

-2541/216-566-2917

CAGE:87187

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

=====  
===== Composition/Information on Ingredients =====

Ingred Name:PROPANE. VP: 760.0 MM HG

CAS:74-98-6

RTECS #:TX2275000

= Wt:14.

OSHA PEL:1800 MG/M3;1000 PPM

OSHA STEL:1000 PPM

Ingred Name:BUTANE. VP: 780.0 MM HG

CAS:106-97-8

RTECS #:EJ4200000

= Wt:6.

OSHA PEL:800 PPM

ACGIH TLV:1900 MG/M3;800 PPM

Ingred Name:HEXANE. VP: 127.0 MM HG

CAS:110-54-3

RTECS #:MN9275000

= Wt:11.

OSHA PEL:1800 MG/M3;500 PPM

ACGIH TLV:50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ISOHEXANE; (ISOHAXAND ISOMARS). VP: 250.0 MM HG

CAS:107-83-5

RTECS #:SA2985000

= Wt:4.

OSHA PEL:500 PPM

ACGIH TLV:500 PPM

Ingred Name:LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM); ( V.M.& P  
NEPHTHA). VP: 12.0 MM HG

CAS:64742-89-8

= Wt:16.

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:XYLENE. VP

: 5.9 MM HG  
CAS:1330-20-7  
RTECS #:ZE2100000  
= Wt:1.  
OSHA PEL:100 PPM  
ACGIH TLV:434 MG/M3;100 PPM  
ACGIH STEL:651 MG/M3;150 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE. VP: 180.0 MM HG  
CAS:67-64-1  
RTECS #:AL3150000  
= Wt:12.  
OSHA PEL:2400 MG/M3;1000 PPM  
ACGIH TLV:1780 MG/M3;750 PPM  
ACGIH STEL:2380 MG/M3;1000 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:CALCIUM CARABONATE  
CAS:471-34-1  
RTECS #:FF9335000  
= Wt:3.3  
OSHA PEL:15 [5] (MG/MG)  
ACGIH TLV:10 (MG/M3)

Ingred  
Name:BARIUM SULFATE  
CAS:7727-43-7  
RTECS #:CR0600000  
= Wt:18.3  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:BARIUM COMPOUND; (% BARIUM)  
Fraction by Wt: 0(10.8%)

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: IRRIT OF EYES, SKIN & RESP SYS.  
MAY CAUSE NERVOUS SYS DEPRESS. EXTREME OVEREXP MAY RSLT IN  
UNCONSCIOUSNES

S & POSS DEATH. HDCH, DIZZ, NAUSEA, & LOSS OF COORDINATION ARE INDICATION OF EXCESSIVE EXPOS TO VAPS/SPRAY MISTS. REDNESS & ITCHING/BURNING SENSATION MAY INDICATE EYE/EXCESSIVE SKIN EXPOS. CHRONIC: PRLNGD & RPTD OVEREXP TO XYLENE MAY CAUSE DMG TO NERVE TISSUE OF THE ARMS & LEGS (PERIPHERAL NEUROPATHY), RSLTG IN MUSCULAR WEAK & LOSS OF SENSATION. THIS AFFECT MAY BE INCRD BY THIS PRESENCE OF METHYL ETHYL KETONE. METHYL ETHYL KETONE MAY INCR NERVOUS SYS EFTS OF OTHER S

OLV. (EFTS OF OVER EXP)

Effects of Overexposure:HLTH HAZ: PROLONGED OVEREXPOSURE TO SOLVENT INGREDIENTS IN SECTION 2 MAY CAUSE ADVERSE EFFECTS TO THE LIVER, ORDINARY, BLOOD-FORMING, CARDIOVASCULAR, AND REPRODUCTIVE SYSTEM. RATS EXPOSED TO TITMAIUM DIOXIDE DUST AT 250 MG. RAT DEVELOPED LUNG CANCER, HOWEVER, SUCH EXPOSURE LEVELS ARE NOT ATTAINABLE IN THE WORKPLACE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PARME NT BRAIN AND NERVOUS S

YSTEM

DEPRESSION.

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

===== First Aid Measures =====

First Aid:INHAL: IF AFFECTED, REMOVE FROM EXPOSURE, RESTORE BREATHING. KEEP WARM AND QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE RE-USE. EYE: FLUSH WITH LARGE AMOUNTS OF WATER FOR ATLEAST 15 MINUTES. GET MEDICAL ATTENTION. INGEST: NEVER GIVE ANYTHING BY MOUTH

TO AN

UNCONSCIOUS PERSON. DO NOT INDUCE VOMITING. GIVE SEVERAL GLASSES OF WATER. G ET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point: