CAMLAUR SCIENTIFIC -- ACETONE -- 6810-00-264-8955 Product ID:ACETONE MSDS Date:02/10/1999 FSC:6810 NIIN:00-264-8955 Status Code:A MSDS Number: CJDXW === Responsible Party === Company Name: CAMLAUR SCIENTIFIC Address:4820 SPANISH TRAIL City:HOUSTON State:TX ZIP:77221 Country:US Info Phone Num:281-343-0364 Emergency Phone Num:213-516-8000 CAGE:TO062 === Contractor Identification === Company Name: CAMLAUR SCIENTIFIC Address:4820 S **PANISH TRAIL** Box:City:HOUSTON State:TX ZIP:77221 Country:US Phone:281-343-0364 CAGE:TO062 Company Name: LOS ANGELES CHEMICAL CO Address:4545 ARDINE ST Box:1987 City:SOUTH GATE State:CA ZIP:90280 Country:US Phone:213-562-9500 Contract Num:SP0450-99-M-C379 CAGE:75656 ======= Composition/Information on Ingredients ========

Ingred Name: ACETONE (SARA 313) (CERCLA)

CAS:67-64-1

RTECS #:AL3150000

= Wt:100.

Other REC Limits: NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:750PPM/1000STEL;9596

Е

PA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

========= Hazards Identification ==============

LD50 LC50 Mixture:LD50 (ORAL, RAT) 5,800 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS: BLOOD, LIVER, KIDNEYS, LUNGS. THE NERVOUS SYSTEM, MUCOUS MEMBRANES. ACUTE- SLIGHTLY DANGEROUS TO DANGEROUS IN CASE OF SKIN CONTACT (PERMEABLE), OF EYE CONTACT (IRRITANT),

OF INGESTION, OF INHALATION. VERY SLIGHTLY TO SLIGHTLYDANGEROUS IN CASE OF SKIN CONTACT (IRRITANT, SENSITIZER). THIS PRODUCT MAY IRRITATE EYES AND SKIN UPON CONTACT. CHRONIC- THE SUBSTANCE IS TOXIC TO BLOOD, KIDNE YS, LUNGS, THE NERVOUS SYSTEM, LIVER, MUCOUS MEMBRANES. REPEATED OR PROLONGED EXPOSURE TO THE SUBSTANCE CAN PRODUCE TARGET ORGANS DAMAGE.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCIN OGENS OR SUSPECT

CARCINOGENS.

Effects of Overexposure:UPPER RESPIRATORY TRACT IRRITATION, WEAKNESS OF THE LEGS, HEADACHE, DIZZINESS, DROWSINESS, NAUSEA, MALAISE, INCOORDINATION, SKIN IRRITATION, DEFATTING, STINGING SENSATION IN EYES, FRUITY ODOR OF THE B REATH, RESTLESSNESS, DIARRHEA, NAUSEA, VOMITING, HEMATEMESIS, COLLAPSE

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED LIVER, KIDNEY OR RESPIRATORY FUNCTION MAY B

E MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. RINSE WITH PLENTY OF WATER OR UNDER SHOWER. IF IRRITATION PERSISTS, GET MED ICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, DRINK S

EVERAL GLASSES OF WATER OR MILK. SEEK IMMEDIATE MEDIC AL ATTENTION.

Flash Point Method:CC Flash Point:=-20.C, -4.F Autoignition Temp:=465.C, 869.F Lower Limits: 2.6 % Upper Limits:12.8% Extinguishing Media: SMALL FIRE: USE DRY CHEMICALS, CARBON DIOXIDE, WATER SPRAY, ALCOHOL FOAM, LARGE FIRE: USE ALCOHOL FOAM, WATER SPRAY OR FOG. Fire Fighting Procedures: WEAR FULL PROTECTIVE CLOTHING, INCLUDING HELMET AND NIOSH-A PPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR AND CAN TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CAN FORM MAY FORM CARBON MONOXIDE, CARBON DIOXIDE. ======== Accidental Release Measures ============= Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. EVACUATE AREA. WEAR PROPER PERSONAL PROTECTIVE EQUIPMENT. VENTILATE ARE A. DILUTE WITH WATER AND MOP UP OR ABSORB WITH INERT, NON-FLAMMABLE DRY MATERIAL AND PLACE IN AN A PPROPRIATE WASTE DISPOSAL CONTAINER. Neutralizing Agent: DILUTE WITH WATER ============ Handling and Storage =========================== Handling and Storage Precautions:FLAMMABLE MATERIAL SHOULD BE STORED IN SOURCES OF IGNITION IN A COOL, WELL-VENTILATED PLACE. KEEP

A SEPARATE SAFETY STORAGE CABINET OR ROOM. KEEP AWAY FROM HEAT, CONTAINER TIGHTLY CLOSED. GROUND ALL E QUI

PM, ENTS CONTAINING THIS MATERIAL.

Other Precautions: AVOID CONTACT WITH HEAT, SPARKS, FLAMES OR OTHER SOURCES OF IGNITION. VAPORS MAY BE EXPLOASIVE. DO NOT ALLOW UNNECESSARY PERSONNEL IN AREA. DO NOT OVERHEAT CONTAINERS. CONTAINERS MAY VIOLENTLY RUPTURE IN FIRE. A REFRIGERATED ROOM WOULD BE PREFERABLE FOR MATERIALS WITH A FLASH POINT LOWER THAN 37.8C (100F)

====== Exposure Controls/Personal Protection ========

Respiratory Protection: IF VENTILATION DOES NO

T MAINTAIN INHALATION

EXOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH RESPIRATOR SELECTION.

Ventilation: MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves: DISPOSABLE VINYL

Eye Protection: SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO AVOID SKIN CONTACT. BE SURE THAT EYE WASH STATIO

N AND SAFETY SHOWER IS

PROXIMAL TO THE WORK-STATION LOCATION.

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and Health

======== Physical/Chemical Properties ===========

HCC:F2

Boiling Pt:=56.2C, 133.2F

Melt/Freeze Pt:=-95.4C, -139.7F

Vapor Pres:186.2 MM OF HG @ 20 DEG C

Vapor Density:2 (AIR=1)

Spec Gravity:0.79 (WATER=1)

Viscosity:NOT RE

LEVANT

Solubility in Water: VERY SOLUBLE Percent Volatiles by Volume: 100 %

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

NO SPECIFIC INFORMATION IS AVAILABLE REGARDING THE REACTIVITY OF THIS MATERIAL IN PRESENCE OF VARIOUS OTHER MATERIALS.

Stability Condition to Avoid:HEAT, OPEN FLAME, IGNITION SOURCES, STATIC ELECTRICITY, SPARKS

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE

====== Toxicol

ogical Information =============
Toxicological Information:ACUTE DERMAL TOXICITY (LD50): 20000 MG/KG (RABBIT). ACUTE TOXICITY OF THE VAPOR (LC50): 29853 PPM (RAT).
=========== Ecological Information =============
Ecological:NOT EXPECTED TO BE TOXIC TO EQUATIC LIFE. LC50/96 HOUR VALUES FOR FISH ARE OVER 100 MG/L.
======== Disposal Considerations ============
Waste Disposal Methods:DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR
LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. RECYCLE IF POSSIBLE OR BURN FOR ENERGY RECOVERY.
======================================
State Regulatory Information:LISTED BY PENNSYLVANIA AND MASSACHUSETTS
Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warra nts this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.