

AMERICAN SAFETY TECHNOLOGIES INC -- MS-7C HARDENER COMPONENT -- 8010-01-397-3986

===== Product Identification =====

Product ID:MS-7C HARDENER COMPONENT

MSDS Date:07/14/1998

FSC:8010

NIIN:01-397-3986

Kit Part:Y

MSDS Number: CJHQZ

=== Responsible Party ===

Company Name:AMERICAN SAFETY TECHNOLOGIES INC

Address:565 EAGLE ROCK AVE

City:ROSELAND

State:NJ

ZIP:07068-1501

Country:US

Info Phone Num:973-403-

2600/FAX 201-403-1108

Emergency Phone Num:973-403-2600

Resp. Party Other MSDS Num.:0076

Preparer's Name:J. HERMELE

Chemtrec Ind/Phone:(800)424-9300

CAGE:88444

=== Contractor Identification ===

Company Name:AMERICAN SAFETY TECHNOLOGIES INC

Address:565 EAGLE ROCK AVE

Box:City:ROSELAND

State:NJ

ZIP:07068

Country:US

Phone:973-403-2600

CAGE:88444

===== Composition/Information on Ingredients =====

Ingred Name:POLYAMIDE/EPOXY ADDUCT

CAS:68424-41-9

Minumum % Wt:60.

Maxumum % Wt:80.

Ingred Name:AMIDOAMINE RESIN

CAS:68443-08-3

Minumum % Wt:5.

Maxumum % Wt:10.

Ingred Name:1-METHOXY-2-PROPANOL

CAS:107-98-2

RTECS #:UB7700000

Minumum % Wt:20.

Maxumum % Wt:35.

OSHA PEL:100PPM

ACGIH TLV:369 MG/M3;100 PPM

ACGIH STEL:553 MG/M3;150 PPM

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute

and Chronic:EYES: CAUSES SEVERE IRRITATION OR

BURNS. MAY CAUSE PERMANENT VISUAL IMPAIRMENT. SKIN: CAUSES SEVERE IRRITATION OR BURNS. MAY BE ABSORBED THROUGH SKIN IN HARMFUL AMOUNTS. INHALATION: MAY CAUSE UPPER RE SPIRATORY TRACT IRRITATION. INGESTION: MAY CAUSE BURNS OF MOUTH AND THROAT. CONTAINS MATERIAL THAT MAY BE SLIGHTLY TOXIC. OVEREXPOSURE EFFECTS: IRRITATION, SENSITIZATION AND DERMATITIS.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:ALLERGY, ECZEMA AND OTHER SKIN CONDITIONS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH CONTACT AREA WITH MILD SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST CONSULT MD. INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE LARGE QUANTITIES

OF WATER TO
DILUTE. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:=34.4C, 94.F

Lower Limits:1.5%

Upper Limits:10.9%

Extinguishing Media:DRY CHEMICAL, CHEMICAL FOAM, CARBON DIOXIDE OR
WATER.

Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE
EQUIPMENT . REMOVE ALL SOURCES OF IGNITION.

Unusual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY
BE TOXIC.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. DIKE SPILL.
ABSORB WITH INERT MATERIAL AND COLLECT FOR DISPOSAL. FLUSH
CONTAMINATED AREA WITH DILUTE (5%) ACETIC ACID AND COLLECT RINSATE
FOR DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID ALL PERSONAL CONTACT. DO NOT
EXCEED 110F/43C IN STORAGE AREA. GROUND AND BOND METAL CONTAINERS
FOR LIQUID T

RANSFER TO AVOID STATIC SPARKS.

Other Precautions:IMMEDIATELY REMOVE AND THOROUGHLY LAUNDER
CONTAMINATED CLOTHING BEFORE REUSE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR
CARTRIDGE IF REQUIRED.

Ventilation:EXPLOSION-PROOF MECHANICAL VENTILATION & LOCAL EXHAUST
RECOMMENDED. MECHANICAL EXHAUST IS NOT RECOMMENDED AS THE SOLE
MEANS OF CONTROLLING EMPLOYEE EXPOSURE.

Protective Gloves:IMPERVI

OUS GLOVES.

Eye Protection:ANSI APPROVED CHEMICAL WORKERS GOGGLES AND FULL LENGTH
FACESHIELD .

Other Protective Equipment:EYE WASH & DELUGE SHOWER MEETING ANSI DESIGN
CRITERIA . IN OPERATIONS WHERE CONTACT MAY OCCUR COVERALLS, APRON
&IMPERVIOUS FOOT COVERING ARE RECOMMENDED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt.=120.C, 248.F

Vapor Pres:12.5 MM HG

Vapor Density:3.12

Spec Gravity:0.96

Evaporation Rate & Ref

erence:0.83 (BUTYL ACETATE =1)

Solubility in Water:PARTIALLY SOLUBLE

Appearance and Odor:AMBER LIQUID; SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:EXCESSIVE HEAT.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
ALDEHYDES AND OXIDES OF NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:THI

S PRODUCT, IF DISPOSED AS SHIPPED, MEETS EPA

CRITERIA OF HAZARDOUS WASTE AS SPECIFIED IN 40 CFR 261 ON BASIS OF
ITS IGNITABILITY. DISPOSE OF IN A LICENSED HAZARDOUS WASTE FACILITY
IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL LAWS.

===== MSDS Transport Information =====

Transport Information:DOT SHIPPING CLASSIFICATION (49 CFR 172.101):

PAINT, 3, UN1263, III.

===== Regulatory Information =====

SARA Titl

e III Information:SECTION 313 SUPPLIER INFORMATION: THIS
PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) SUBJECT TO THE REPORTING
REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY
RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 372. THIS INFORMATION MUST
BE INCLUDED IN ALL MSDS'S THAT ARE COPIED AND DISTRIBUTED FOR THIS
MATERIAL. CHEMICAL NAME: NONE.

===== Other Information =====

Disclaimer (provided with this information by the
compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.