CONCORDE BATTERY CORP -- VALVE REGULATED LEAD ACID BATTERY (D8565/14-1) - 6140-01-420-8988

Product ID:VALVE REGULATED LEAD ACID BATTERY (D8565/14-1) MSDS Date:08/18/1999 FSC:6140 NIIN:01-420-8988 MSDS Number: CJKXZ === Responsible Party === Company Name: CONCORDE BATTERY CORP Address:2009 SAN BERNARDINO RD **City:WEST COVINA** State:CA ZIP:91790-1006 Country:US Info Phone Num:800-255-3924/818-813-1234 Emergency Phone Num:626-813-1234/800-255-3924(AFTER HR) Preparer's Name: JOHN B. HINER CAGE:63017 === Contractor Identification === Company Name: ADVANCED POWER PRODUCTS Address:7702 S GREENLEAF AVE Box:City:WHITTIER State:CA ZIP:90602 Country:US Phone:562-696-7334 Contract Num:SP0430-98-M-JP54 CAGE:1CNZ7 Company Name: CONCORDE BATTERY CORP Address:2009 SAN BERNARDINO RD Box:City:WEST COVINA State:CA ZIP:91790-1006 Country:US Phone:800-255-3924/818-813-1234 Contract Num:SP0430-00-C-5007 CAGE:63017 Company Name: CONCORDE BATTER

Y CORP Address:2009 SAN BERNARDINO RD Box:City:WEST COVINA State:CA ZIP:91790-1006 Country:US Phone:800-255-3924/818-813-1234 Contract Num:SP0430-01-C-0781 CAGE:63017

Ingred Name:LEAD/LEAD OXIDE CAS:7439-92-1 RTECS #: OF7525000 Minumum % Wt:60. Maxumum % Wt:70. Other REC Limits: ACGIH-TLV(MSDS) 0.05 OSHA PEL:0.05 MG/M3 ACGIH TLV:0.15 MG/M3 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name:SULFURIC ACID CAS:7664-93-9 **RTECS #:WS5600** 000 Minumum % Wt:20. Maxumum % Wt:30. Other REC Limits:0.5 MG/M3 (MSDS) OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3 ACGIH STEL:3 MG/M3 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name:ARSENIC CAS:7440-38-2 RTECS #:CG0525000 < Wt:1. Other REC Limits:NOT PROVIDED OSHA PEL:.01 MG/M3 ACGIH TLV:0.01 MG/M3 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name:CALCIUM CAS:7440-70-2 RTECS #:EV8040000 < Wt:.15

Other REC Limits:NOT PROVIDED OSHA PEL:NOT AVAILABLE ACGIH TLV:NOT AVAILABLE LD50 LC50 Mixture:NOT PROVIDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic: EXPOSURE MAY OCCUR IF BATTERY CASE IS DAMAGED. LEAD: CHRONIC: TIRE EASILY, LOSS OF APPETITE,

IRRITABILITY, METALLIC TASTE, INSOMNIA; TOXIC TO NERVOUS SYSTEM, KIDNEYS, REPRODUCTIVE SYSTEM. ACUTE: CONS TIPATION, VOMITING, BLUE

LINE ON GUMS, WEAK WRISTS/ANKL ES, WEIGHT LOSS, YELLOWISH SKIN.

ACID: CHRONIC - EROSION OF TEETH, INFLAMMATION OF NOSE, THROAT, BRONCHIAL TUBES. ACUTE: EYES - SEVERE BURNS, CO RNEA DAMAGE, BLINDNESS. SKIN - SEVERE IRRITATION, BURNS, ULCERATION. INHALATION - RESPIRATORY IRRITATION, INFLAMMATION OF BRONCHIAL MEMBRANES. INGESTION - SEVERE BURNS OF MOUTH, THROAT, ESOPHAGUS AND STOMACH, DAMAGE TO KIDNEY AND INTESTINE

Explanation of Carcinogenicity: CONTAINS ARSENIC AND LEAD.

Effects of Overexposure: EXPOSUR

E MAY OCCUR IF BATTERY CASE IS DAMAGED.

LEAD: CONSTIPATION, VOMITING, BLUE LINE ON GUMS, WEAK WRISTS/ANKLES, WEIGHT LOSS, YELLOWISH SKIN. ACID: EYES - SEVERE BURNS, CORNEA DAMAGE, BLINDNESS. SK IN - SEVERE IRRITATION, BURNS, ULCERATION. INHALATION - RESPIRATORY IRRITATION, INFLAMMATION OF BRONCHIAL MEMBRANES. INGESTION - SEVERE BURNS OF MOUTH, THROAT, ESOPHAGUS AND STOMACH.

Medical Cond Aggravated by Exposure:SULFURIC ACID AGGRAVATES PULMONARY CONDITIONS. HARMFUL EFFE

CTS OF LEAD ARE INCREASED IN PESONS WITH DIETARY DEFICIENCIES OF CALCIUM, IRON AND ZINC.

First Aid:LEAD: INHALATION: REMOVE FROM EXPOSURE. SEE PHYSICIAN. EYES:(DRY OXIDE) WASH WITH WATER FOR 15 MINUTES. SEE PHYSICIAN. SKIN: NOT A ROUTE OF ENTRY. INGESTION: SEE PHYSICIAN. SULFURIC ACID: INHALATION: REMOVE TO FRESH AIR. SEE PHYSICIAN IMMEDIATELY. IF UNCONSCIOUS, PERFORM CPR. KEEP VICTIM WARM, RESTED. IF BRE ATHING

IS DIFFICULT, GIVE OXYGEN. EYES: WASH WITH WATER FOR 15 MINUTES OR UNTIL ACID IS RE MOVED. SEE PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHES. FLUSH SKIN WITH PLENTY OF WATER UNTIL ACID FREE. INGESTION: DO NOT INDUCE VOMITING. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON, SEE PHYSICIAN IMMEDIATELY.

Flash Point Method:CC Flash Point:>357.2C, 675.F POLYPROPYLENE Extinguishing Media:HALON, DRY CHEMICAL

Fire Fighting Procedures:BATTERIES DO NOT BURN OR BURN WITH DIFFICULTY. EXTINGUISH FIRE WITH AGENT SUITABLE FOR SURROUNDING COMBUSTIBLE MATERIALS. COOL EXTERIOR OF BATTERY IF EXPOSED TO FIRE TO PREVENT RELEASE OF LEAD COMPOUN DS AND FUMES.

Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: WILL NOT OCCUR UNLESS SEALED CASE IS DAMAGED. PICK UP AND CONTAINERIZE ALL BATTERY PARTS AND MATERIALS. L IMIT

PERSONAL EXPOSURE WITH GLOVES, EYE AND FACE PROTECTION. NEUTRALIZE SULFURIC ACID WITH LIME, SODA ASH, OR SODIUM BICARBONATE. Neutralizing Agent:LIME, SODA ASH, OR SODIUM BICARBONATE.

Handling and Storage Precautions: EXERCISE CAUTION IN HANDLING AND STORAGE DUE TO WEIGHT OF UNITS. DO NOT STORE IN AIR TIGHT CONTAINER.

Other Precautions:DO NOT ALLOW METAL OR OTHER CONDUCTIVE MATERIAL TO SHORT CIRCUIT TE

RMINALS. HEAT, SPARKS, DAMAGE TO ELECTRICAL

CIRCUITS, AND FIRE MAY RESULT FROM SHORT CIRCUITING. PRACTICE GOOD HYGIENE TO MINIMIZE PERSONAL EXPOSURE. BATTERY MAY RELEASE HYDROGEN DURING CHARGING OR IF EXPOSED TO HIG H TEMPERATURES.

Respiratory Protection: IF PRODUCT IS INVOLVED IN FIRE, RELEASE OF DUST OR FUMES FROM DAMAGED CASES MAY RESULT. USE OF SCBA FULL FACE OR HALF-MASK RESPIRATOR WITH HEPA CARTRID GE WOULD BE RECOMMENDED. Ventilation: NO

Protective Gloves: USE LEATHER OR OTHER PROTECTIVE GLOVES IF HANDLING BROKEN UNITS.

Eye Protection:SAFETY GLASSES, FACE SHIELD, OR GOGGLES FOR HANDLING BROKEN OR DAMAGED PRODUCT.

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:NOT PROVIDED

Supplemental Safety and Health

ABBREVIATION: N/A = NOT APPLICABLE. N/AV = NOT AVAILABLE. N/K =

UNKNOWN. N/P = NOT PROVIDED. N/R = NOT RELEVANT. N/D = NOT

DETERMINED. N/E = NOT ESTABLISHED

. SCBA = SELF CONTAINED BREATHING APPARATUS.

HCC:Z4 NRC/State Lic Num:NOT RELEVANT Melt/Freeze Pt:>160.C, 320.F M.P/F.P Text:POLYPROPYLENE Decomp Temp:Decomp Text:NOT PROVIDED Spec Gravity: LEAD, APPROX. 13 Appearance and Odor:SOLID UNIT: BATTERY: LEAD/LEAD OXIDE(INTERNAL): GREY METALLIC SOLID; BROWN/GREY Percent Volatiles by Volume:NONE Corrosion Rate:NOT PROVIDED \_\_\_\_\_ Stability Indicator/Materials to Avoid:YES KEEP BATTERY CASE AWAY FROM STRONG OXIDIZERS. Stability Condition to Avoid:NOT PROVIDED Hazardous Decomposition Products:NONE Toxicological Information:NOT PROVIDED Ecological:NOT PROVIDED 

Waste Disposal Methods:BATTERY PARTS MAY B E RECYCLED BY EPA PERMITTED SECONDARY LEAD SMELTING FACILITY OR DISPOSED OF AS HAZARDOUS WASTE PURSUANT TO RCRA REQUIREMENTS.

Transport Information:DOT DESCRIPTION: BATTERY, WET, NON-SPILLABLE, 8, UN2800, PG III. BATTERY EXEMPT FROM DOT REQUIREMENTS WHEN TESTED PER 49CFR173.159(D)

SARA Title III Information:NOT PROVIDED Federal Regulatory

## Information:NOT PROVIDED State Regulatory Information:PROPOSITION 65 WARNING: THIS PRODUCT CONTAINS LEAD AND LEAD COMPOUNDS. LEAD AND LEAD COMPOUNDS ARE CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. LEAD IS A CHEMICAL KNOWN TO T HE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS AND REPRODUCTIVE TOXICITY IN BOTH MALES AND FEMALES.

Disclaimer (provided with this information by the compiling a gencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.