View NSN Online: https://aerobasegroup.es/nsn/6830-01-360-1866

MG INDUSTRIES -- MGI68220 -- 6830-01-360-1866

Product ID:MGI68220 MSDS Date:06/30/1994

FSC:6830

NIIN:01-360-1866

Status Code:A

MSDS Number: CJLTX === Responsible Party ===

Company Name: MG INDUSTRIES Address: 3 GREAT VALLEY PKY

City:MALVERN

State:PA

ZIP:19355-1424

Country:US

Info Phone Num:610-695-7449

Emergency Phone Num:610-695-7400

Chemtrec Ind/Phone:(800)424-93

00

CAGE:08772

=== Contractor Identification === Company Name:MG INDUSTRIES Address:3 GREAT VALLEY PKY

Box:City:MALVERN

State:PA

ZIP:19355-1424

Country:US

Phone:610-695-7400 / 610-695-7449

CAGE:08772

Company Name:MG INDUSTRIES Address:8025 DORSEY RUN RD

Box:City:JESSUP

State:MD

ZIP:20794-9326 Country:US

Phone:301-796-8845

Contract Num:SP0450-99-M-JB74

CAGE:8K810

======= Composition/Information on Ingredients ========

Ingred Name: HYDROGEN

CAS:1333-74-0

RTECS #:MW8900000

< Wt:4.

Ingred Name:AIR Minumum % Wt:0. Maxumum % Wt:99.9

Ingred Name:ARGON CAS:7440-37-1 RTECS #:CF2300000 Minumum % Wt:0. Maxumum % Wt:99.9

Ingred Name:HELIUM CAS:7440-59-7 RTECS #:MH6520000 Minumum % Wt:0. Maxumum % Wt:99.9

Ingred Name:NITROGEN CAS:7727-37-9 RTECS #:QW9700000 Minumum % Wt:0. Maxumum % Wt:99.9

Ingred Name:NEON CAS:7440-01-9 RTECS #:QP4550000 Minumum % Wt:0. Maxumum % Wt:99.9

========== Hazards Identification ================

Reports of Carcinogenicity:NTP:NO

IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET EFFECTS: SIMPLE ASPHYXIANT.
AIR; ACUTE - INHALATION OF COMPRESSED AIR MAY CAUSE DECOMPRESSION
SICKNESS. SYMPTOMS MAY INCLUDE: HEADACHE, VERTIGO, FATIGUE,
VOMITING, BURNING SENSATION IN CHEST, P ULMONARY EDEMA, VISUAL
DEFECTS, DEAFNESS, CONVULSIONS, UNCONSCIOUSNESS AND DEATH. SIMPLE
ASPHYXIANTS: UNCONSCIOUSNESS MAY BE IMMEDIATE. MAY CAUSE RAPID
RESPIRATION AND PULSE, AIR HUNGER, DIZZINESS, RE DUCED AWARENESS,
TIG

HTNESS IN HEAD, INCOORDINATION, FAULTY JUDGEMENT, COLLAPSE, UNCONSCIOUSNESS, CONVULSIONS, DEEP COMA AND DEATH. CHRONIC - NO DATA AVAILABLE. INGESTION IS UNLIKELY. CONTACT WITH GAS MAY CAUSE FROSTBITE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:AIR: HEADACHE, VERTIGO, FATIGUE, VOMITING, DYSPNEA, BURNING SENSATION IN CHEST, COUGH, CUTANEOUS IRRITATION, ITCHING, VISUAL DEFECTS, DEAFNESS, PAIN IN MUSCLE, TINGLING, NUMNESS, WEAKNESS OF PARALYSIS OF LIMPS, AN

GINA. HYPOTENSION.

CONVULSIONS, UNCONSCIOUSNESS, COMA AND DEATH, JOINT COLLAPSE.
SIMPLE ASPHYXIANTS: RAPID RESPIRATION AND PULSE, AIR HUNGER,
DIZZINESS, REDUCED AWARENESS, TIGHTNESS IN HE AD, INCOORDINATION,
FAULTY JUDGEMENT, COLLAPSE, UNCONSCIOUSNESS, CONVULSIONS, DEEP COMA
AND DEATH. EYE AND SKIN FROSTBITE MAY OCCUR.

| ======== First | rst Aid Measures | |
|----------------|------------------|--|
|----------------|------------------|--|

First Aid:REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. PERFORM ARTIFICIAL RES

PIRATION IF NECESSARY. MAINTAIN AIRWAY, BLOOD
PRESSURE AND RESPIRATION. KEEP WARM AT REST. TREAT SYMPTOMATICALLY
AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY. QUALIFIED
MEDICAL PERSONNEL SHOULD ADMINISTER OXYGEN. IT IS UNLIKELY THAT
EMERGENCY TREATMENT WILL BE REQUIRED FOR EYE OR SKIN CONTACT. IF
NEEDED, WARM AFFECTED AREA IN SKIN WITH WARM WATER (107F). GET
MEDICAL ATTENTION IMMEDIATELY. IF CONTACT WITH LIQUEFIED OR
COMPRESSED GAS OCCURS, WASH EYE WITH LAR

GE AMOUNT OF WATER FOR AT LEAST 15-20 MINUTES. GET MEDIC AL ATTENTION IMMEDIATELY.

| | Fire Fighting Measures | |
|--|------------------------|--|
|--|------------------------|--|

- Extinguishing Media:DRY CHEMICAL OR CARBON DIOXIDE. FOR LARGER FIRES, USE WATER SPRAY, FOG OR REGUALR FOAM (1993 EMERGENCY RESPONSE GUIDEBOOK, RSPA P 5800.6).
- Fire Fighting Procedures:MOVE CONTAINER FROM FIRE IF YOU CAN DO IT WITHOUT RISK. COOL CYLINDERS WITH FLOODING AMOUNTS OF WATER FROM AS FAR A DISTANCE AS POSSIBLE. DO N
- OT USE WATER DIRECTLY ON MATERIAL, USE WATER SPRAY TO ABSO RB VAPORS. AVOID BREATHING VAPORS, KEEP UPWIND.
- Unusual Fire/Explosion Hazard:CONTAINER MAY EXPLODE IN HEAT OF FIRE.
 CONSIDER EVACUATION OF DOWNWIND AREA IF MATERIAL IS LEAKING.
 WITHDRAW IMMEDIATELY IN CASE OF RISING SOUND FROM VENTING SAFETY
 DEVICE OR ANY DISCOLORATION OF TANK DUE TO FIRE. MAY LEAVE A
 FLAMMABLE RESIDUE

| ======================================= | Handling | and Storage | ======================================= |
|---|----------|-------------|---|
| | | | |

Handling and Storage Pre

| cautions:OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING THIS SUBSTANCE STORE IN ACCORDANCE WITH 29 CFR 1910.101. STORE AWAY FROM INCOMPATIBLE SUBSTANCES. Other Precautions:DO NOT PERMIT PHYSICAL DAMAGE OR OVERHEATING OF CONTAINERS. CONTAINERS ARE UNDER PRESSURE; CONTAIENRS MAY VIOLENTLY RUPTURE AND TRAVEL A CONSIDERABLE DISTANCE. |
|---|
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:NIOSH-MSHA APPROVED SUPPLIED-AIR RESPIRATO R IN |
| PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE OR SELF-CONTAINED BREATHING APPARATUS (SCBA) BASED ON CONTAMINATION LEVELS IN WORK PLACE. FOR FIREFIGHTIN G AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS USE NIOSH-MSHA APPROVED SUPPLIED-AIR RESPIRATOR, FULL FACEPIECE, POSITIVE PRESSURE MODE AND SCBA. Ventilation:PROVIDE GENERAL DILUTION VENTILATION Protective Gloves:WEAR FULL PROTECTIVE, COLD INSULATING GLOVES Eye Protection:SPLASH-PROOF SAFETY GOGGLES AND F |
| ACESHIELD IF CONTACT WITH LIQUID IS POSSIBLE. |
| Other Protective Equipment:EYE BATH, WASHING FACILITY, EMERGENCY SHOWER, AND APPROPRIATE PROTECTIVE CLOTHING AND EQUIPMENT TO PREVENT SKIN FROM FREEZING IF CONTACT WITH LIQUID IS POSSIBLE. Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. Supplemental Safety and Health |
| NONE |
| ====================================== |
| HCC:G3 Appearance and Odor:GAS |
| ========== Stability and Reactivity Data ========== |

ALKALINE METALS, CA CARBONATE+MG, CHLORINE DIOXIDE, COPPER OXIDE, NITROGEN OXIDE, NITROSYL CHLORIDE, OXYGEN, OZONE, CHARCOAL, COMBUSTIBLE MATERIALS, ETHER, HYDROCARBONS, ORGANIC MATERIALS, STRONG REDUCING AGENTS, LITHIUM, T

Stability Condition to Avoid:STABLE UNDER NORMAL TEMPERATURES AND PRESSURES.

Hazardous Decomposition

Stability Indicator/Materials to Avoid:YES

| Disposal Consideration | ons ========== |
|----------------------------|----------------|

Products: TOXIC AND/OR HAZARDOUS GASES.

Waste Disposal Methods:OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN DISPOSING OF THIS SUBSTANCE..

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.