

THE P. D. GEORGE COMPANY -- PED 12-0-12 INSULATING VARNISH -- 5970-00-166-1682

=====
Product Identification
=====

Product ID:PED 12-0-12 INSULATING VARNISH

MSDS Date:01/18/1999

FSC:5970

NIIN:00-166-1682

Status Code:A

MSDS Number: CJRGH

=== Responsible Party ===

Company Name:THE P. D. GEORGE COMPANY

Address:5200 N 2ND ST

City:ST LOUIS

State:MO

ZIP:63147-3122

Country:US

Info Phone Num:314-621-5700

E

mergency Phone Num:800-935-5053

CAGE:97160

=== Contractor Identification ===

Company Name:THE P. D. GEORGE COMPANY

Address:5200 N 2ND ST

Box:City:ST LOUIS

State:MO

ZIP:63147-3122

Country:US

Phone:314-621-5700

CAGE:97160

Company Name:THE SMITH GROUP INC.

Address:811 E. CAYUGA STREET

Box:City:PHILADELPHIA

State:PA

ZIP:19124-3893

Country:US

Phone:215-743-8200

Contract Num:SP0430-99-M-TF52

CAGE:2B613

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL BENZENE

CAS

:100-41-4

RTECS #:DA0700000

< Wt:7.

OSHA PEL:435 MG/M3;100 PPM

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:543 MG/M3;125 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE (MIXED ISOMERS)

CAS:1330-20-7

RTECS #:ZE2100000

< Wt:18.

OSHA PEL:100 PPM/435 MG/M3

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ALIPHATIC NAPHTHA

CAS:64742-89-8

< Wt:15.

OSHA PEL:500 MG/M3

ACGIH TLV:300 PPM/1370 MG/M3

Ingred Name:MINERAL SP

IRITS INCLUDING THE TWO FOLLOWING INGREDIENTS.

CAS:8052-41-3

RTECS #:WJ8925000

< Wt:8.

OSHA PEL:2900 MG/M3;500 PPM

ACGIH TLV:525 MG/M3;100 PPM

Ingred Name:1,3,5-TRIMETHYLBENZENE

CAS:108-67-8

RTECS #:OX6825000

= Wt:2.5

Other REC Limits:NOT PROVIDED.

OSHA PEL:NOT DETERMINED.

ACGIH TLV:NOT DETERMINED.

Ingred Name:1,2,4-TRIMETHYLBENZENE

CAS:95-63-6

RTECS #:DC3325000

= Wt:2.5

Other REC Limits:NOT PROVIDED.

OSHA PEL:NOT DETERMINED.

ACGIH TLV:NOT DETERMINED.

Ingred Name:ALIPHATIC SOLVENT NAPHTHA

(CAS 64742-89-8 ALREADY IN FOR
ALIPHATIC NAPHTHA, 93.3C, 200.F

Vapor Density:NO DATA

Spec Gravity:0.95

Evaporation Rate & Reference:NO DATA

Percent Volatiles by Volume:58%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS AND ACIDS

Stability Condition to Avoid:OPEN FLAME,SPARKS,HIGH TEMPERATURE

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE AND
TOXIC VAPORS

===== T
oxicological Information =====

Toxicological Information:NOT PROVIDED.

===== Ecological Information =====

Ecological:NOT PROVIDED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE
FEDERAL, STATE, AND LOCAL REGULATIONS. UNDER THE RESOURCE
CONSERVATION AND RECOVERY ACT (RCRA) REGULATORY, IT IS THE
RESPONSIBILITY OF THE PRODUCT USER TO DETERMINE, AT THE
TIME OF
DISPOSAL, WHETHER A MATERIAL SHOULD BE CLASSIFIED AS A HAZARDOUS
WASTE. CONSULT YOUR ATTORNEY OR REGULATORY OFFICER.

===== Regulatory Information =====

SARA Title III Information:SECTION 312: FIRE HAZARD + ACUTE HEALTH
HAZARD + CHRONIC HEALTH HAZARD. SECTION 313 STATUS: ETHYL BENZENE
100-41-4 < 7%, XYLENE (MIXED ISOMERS) 1330-20-7 < 18%

Federal Regulatory Information:ALL COMPONENTS OF THIS PRODUCT ARE
LISTED ON THE TOXIC SUBST

ANCE CONTROL ACT (TSCA) SECTION B(B)
INVENTORY OR EXEMPT FROM THE INVENTORY.

State Regulatory Information: CALIFORNIA PROPOSITION 65 STATUS: WARNING:
THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA
TO CAUSE CANCER. WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN
TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER
REPRODUCTIVE HARM. MASSACHUSETTS RIGHT TO KNOW: ETHYL BENZENE