

DEXTER CORP DEXTER ELECTRONI -- HYSOL PC18M

MSDS Safety Information

FSC: 5970

NIIN: 01-223-0782

MSDS Date: 04/17/1997

MSDS Num: CJSJS

Product ID: HYSOL PC18M

MFN: 01

Responsible Party

Cage: 04347

Name: DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV.

Address: 211 FRANKLIN ST.

City: OLEAN NY 14760-1297

Info Phone Number: 716-372-6300/6309

Emergency Ph

one Number: 716-372-6300

Item Description Information

Item Manager: S9G

Item Name: INSULATING VARNISH,ELECTRICAL

Unit of Issue: EA

UI Container Qty: 1

Type of Container: CAN

Ingredients

Name: \*\*\* PROPRIETARY \*\*\*

Health Hazards Data

LD50 LC50 Mixture: NOT PROVIDED

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: YES

IARC: YES

OSHA: NO

Effects of Exposure: TARGET ORGANS: EYES, SKIN, RESPIRATORY TRACT. EYE CONTACT:  
MAY CAUSE EYE IRRITATION. SKIN CONTACT: PROLONGED OR REPEATED SKIN CONTACT  
MAY CAUSE IRRITATION. CONTACT WITH PRODUCT AT ELEVATED TEMPERATURE S  
>150C) CAN RESULT I

N THERMAL BURNS. INHALATION: HARMFUL IF INHALED, MAY CAUSE ALLERGIC RESPIRATORY REACTION SUCH AS ASTHMA. INGESTION: MODERATELY TOXIC, MAY CAUSE VOMITING.

Explanation Of Carcinogenicity: CONTAINS BENZENE, 2,4-DIISOCYANATE-1-ME, BENZENE, 1,3-DIISOCYANATE-2-ME.

Signs And Symptions Of Overexposure: MAY CAUSE EYE IRRITATION. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION. CONTACT WITH PRODUCT AT ELEVATED TEMPERATURES (>150C) CAN RESULT IN THERMAL BURNS. HARMFUL IF INHALED, MAY

CAUSE ALLE RGIC RESPIRATORY REACTION SUCH AS ASTHMA. MODERATELY TOXIC BY INGESTION. MAY CAUSE VOMITING.

Medical Cond Aggravated By Exposure: PREEXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. PRE-EXISTING SKIN OR LUNG ALLERGIES MAY INCREASE THE CHANCE OF DEVELOPING INCREASED ALLERGIC SYMPTOMS TO THIS PRODUCT.

First Aid: EYE CONTACT: IMMEDIATELY WASH/ FLUSH EYES WITH WATER FOR MINIMUM 10 MINUTES. SEEK MEDICAL ATTENTION. SKIN CONTACT: WASH OFF IN FLOWING W

ATER OR

SHOWER. REMOVE CONTAMINATED CLOTHING AND SHOES. SEEK MEDICAL ATTENTION, IF IRRITATION DEVELOPS. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING, GIVE MOUTH TO MOUTH RESUSCITATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. SEEK MEDICAL ATTENTION. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. SEEK PROMPT MEDICAL ATTENTION. NOTE TO PHYSICIAN: TREATMENT SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS. THERE ARE NO SPECIFIC ANTIDOTES.

=====

=====

Handling and Disposal

=====

Spill Release Procedures: CLEAN-UP: CONTAIN SPILL IN NATURAL FORM OR WITH SAND OR DIRT. ELIMINATE ALL IGNITION SOURCES. PREVENT RUNOFF TO STORM SEWERS, DITCHES AND WATERWAYS. SHOVEL OR SCRAPE (NON-METALLIC) ABSORBED WASTE MATERIAL INTO DISPOSAL CONTAINER. SEAL LID TIGHTLY WITH TAPE AND LABEL PROPERLY. CLEAN UP SPILL IMMEDIATELY. OBSERVE PRECAUTIONS INCLUDING VENTILATIO

N AND/ OR

PERSONAL PROTECTIVE EQUIPMENT.

Neutralizing Agent: NOT RELEVANT.

Waste Disposal Methods: LEGAL DISPOSITION OF WASTE IS THE RESPONSIBILITY OF THE OWNER/ GENERATOR OF THE WASTE. APPLICABLE FEDERAL, STATE, AND/ OR LOCAL REGULATIONS MUST BE FOLLOWED DURING TREATMENT, STORAGE, OR DISPOSAL OF WASTE CONTAINING THIS PRODUCT. DO NOT DISPOSE OF IN AN UNCONTROLLED MANNER.

Handling And Storage Precautions: STORE AT LESS THAN TWENTY FIVE DEGREE CENTIGRADE (<25C) (77F) FOR OPTIMUM SHELF

LIFE. DRY ATMOSPHERIC  
CONDITIONS. KEEP CONTAINERS CLOSED AND TIGHTLY SEALED. PLASTIC CONTAINER MAY  
BE SLIPPERY WHEN HAND LING.  
Other Precautions: DO NOT EXPOSE TO DIRECT SUNLIGHT. ONCE CONTAINER IS OPEN,  
USE NITROGEN BLANKET ON MATERIAL AND RESEAL.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Method: CC  
Flash Point: =31.7C, 89.F  
Extinguishing Media: WATER FOG, CARBON DIOXI  
DE, DRY CHEMICAL, FOAM.  
Fire Fighting Procedures: RECOMMENDED USE OF SELF CONTAINED BREATHING APPARATUS  
(SCBA).  
Unusual Fire/Explosion Hazard: NO UNUSUAL FIRE OR EXPLOSION HAZARDS.

=====  
Control Measures  
=====

Respiratory Protection: NO RESPIRATOR IS REQUIRED IF INGREDIENT EXPOSURE LIMITS  
ARE NOT EXCEEDED. AN OSHA APPROVED (29CFR1910.134USA DEPT OF LABOR),  
AIR-PURIFYING RESPIRATOR WITH APPR  
OPRIATE CARTRIDGE SHOULD BE USED IF EXPOS  
URE LIMITS ARE EXCEEDED.  
Ventilation: USE LOCAL EXHAUST VENTILATION NEAR THE SOURCE.  
Protective Gloves: PVC, RUBBER (LATEX, NITRILE, BUTYL)  
Eye Protection: SAFETY GLASSES WITH SIDE SHIELD OR GOGGLES.  
Other Protective Equipment: A SAFETY SHOWER AND EYE WASH STATION SHOULD BE  
WITHIN REASONABLE DISTANCE TO THE WORK AREA.  
Work Hygienic Practices: NOT PROVIDED  
Supplemental Safety and Health: CONTRACTOR'S (CAGE: 7B953) PART NUMBER:  
MIL-I-46058C, HSOL DIV

=====  
Physical/Chemical Properties  
=====

HCC: F3  
NRC/State LIC No: NOT RELEVANT.  
B.P. Text: NOT PROVIDED  
M.P/F.P Text: NOT PROVIDED  
Decomp Text: NOT PROVIDED  
Vapor Pres: 9.5  
Vapor Density: 3.7  
Spec Gravity: 1.0  
VOC Pounds/Gallon: 4.6  
PH: NOT PROVIDED  
VOC Grams/Liter: 550  
Viscosity: NOT PROVIDED.  
Evaporation Rate & Reference: 0.5 NO REF  
Solubility in Water: SOLUBLE  
Appearance and Odor: LIQUI

D, MEDIUM VISCOSITY, AMBER COLOR, AROMATIC ODOR

Corrosion Rate: NOT PROVIDED

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: HIGH TEMPERATURES; OPEN FLAMES

Materials To Avoid: NONE IDENTIFIED

Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE; POSSIBLE ORGANICS

Hazardous Polymerization Indicator: YES

Conditions To Avoid Polymerization: EXOTHERMIC.

Toxicological Information

Toxicological Information: TESTING HAS NOT BEEN PERFORMED ON THIS PRODUCT. FOR DATA ON COMPONENTS, PLEASE PHONE 716-372-6300.

Ecological Information

Ecological: NO SPECIFIC STUDIES HAVE BEEN CONDUCTED. HOWEVER, UNCONTROLLED RELEASES OF CERTAIN CONSTITUENTS OF THIS MATERIAL TO SOIL, GROUNDWATER, OR SURFACE WATERS COULD ENTAIL ACUTE AND/OR CHRONIC ECOLOGICAL EFFECTS, DEPENDING ON THE QUANTITY AND CONCENTRATION OF SUCH RELEASES. RELEASES OF VOLATILE COMPONENTS TO THE ATMOSPHERE ARE NOT BELIEVED TO ENTAIL SIGNIFICANT ECOLOGICAL CONSEQUENCES PROVIDED SUCH RELEASES ARE WITHIN THE EXPOSURE LEVELS. ACCORDINGLY, ALL APPROPRIATE MEASURES SHOULD BE TAKEN TO AVOID UNCONTROLLED RELEASES TO THE ENVIRONMENT, AND ANY SPILLS SHOULD BE CONTAINED AND CLEANED UP IMMEDIATELY.

MSDS Transport Information

Transport Information: DOT/IATA PROPER SHIPPING NAME: RESIN SOLUTION, FLAMMABLE. DOT/IATA PACKING GROUP: III. DOT/IATA HAZARD CLASS OR DIV: 3. DOT/IATA LABEL: FLAMMABLE LIQUID. DOT/IATA PLACARD: FLAMMABLE LIQUID. DOT/IATA UN NUMBER: UN1866.

Regulatory

## Information

=====

Sara Title III Information: COMPONENT URETHANE PREPOLYMER AND COMPONENT 2-PROPANOL, 1-METHOX ARE SUBJECT TO ENVIRONMENTAL LIST SARA SECTION 311/312. COMPONENTS BENZENE, DIMETHYL- BENZENE, ETHYL-, BENZENE, METHYL- ARE SUB JECT TO ENVIRONMENTAL LIST SECTION 302AND CERCLA LISTS SARA SECTION 311/312 AND SARA SECTION 313. COMPONENT BENZENE, 1,3 DIISOCY IS SUBJECT TO THE FOLLOWING ENVIRONMENTAL LIST CERCLA

### HAZARD OUS SUBSTANCE

PROP65-C CA PROP 65 CARCINOGEN 304 SEC 302 AND CERCLA LISTS SARA SECT. 311/312 AND SARA SECT. 313

Federal Regulatory Information: RCRA STATUS THIS PRODUCT IS CLASSIFIED AS RCRA HAZARDOUS WASTE. OSHA STATUS THIS PRODUCT IS HAZARDOUS UNDER THE CRITERIA OF THE FEDERAL (USA) OSHA HAZARDOUS COMMUNICATION STANDARD 29 CFR 1910.1200. THERMAL PROCESSING AND DECOMPOSITION FUMES FROM THIS PRODUCT MAY BE HAZARDOUS.

State Regulatory Information: PROP65-T CA PROP 65 RE

PRODUCTIVE TOXIN: BENZENE,

METHYL- PROP 65-C THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: BENZENE, 1,3 DIISOCY.

## Other Information

=====

Other Information: ANY INGREDIENT CLAIMED AS A TRADE SECRET WILL BE DISCLOSED IN ACCORDANCE WITH 29 CFR 1910.1200 (I). WARNING! POSSIBLE IRRITATION TO EYES, SKIN AND RESPIRATORY TRACT.

## Transportation Information

=====

Responsible Party Cage: 04347

Trans ID NO: 149848

Product ID: HYSOL PC18M

MSDS Prepared Date: 04/17/1997

Review Date: 11/07/1999

MFN: 1

Net Unit Weight: 2.1 LBS

Multiple KIT Number: 0

Unit Of Issue: EA

Container QTY: 1

Type Of Container: CAN

Additional Data: LIMITED QUANTITIES ARE EXEMPT FROM LABELING AND PLACARDING; UNLESS OFFERED FOR TRANSPORTATION BY AIR , PACKED

IN STRONG OUTER PACKAGINGS;  
AND GROSS WEIGHT &lt; 66 LBS/30 KG, 49CFR 173.150. PROPER SHIPPING NAME, UN  
ID NUMBER, HAZARD CLASS AND PACKING GROUP, PER MSDS.

=====

Detail DOT Information

=====

DOT PSN QS  
DOT Proper Shipping Name: RESIN SOLUTION  
DOT PSN Modifier: FLAMMABLE  
Hazard Class: 3  
UN ID Num: UN1866  
DOT Packaging Group: III  
Label: FLAMMABLE LIQUID  
Special Provision: B1,B52,T7,T30  
Packag  
ing Exception: 150  
Non Bulk Pack: 173  
Bulk Pack: 242  
Max Qty Pass: 60 L  
Max Qty Cargo: 220 L  
Vessel Stow Req: A

=====

Detail IMO Information

=====

IMO PSN Code: NBJ  
IMO Proper Shipping Name: RESIN,SOLUTION  
IMO PSN Modifier: FLAMMABLE o  
IMDG Page Number: 3379  
UN Number: 1866  
UN Hazard Class: 3.3  
IMO Packaging Group: III  
Subsidiary Risk Label: -  
EMS Number: 3-05  
MED First Aid Guide NUM: 310

=====

=====

Detail IATA Information

=====

IATA PSN Code: VSA  
IATA UN ID Num: 1866  
IATA Proper Shipping Name: RESIN SOLUTION  
IATA PSN Modifier: ,FLAMMABLE  
IATA UN Class: 3  
IATA Label: FLAMMABLE LIQUID  
UN Packing Group: III  
Packing Note Passenger: 309  
Max Quant Pass: 60L  
Max Quant Cargo: 220L  
Packaging Note Cargo: 310

=====

Detail AFI Information

=====

=====

AFI PSN Code: VSA  
AFI Proper Shipping Name: RESIN SOLUTION  
AFI PSN Modifier: ,FLAMMABLE  
AFI Hazard Class: 3  
AFI UN ID NUM: UN1866  
AFI Packing Group: III  
Special Provisions: P5  
Back Pack Reference: A7.3

=====

HAZCOM Label

=====

Product ID: HYSOL PC18M  
Cage: 04347  
Company Name: DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV  
Street: 211 FRANKLIN ST.  
City: OL  
EAN NY  
Zipcode: 14760-1297  
Health Emergency Phone: 716-372-6300  
Label Required IND: Y  
Date Of Label Review: 08/18/2000  
Status Code: C  
MFG Label NO: P00011 650  
Label Date: 04/17/1997  
Year Procured: 2000  
Origination  
Eye Protection IND: YES  
Skin Protection IND: YES  
Signal Word: DANGER  
Respiratory Protection IND: NO  
Health Hazard: Moderate  
Contact Hazard: Slight  
Fire Hazard: Severe  
Reactivity Hazard: None  
Hazard And Precautions: TARGET ORGANS: EYES, SKIN, RESPIRATORY TRACT. WARNING:  
MAY CAUSE INJURY TO SKIN FOLLOWING PROLONGED OR REPEATED CONTACT. FLAMMABLE!  
FREQUENT PROLONGED OR FREQUENT SKIN CONTACT: IF CONTACT OCCURS, WASH AT  
FIRST OPPORTUNITY WITH SOAP AND WATER. KEEP AWAY FROM HEAT, SPARKS AND OPEN  
FLAME. USE WITH ADEQUATE VENTILATION. WARNING! THIS PRODUCT CONTAINS A  
CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. FOR INDUSTRIAL  
USE ONLY. KEEP CONTAINER CLOSED. SOME MATERIALS OF THIS TYPE ABSORB CHEMICALS  
FROM THE AIR WHICH CAN RESULT IN A CHANGE OF PROP

ERTIES.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any

instrumentality of the United

States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.