Product ID:EASE OFF #990 MSDS Date:10/17/1994 FSC:8030 NIIN:00-664-6146 Status Code:A MSDS Number: CKCXW === Responsible Party === Company Name: TEXACONE CO Address:4111 FORNEY RD City:MESQUITE State:TX ZIP:75149-2722 Country:US Emergency Phone Num:214-363-1891 CAGE:87889 === Contractor Identification === Company Name: TEXACONE CO THE Address:4111 FORNEY RD Box:City:MESQUITE Stat e:TX ZIP:75149-2722 Country:US Phone:800-235-2727 CAGE:87889 

Ingred Name:RED LEAD CAS:1314-41-6 RTECS #:OG5425000 Fraction by Wt: 19% OSHA PEL:0.05 MG/M3 ACGIH TLV:0.15 MG/M3

Ingred Name:DIBUTYL PHTHALATE CAS:84-74-2 RTECS #:TI0875000 Fraction by Wt: 33.5% OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name:MOLYBDENUM DISULFIDE CAS:1317-33-5 RTECS #:QA4697000 Fraction by Wt: 25.4% OSHA PEL:1

======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:ACUTE - ENCEPHALOPATHY DEVELOPS QUICKLY TO SEIZURES, COMA AND DEATH. CHRONIC - SEVERE DAMGE TO BLOOD FORMING, NERVOUS, URINARY AND REPRODUCTIVE SYSTEMS. Effects of Overexposure:LOSS OF APPETITE, METALLIC TASTE IN MOUTH, ANXIETY, CONSTIPATION, NAUSEA, PALLOR, INSOMNIA, HEADACHE, ABDOMINAL PAI N.
Medical Cond Aggravated by Exposure:TARGET ORGANS ) : GASTROINTESTINAL, CENTRAL NERVOUS SYSTEM, KIDNEYS, BLOOD, GINGIVAL TISSUE.
======================================
First Aid:EYE - IRRIGATE IMMEDIATELY. SKIN - SOAP FLESH PROMPTLY. BREATH - ARTIFICIAL RESPIRATION. SWALLOW - WATER; VOMIT
======================================
Flash Point Method:COC Flash Point:=154.4C, 310.F =310F Extinguishing Media:CO2 OR DRY C HEMICAL
======================================
Spill Release Procedures: TREAT AS IF AN OIL SPILL. KEEP AWAY FROM FLAMES
======================================
Handling and Storage Precautions:NO SPECIAL REQUIREMENTS - INDEFINITE SHELF LIFE.
======================================
Respiratory Protection: APPROPRIATE RESPIRATORY PROTECTION MAY BE REQUIRED.

Ventilation:LOCAL EXHAUST-VENTED FAN SP

ECIAL : NONE MECHANICAL : NO Supplemental Safety and Health UNLESS EXPOSURE TO LEAD ABOVE PEL.

Melt/Freeze Pt:>51.7C, 125.F M.P/F.P Text:>125F Spec Gravity:( H2O=1 ): 1.67 Evaporation Rate & amp; Reference:( BUTYL ACETATE=1 ) Appearance and Odor:BROWN PASTE, PAINT-LIKE ODOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS, HYDROGEN PEROXIDE ACTIVE METALS (SODIUM POTASSIUM).

Hazardous Decomposition Products:CO, CO2, AND HEAVY METAL OXIDES.

Toxicological Information:RED\_LEAD OXIDE: 1 PR LD-50 630 MG/KG RAT DIBUTYL PHTHALATE: ORAL LD-50 (RAT): 30.6 G/KG\_DERMAL LD-50 ( RABBIT) : 720 ML/KG\_EYE IRRITATION (RABBIT) : SLIGHT MOLYBDENUM DISULFIDE: ACUTE\_ORAL (RAT) >15,000 MG/KG - NO EFFECT\_DERMAL\_IRRITATION: (RABBIT) 0.5 GRAMS -NO IRRITATION EYE IRRITATION: (RABBIT) 0.1 GRAM - NO IRRITATION.

Waste Disposal Methods: SECURE LAND BURIAL OR INCINERATED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or imp lied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.