

MSDS Safety Information

FSC: 8030  
NIIN: 01-367-7357  
MSDS Date: 03/03/1992  
MSDS Num: CKDYK  
Product ID: SKYFLEX AIRCRAFT SEALANT  
MFN: 01  
Responsible Party  
Cage: 0AMD8  
Name: W L GORE & ASSOCIATES INC  
Address: 100 AIRPORT RD  
Box: 1010  
City: ELKTON MD 21922-1010  
Info Phone Number: 410-392-3200  
Emergency Phone Number: 1-410-392-3200  
Preparer's Name: THOMAS E. DYKES  
Review Ind: Y  
Published: Y

Contractor Summary

Cage: 0AMD8  
Name: W. L. GORE & ASSOCIATES INC, INDUSTRIAL SEALANT GROUP  
Address: 100 AIRPORT RD  
City: ELKTON MD 21921  
Phone: 410-392-3200

Item Description Information

Item Manager: GSA  
Item Name: SEALING COMPOUND  
Unit of Issue: RO  
Quantitative Expression: 00000000100FT  
UI Container Qty: 0  
Type of Container: ROLL

Health Hazards Data

Effects of Exposure: PTFE, WHEN THERMALLY DECOMPOSED MAY CAUSE POLYMER FUME FEVER AND FLU-LIKE SYMPOMS.  
First Aid: ON EXPOSURE TO THERMAL DECOMPOSITION PRODUCTS: INHALATION - MOVE TO FRESH AIR. SKIN CONTACT -

WASH WITH SOAP AND WATER  
EYE CONTACT - FLUSH WITH WATER FOR A T LEAST 15 MINUTES.  
CALL A PHYSICIAN.

=====

Handling and Disposal

=====

Spill Release Procedures: SWEEP OR PICK UP AND DISPOSE OF AS REGULAR TRASH.  
Waste Disposal Methods: LANDFILL PREFERRED. CONFROM TO LOCAL, STATE, AND  
FEDERAL REGULATIONS.  
Other Precautions: STEPS SHOULD BE TAKEN NOT TO CONTAMINATE TOBACCO AND SMOKING  
UTENSILS, AS THERMALLY DECOMPOSED MATERIAL MAY CAUSE POLYMER FUME FEVER.

=====

Fire and Explosion Hazard Information

=====

Fire Fighting Procedures: PTFE DOES NOT BURN WITHOUT AN EXTERNAL SOURCE OF  
FUEL. IN EXTREME FIRE SITUATIONS, USE SELF-CONTAINED BREATHING APPARATUS AS  
TOXIC FLOURINE COMPOUNDS ARE EVOLVED IN A FIRE.  
Unusual Fire/Explosion Hazard: PTFE WILL BURN IN 95% OXYGEN ATMOSPHER  
E WHEN AN  
IGNITION SOURCE IS PRESENT. DO NOT USE PRODUCT WITH ADHESSIVE IN COMPRESSED  
OXYGEN SERVICE.

=====

Control Measures

=====

Respiratory Protection: WHEN PROCESSED AT ELEVATED TEMPERATURES, USE ADEQUATE  
VENTILATION.  
Ventilation: LOCAL EXHUAST AT TEMPERATURES ABOVE 752 F.  
Work Hygienic Practices: WASH HANDS AFTER HANDLING.  
Supplemental Safety and Health: USE PROTECTIVE EQUIPMENT AS RE  
QUIRED BY YOUR  
COMPANY.

=====

Physical/Chemical Properties

=====

B.P. Text: `  
Spec Gravity: 0.4 - 1.7  
Appearance and Odor: GRAY, RIBBED, MARSHMALLOWY TAPE, ODORLESS

=====

Reactivity Data

=====

Stability Indicator: YES  
Stability Condition To Avoid: TEMPERATURES ABOVE 400'C/ 752'F AND INCINERATION

Materials To Avoid: MOLTEN ALKALI METALS AND SOME REACTIVE INTERHALOGEN COMPOUNDS.

Hazardous Decomposition Products: HYDROGEN FLUOURIDE AND PERFLUOROCARBON OLEFINS MAY BE EVOLVED ABOVE 400'C/752'F

Regulatory Information

Sara Title III Information: THIS PRODUCT IS NOT SUBJECT TO THE REPORTING REQUIRMENTS OF THE SECTION 313 OF TITLE III OF SUPERFUND AMENDMENTS AND REAUTHORIZAT ION ACT OF 1986 AND 40 CFR PART 372

Other Information

Other Information: 1.625 INCHES WIDE UNIT PRICE 2485.43

Transportation Information

Responsible Party Cage: 0AMD8  
Trans ID NO: 151971  
Product ID: SKYFLEX AIRCRAFT SEALANT  
MSDS Prepared Date: 03/03/1992  
Review Date: 01/26 /2000  
MFN: 1  
Multiple KIT Number: 0  
Unit Of Issue: RO  
Container QTY: 0  
Type Of Container: ROLL

Detail DOT Information

DOT PSN Code: ZZZ  
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail IMO Information

IMO PSN Code: ZZZ  
IMO Proper Shipping Name:

NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: SKYFLEX AIRCRAFT SEALANT

Cage: 0AMD8

Company Name: W. L. GORE & ASSOCIATES INC, INDUSTRIAL SEALANT GROUP

Street: 100 AIRPORT RD

City: ELKTON MD

Zipcode: 21921

Health Emergency Phone: 1-410-392-3200

Label Required IND: Y

Date Of Label Review: 03/16/2000

Status Code: A

Origination Code: G

Hazard And Precautions: PTFE, WHEN THERMALLY DECOMPOSED MAY CAUSE POLYMER FUME  
FEVER AND FLU-LIKE SYMPOMS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.