

CAAP CO INC -- CAAPCOAT FP200 COLOR MATCHED POLYURITHANE RAIN EROSION COATI --
8010-01-235-0828

===== Product Identification =====

Product ID:CAAPCOAT FP200 COLOR MATCHED POLYURITHANE RAIN EROSION COATI

MSDS Date:09/01/1996

FSC:8010

NIIN:01-235-0828

Status Code:A

MSDS Number: CKNMR

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

City:MILFORD

State:CT

ZIP:06460

Country

:US

Info Phone Num:203-877-0375

Emergency Phone Num:7035273887

Chemtrec Ind/Phone:(800)424-9300

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISO-BUTYL KETONE MIBK

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 13%

Other REC Limits:75PPPM-STEL

OSHA PEL:50PPM TWA

ACGIH TLV:50PPM TWA

EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 39%
Other REC Limits:150PPM-STEL
OSHA PEL:100PPM
ACGIH TLV:100PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYLENEBIS(4-CYCLOHEXYL ISOCYANATE)
CAS:5124-30-1
RTECS #:HQ9250000
Fraction by Wt: 116.1C, 241.F
B.P. Text:241-281F **
Melt/Freeze Pt:M.P/F.P Text:NA
Vapor Pres:8MMHG
Vapor Density:3.6AIR=1
Spec Gravity:1.007(COATING)H2O=1
VOC Pounds/Gallon:541
VOC Grams/Liter:4.5
Evaporation Rate & Reference:0.85 BUTYL ACETATE =1
Solubility in Water:INSOLLUABLE (COATING)
Appearance and Odor:LIGHT TO DARK GRAY OR GREEN LIQUID, AROMATIC
SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
THE PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:SHOULD BE KEPT AWAY FROM ALL IGNITION
SOURCES, HOT SURFACES, AND TEMPERATURES ABOVE 100 DEG. F.
Hazardous Decomposition Products:CARBON MONOXIDE CARBON DIOXIDE OXIDES
OF NITROGEN AS WELL AS TRACES OF HCN MAY BE RELEASED DURING
COMBUSTION.

===== Toxicological Information =====

Toxicological Information:* OVERSHOES IS REQUIRED. WEAR SOLVENT
RESISTANT APRON AND BOOTS FOR SPILLS. AN EYE WASH AND SAFETY SHOWER
SHOULD BE NEARBY AND READY FOR USE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION IN A PROPERLY DESIGNED

AND LICENCED
INCNRATR IS PREFERRED; THIS IS RCRA HAZARDOUS IGNITABLE WASTE.
REGULATIONS MAY VARY FROM STATE TO STATE; DISPOSE OF ACCOR. TO
STATE AND FDERAL RGLATIONS. WHEN THE FP-200, CURING AGENT AND
ACCLEATR ARE MIXED AND THE SOLVENT IS ALLOWED TO EVAPORATE, THE SO
LID END POODUCT IS A NON=HAZARDOUS LANDFILL ITEM.

===== MSDS Transport Information =====

Transport Information:SHIPPING NAME PAINT RELATED MATERIAL. DOT
CLASSIFICATION 3 (FLA
MMABLE LIQUID)

===== Regulatory Information =====

SARA Title III Information:MIBK XYLENE CHROMIUM III OXIDE GREEN, COPPER
PHTHALOCYANINE BLUE.
State Regulatory Information:THE FOLLOWING CHEMICALS ARE LISTED BY
INDIVIDUAL STATES. FOR MORE COMPLETE INFORMATION, CONTACT THE
APPROPRIATE AGENCY IN YOUR STATE. OTHER PRODUCT SPECIFIC HEALTH AND
SAFETY DATA IN OTHER SECTIONS IN THE MSDS MAY ALSO BE ALPPLICALLE
FOR STATE REQUIREMENTS. FOR DETAILS O
N YOUR REGULATORY
REQUIREMENTS, YOU SHOULD CONTACT THE APPROPRIATE AGENCY IN YOUR
STATE. MIBK: =MA, PA RIGHT-TO-KNOW XYLENE=MA, PA, RIGHT-TO-KNOW.
METHALENE BIS(4CYCLOHEXYLISOCYANATE)=MA, NJ, PA, RIGHT-TO-KNOW.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoe
ver,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.