

SAFT NIFE INC -- 401096-017, INDUSTRIAL NICKEL CADMIUM STORAGE BATTERY --
6140-01-274-8889

===== Product Identification =====

Product ID:401096-017, INDUSTRIAL NICKEL CADMIUM STORAGE BATTERY

MSDS Date:06/16/1994

FSC:6140

NIIN:01-274-8889

Status Code:A

MSDS Number: CKQYN

=== Responsible Party ===

Company Name:SAFT NIFE INC

Address:711 INDUSTRIAL BLVD

Box:1886

City:VALDOSTA

State:GA

ZIP:31603-1886

Country:US

Info Phone Num:912-247-2331

Emergency Phone Num:912-24

7-2331

Chemtrec Ind/Phone:(800)424-9300

CAGE:1HB35

=== Contractor Identification ===

Company Name:SAFT AMERICA INC.

Address:711 INDUSTRIAL BLVD

Box:1886

City:VALDOSTA

State:GA

ZIP:31602

Country:US

Phone:912-247-2331

CAGE:09052

Company Name:SAFT NIFE INC

Address:711 INDUSTRIAL BLVD

Box:1886

City:VALDOSTA

State:GA

ZIP:31603-1886

Country:US

Phone:912-247-2331

CAGE:1HB35

===== Composition/Information on Ingredients =====

Ingred Name:ACRYLIC POLYMER CONTAINER

= Wt:10.

Ingred Name

:POLYSULFONE CONTAINER

= Wt:10.

Ingred Name:POLYPROPYLENE CONTAINER

= Wt:10.

Ingred Name:NICKEL OXIDE, SOLID

CAS:1313-99-1

RTECS #:QR8400000

= Wt:10.

OSHA PEL:1 MG/M3

Ingred Name:LITHIUM HYDROXIDE

CAS:1310-66-3

< Wt:1.

Ingred Name:GRAPHITE

CAS:7782-42-5

RTECS #:MD9659600

= Wt:3.

OSHA PEL:SEE TABLE Z-3

ACGIH TLV:2 MG/M3

Ingred Name:ELECTROLYTE SOLUTION (18-28% POTASSIUM HYDROXIDE)

CAS:1310-58-3

RTECS #:TT2100000

= Wt:28.

ACGIH STEL:C2 MG/M3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingre

d Name:STEEL

= Wt:39.

Ingred Name:CADMIUM OXIDE

CAS:1306-19-0

RTECS #:EV1925000

= Wt:9.

===== Hazards Identification =====

LD50 LC50 Mixture:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO

Health Hazards Acute and Chronic:EYE: CONTACT WITH ELECTROLYTE SOLUTION
CAUSES RAPID, SEVERE DAMAGE. EXTREMELY CORROSIVE TO EYE TISSUES.
MAY RESULT IN PERMANENT BLINDNESS. CONTACT WITH NICKEL OXIDE MAY
CAUSE

IRRITATION. SKIN: CONTACT WITH ELECTROLYTE SOLUTION MAY CAUSE SERIOUS BURNS TO SKIN TISSUES. CONTACT WITH NICKEL COMPOUNDS MAY CAUSE SKIN SENSITIZATION. INGESTION: INGESTION OF ELECTROLYTE CAUSES TISSUE DAMAGE TO THROAT & GAS TRO/RESPIRATORY TRACT. INGESTION OF NICKEL CAUSES NAUSEA & INTESINAL DISORDERS. INHALATION: MIST GENERATED DURING ACTIVATION MAY CAUSE VARYING DEGREES OF RESPIRATORY IRRITATION. INHALATION OF CADMIUM MAY CAUSE IRRITATION, PULMONARY EDEMA.

Expl
anation of Carcinogenicity:NIOSH RECOMMENDS THAT NICKEL AND CADMIUM BE TREATED AS OCCUPATIONAL CARCINOGENS.

Effects of Overexposure:EYES: IRRITATION, BLINDNESS, RAID/SEVERE DAMAGE. SKIN: BURNS, CHRONIC ECZEMA, NICKEL ITCH. INGESTION: THROAT DAMAGE, NAUSEA, INTERNAL DISORDERS. INHALED: DRY THROAT, COUGH, HEADACHE, VOMITING, CHEST P AIN, CHILLS, PULMONARY EDEMA, BREATHING DIFFICULTY, PROSTRATION.

Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY RESPONSIBLE PARTY.

==
===== First Aid Measures =====

First Aid:ELECTROLYTE: EYE CONTACT: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION. SKIN CONTACT: REMOVE CONTAMINATED CLOTHING & FLUSH AFFECTED AREAS WITH PLENTY OF WATER FO R AT LEAST 15 MINUTES. INGESTION: DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER. IF AVAILABLE, GIVE SEVERAL GLASSES OF MILK. GET IMMEDIATE MEDICAL ATTENTION. DO NOT GIVE ANYTHING BY MOUTH TO UNCON
SCI OUS PERSON. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED. GET IMMEDIATE MEDICAL ATTENTION. NICKEL OXIDE: SKIN CONTACT: WASH WITH SOAP & WATER.

===== Fire Fighting Measures =====

Extinguishing Media:CO2, SAND.
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS TO AVOID BREATHING TOXIC FUMES. WEAR PROTECTIVE CLOTHING AND EQUIPMENT TO PREVENT POTENTIAL BODY CONTACT WITH ELECTROLYTE SOLUTION OR

MIXTURE OF WATER AND SOLUTION. DISCONNECT OR CUT ALL CABLES TO AND FROM BATTERY.

Unusual Fire/Explosion Hazard:ELECTROLYTE SOLUTION IS CORROSIVE TO ALL HUMAN TISSUES. IT WILL REACT WITH MANY ORGANIC MATERIALS. ELECTROLYTE REACTS WITH ZINC, ALUMINUM, TIN & OTHER REACTIVE METALS RELEASING FLAMMABLE HYDROGEN GAS. CADMIUM FUMES MAY BE RELEASED WHEN BATTERIES ARE SUBJECTED TO HIGH TEMPERATURES.

===== Accidental Release Measures =====

Spill Release

Procedures:ELECTROLYTE SPILLS: SMALL (UP TO 5 GALLONS):

FLUSH WITH WATER AND NEUTRALIZE WITH DILUTE CITRIC ACID. LARGE SPILL: CONTAIN MATERIAL IN SUITABLE CONTAINER OR HOLDING AREA. DO NOT ALLOW MATERIAL TO ENTER SEWERS, STREAMS OR STORM CONDUITS. RECOVER MATERIAL WITH VACUUM TRUCK & DISPOSE OF PROPERLY. REPORTABLE QUANTITY: 1000 LBS. 40 CFR 117.13.

Neutralizing Agent:DILUTE CITRIC ACID.

===== Handling and Storage =====

Handling and Storage

Precautions:PERFORM ACTIVATION PROCEDURES IN A

WELL VENTILATED AREA. BATTERY OPERATING AREAS MUST BE WELL VENTILATED TO REMOVE NORMAL GASES GENERATED. DO NOT ALLOW AN EXPOSED FLAME OR SPARK TO COME NEAR THE CELLS.

Other Precautions:NEVER ACTIVATE OR TOP OFF WITH ACID! DO NOT TRANSPORT BATTERY WITH VENT CAP IN PLACE. WHEN REMOVING BATTERY FROM SERVICE VISUALLY INSPECT FOR LEAKAGE PRIOR TO HANDLING. IF LEAKAGE HAS OCCURRED FOLLOW SPILL MANAGEMENT PROCEDURES.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED MIST RESPIRATOR DURING

ACTIVATION AND ACTUAL USAGE TO MAINTAIN EXPOSURE LEVELS BELOW THE TWA.

Ventilation:PERFORM ACTIVATION IN A WELL-VENTILATED AREA. BATTERY

OPERATING AREAS MUST BE WELL VENTILATED TO REMOVE NORMAL GASES GENERATED.

Protective Gloves:WATER-INSOLUBLE NON-PERMEABLE GLOVES-SYNTHETIC RUBBER (NOT WOOL OR LEATHER!)

Eye Protection:SPLASH GOGGLES OR FACE SHIELD.

O

ther Protective Equipment: RUBBER BOOTS, RUBBER APRON OR RAINWEAR OR EQUIVALENT IF EXPOSURE TO ELECTROLYTE SOLUTION IS LIKELY.

Work Hygienic Practices: NO DATA PROVIDED BY RESPONSIBLE PARTY.

Supplemental Safety and Health

NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Physical/Chemical Properties =====

HCC: B1

Vapor Pres: 2 MM HG @ 68F

Spec Gravity: 1.17-1.25 (ELECTROLYTE)

Evaporation Rate & Reference: NOT DETERMINED

Solubility in Water: ELECTROLYTE-COMPLETE

Appearan

ce and Odor: NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Stability and Reactivity Data =====

ALUMINUM ZINC, TIN & OTHER ACTIVE METALS; ACID, CHLORINATED & AROMATIC HYDROCARBONS, NITROCARBONS, HALOCARBONS, TRICHLOROETHYLENE.

Stability Condition to Avoid: NO DATA PROVIDED BY RESPONSIBLE PARTY.

Hazardous Decomposition Products: NICKEL OXIDE, CADMIUM, CADMIUM OXIDE, POTASSIUM HYDROXIDE. NOTE: THE NORMAL REACTIONS INSIDE THE BATTERY RELEASE FLAMMABLE HYDROGEN GAS. DO SEAL BATTERY FROM ATMOSPHERE.

===== Toxicological Information =====

Toxicological Information: NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Ecological Information =====

Ecological: NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Disposal Considerations =====

Waste Disposal Methods: THIS STORAGE BATTERY IS A HAZARDOUS WASTE UNDER RCRA. IT MAY BE RETURNED TO SAFT NIFE FOR RECYCLING. BATTERY IS

TCLP TOXIC. BATTERY & ELECTROLYTE ARE CORROSIVE. IF NOT RECYCLED, MUST BE DISPOSED OF IN ACCORDANCE WITH ALL FEDERAL, STATE & LOCAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information: NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Regulatory Information =====

SARA Title III Information: NO DATA PROVIDED BY RESPONSIBLE PARTY.

Federal Regulatory Information: NO DATA PROVIDED BY RESPONSIBLE PARTY.

St

ate Regulatory Information:NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek
competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.