

3M GENERAL OFFICES -- SCOTCH-GRIP 847 RUBBER AND GASKET ADHESIVE

=====

MSDS Safety Information

=====

FSC: 5330

NIIN: 01-417-4848

MSDS Date: 11/20/1992

MSDS Num: CKSRJ

Product ID: SCOTCH-GRIP 847 RUBBER AND GASKET ADHESIVE

MFN: 01

Kit Part: Y

Responsible Party

Cage: 76381

Name: 3M GENERAL OFFICES

Address: 3M CENTER

City

: ST PAUL MN 55144-1000

Info Phone Number: 1-800-364-3577

Emergency Phone Number: 612-733-1110

=====

Item Description Information

=====

Item Manager: S9I

Item Name: PARTS KIT,SEAL REPLACEMENT,MECHANICAL EQUIPMENT

Unit of Issue: EA

UI Container Qty: Y

=====

Ingredients

=====

Cas: 67-64-1

RTECS #: A

L3150000

Name: ACETONE

% low Wt: 60.

% high Wt: 70.

OSHA PEL: 2400 MG/M3;1000 PPM

ACGIH TLV: 1780 MG/M3;750 PPM

ACGIH STEL: 2380 MG/M3;1000 PPM

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

-----

Cas: 9003-18-3

Name: ACRYLONITRILE-BUTADIENE POLYMER

% low Wt: 10.

% high Wt: 20.

-----

Cas: 9003-35-4

Name: PHENOL-FORMALDEHYDE POLYMER

% low Wt: 7.

% high Wt: 13.

-----

Cas: 8050-31-5

Name: GLYCEROL ESTERS OF ROSIN ACIDS

% low Wt

: 7.  
% high Wt: 13.

-----  
Cas: 69-72-7  
RTECS #: VO0525000  
Name: SALICYLIC ACID  
% low Wt: 1.  
% high Wt: 5.  
-----

Cas: 1314-13-2  
RTECS #: ZH4810000  
Name: ZINC OXIDE  
&lt; Wt: 2.  
OSHA PEL: 15 MG/M3  
-----

Cas: 68411-46-1  
Name: ANTIOXIDANT  
&lt; Wt: 1.

=====

Health Hazards Data

=====

Effects of Exposure: EYE: MODERATE EYE IRRITATION. SKIN: MILD SKIN IRRITATION (AFTER PROLONGED OR REPEATED CONTACT). INHALATION: CENTRAL NERVOUS SYSTEM DEPRESSION; UPPER RESPIRATORY IRRITATION. INGESTION: IRRITATION OF GASTROINTESTINAL TISSUES, CENTRAL NERVOUS SYSTEM DEPRESSION; ASPIRATION PNEUMONITIS.

Signs And Symptoms Of Overexposure: EYE: REDNESS, SWELLING, PAIN, TEARING, HAZY VISION. SKIN: REDNESS, SWELLING, ITCHING. INHALATION: HEADACHE, DIZZINESS, DROWSINESS, INCOORDINATION, SLOWED REACTION TIME, SLURRED SPEECH, GIDDINESS AND UNCONSCIOUSNESS, SORENESS OF THE NOSE AND THROAT, COUGHING, SNEEZING. INGESTION: PAIN, VOMITING, ABDOMINAL TENDERNESS, NAUSEA, BLOOD IN VOMITUS, AND BLOOD IN FECES. ALSO, DIZZINESS, HEADACHE, DROWSINESS, MUSCULAR WEAKNESS, INCOORDINATION, SLOWED REACTION TIME, FATIGUE, BLURRED VISION, SLURRED SPEECH, GIDDINESS, TREMORS AND CONVULSIONS. DIFFICULTY BREATHING, WHEEZING, COUGHING UP BLOOD AND PNEUMONIA CAN BE FATAL.

First Aid: EYE: IMMEDIATELY FLUSH EYE WITH LARGE AMOUNTS OF WATER. GET IMMEDIATE MEDICAL ATTENTION. SKIN: FLUSH SKIN WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. SWALLOWED: CALL A PHYSICIAN IMMEDIATELY. ONLY INDUCE VOMITING AT THE INSTRUCTION OF A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. INHALATION: REMOVE PERSON TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING DIFFICULT, GET IMMEDIATE MEDICAL ATTENTION.

=====

Hand

## ling and Disposal

=====

Spill Release Procedures: REFER TO OTHER SECTIONS OF THIS MSDS FOR INFORMATION REGARDING PHYSICAL & HEALTH HAZARDS RESPIRATORY PROTECTION, VENTILATION AND PERSONAL PROTECTIVE EQUIPMENT. CALL (612)733-1110 OR (612)733-6100 FOR 24-HOUR SPILL ASSISTANCE. VENTILATE AREA. EXTINGUISH ALL IGNITION SOURCES. COLLECT USING NON-SPARKING TOOLS. COVER WITH ABSORBENT MATERIAL. PLACE IN US DOT-APPROVED CONTAINER AND SEAL.

Waste Disposal Methods: INCINERATE IN A PERMITTED HAZARDOUS WASTE INCINERATOR IN THE PRESENCE OF A COMBUSTIBLE MATERIAL. DISPOSE OF WASTE PRODUCT IN A FACILITY PERMITTED TO ACCEPT CHEMICAL WASTE. SINCE REGULATIONS VARY, CONSULT APPLICABLE REGULATIONS OR AUTHORITIES BEFORE DISPOSAL. US EPA HAZARDOUS WASTE NUMBER = D001 (IGNITABLE)

Handling And Storage Precautions: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

Other Precautions: KEEP CONTAINER TIGHTLY CLOSED. FLAMMABLE LIQUID AND VAPOR.

KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME, AND OTHER SOURCES OF IGNITION. GROUND CONTAINERS SECURELY WHEN TRANSFERRING CONTENTS. WEAR LOW STATIC OR PROPERLY GROUNDED SHOES.

## Fire and Explosion Hazard Information

Flash Point Method: TCC

Flash Point: -17.6C, 0.F

Flash Point Text: ACETONE

Autoignition Temp Text: N/D

Lower Limits: N/D

Upper Limits: N/D

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: WEAR FULL PROTECTIVE CLOTHING, INCLUDING HELMET, SELF-CONTAINED, POSITIVE PRESSURE OR PRESSURE DEMAND BREATHING APPARATUS, INCLUDING BUNKER COAT AND PANTS, BANDS AROUND ARMS, WAIST/LEGS, FACE MASK AND PROTECTIVE COVERING FOR EXPOSED AREAS OF HEAD.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO HEAT FROM FIRE MAY BUILD PRESSURE AND EXPLODE. VAPORS MAY TRAVEL LONG DISTANCES ALONG THE GROUND OR FLOOR TO AN IGNITION SOURCE AND FLASH BACK.

## Control Measures

Respiratory Protection: AVOID PROLONGED BREATHING OF VAPORS. SELECT ONE OF THE FOLLOWING NIOSH APPROVED RESPIRATORS BASED ON AIRBORNE CONCENTRATION OF CONTAMINANTS AND IN ACCORDANCE WITH OSHA REGULATIONS; HALF-MASK ORGANIC VAPOR RESPIRATOR.

Ventilation: USE IN WELL VENTILATED AREA. IF EXHAUST VENTILATION IS NOT ADEQUATE

, USE APPROPRIATE RESPIRATORY PROTECTION.  
Protective Gloves: BUTYL RUBBER, POLYETHYLENE/ETHYLENE VINYL ALCOHOL,  
POLYTETRAFLUOROETHYLENE  
Eye Protection: VENTED GOGGLES, SAFETY GLASSES WITH SIDE SHIELDS  
Work Hygienic Practices: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF  
REACH OF CHILDREN.

=====

Physical/Chemical Properties

=====

HCC: F2  
Boiling Point: =55.6C, 132.F  
B.P. Text: ACETONE  
Va  
por Pres: 180MMHG  
Vapor Density: 2.0  
Spec Gravity: 0.91  
PH: N/D  
VOC Grams/Liter: 583  
Viscosity: 2,750 CPS  
Evaporation Rate & Reference: 1.9  
Solubility in Water: SLIGHT  
Appearance and Odor: DARK BROWN LIQUID; SHARP SOLVENT ODOR  
Percent Volatiles by Volume: 64 (WEIGHT)

=====

Reactivity Data

=====

Stability Indicator: YES  
Materials To Avoid: STRONG OXIDIZING AGENTS.  
Hazardous Decomposition Produ  
cts: CARBON MMONOXIDE, CARBON DIOXIDE, OXIDES OF  
NITROGEN, HYDROGEN CYANIDE, ALDEHYDES, KETONES, HYDROCARBONS, OXIDES OF ZINC  
Hazardous Polymerization Indicator: NO  
Conditions To Avoid Polymerization: WILL NOT OCCUR.

=====

Toxicological Information

=====

=====

Ecological Information

=====

=====

=====

MSDS Transport Information

=====

=====

Regulatory Information

=====

=====

Other Information

=====

=====

Transportation Information

=====

=====

Responsible Party Cage: 76381  
Trans ID NO: 154539  
Product ID: SCOTCH-GRIP 847 RUBBER AND GASKET ADHESIVE  
MSDS Prepared Date: 11/20/1992  
Review Date: 08/28/2000  
MFN: 1  
Net Unit Weight: UNKNOWN  
Multiple KIT Number: 0  
Kit Part IND: Y  
Unit Of Issue: EA  
Container QTY: Y  
Additional Data: PSN FOR DOT/IATA/AFI BASED ON LABELS ACCOMAPNYING MSDS. IMO IS  
BEST GUESS BY DLA- STAFF.

=====

Detail DOT Information

=====

=====

DOT PSN Code: DTJ  
Symbols: D  
DOT Proper Shipping Name: CONSUMER COMMODITY  
Hazard Class: ORM-D  
Label: NONE  
Non Bulk Pack: 156,306  
Bulk Pack: NONE  
Max Qty Pass: 30KGGROSS  
Max Qty Cargo: 30KGGROSS  
Vessel Stow Req: A

=====

Detail IMO Information

=====

IMO PSN Code: HIN  
IMO Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. o  
IMDG Page Number: 3230  
UN Num

ber: 1993  
UN Hazard Class: 3.2  
IMO Packaging Group: I/II  
Subsidiary Risk Label: -  
EMS Number: 3-07  
MED First Aid Guide NUM: T

=====  
Detail IATA Information  
=====

IATA PSN Code: HDW  
IATA UN ID Num: 8000  
IATA Proper Shipping Name: CONSUMER COMMODITY +  
IATA UN Class: 9  
IATA Label: MISCELLANEOUS  
Packing Note Passenger: 910  
Max Quant Pass: 25KG G  
Max Quant Cargo: 25KG G  
Packaging Note Cargo: 910  
Excep  
tions: A112

=====  
Detail AFI Information  
=====

AFI PSN Code: HEB  
AFI Proper Shipping Name: CONSUMER COMMODITY  
AFI Hazard Class: 9  
AFI UN ID NUM: UN8000  
Special Provisions: P5  
Back Pack Reference: A13.13

=====  
HAZCOM Label  
=====

Product ID: SCOTCH-GRIP 847 RUBBER AND GASKET ADHESIVE  
Cage: 76381  
Com  
pany Name: MINNESOTA MINING AND MFG CO, DBA 3M  
Street: 3M CENTER BLDG 224-5S-04  
City: SAINT PAUL MN  
Zipcode: 55144-1000  
Health Emergency Phone: 612-733-1110  
Label Required IND: Y  
Date Of Label Review: 08/28/2000  
Status Code: A  
Year Procured: 1999  
Origination Code: F  
Eye Protection IND: YES  
Skin Protection IND: YES  
Signal Word: DANGER  
Respiratory Protection IND: YES  
Health Hazard: Slight  
Contact Hazard: Slight  
Fire Hazard: Severe  
Reactivity Hazard: None  
Hazard And Precautions: EYE: MODERATE EYE

IRRITATION. SKIN: MILD SKIN  
IRRITATION (AFTER PROLONGED OR REPEATED CONTACT). INHALATION: CENTRAL NERVOUS  
SYSTEM DEPRESSION; UPPER RESPIRATORY IRRITATION. INGESTION: IRRITATION OF GA  
STROINTESTINAL TISSUES, CENTRAL NERVOUSSYSTEM DEPRESSION; ASPIRATION  
PNEUMONITIS. TARGET ORGANS: NO DATA. FIRST AID. EYES: FLUSH WITH WATER. GET  
MEDICAL ATTENTION. SKIN: WASH WITH SOAP & WATER. GET ME DICAL ATTENTION  
IF IRRITATION PERSISTS. INHALED: REMOVE TO FRESH AIR. RESTORE BREATHING. GET  
MEDIC  
AL ATTENTION. INGESTED: DO NOT INDUCE VOMITING! GET MEDICAL ATTENTION  
IMMEDIATELY.

=====

Disclaimer (provided with this information by the compiling agencies): This  
information is formulated for use by elements of the Department of Defense.  
The United States of America in no manner whatsoever expressly or implied  
warrants, states, or intends said information to have any application, use or  
viability by or to any person or persons outsid  
e the Department of Defense  
nor any person or persons contracting with any instrumentality of the United  
States of America and disclaims all liability for such use. Any person  
utilizing this instruction who is not a military or civilian employee of the  
United States of America should seek competent professional advice to verify  
and assume responsibility for the suitability of this information to their  
particular situation regardless of similarity to a corresponding Department  
of De  
fense or other government situation.