

CHEMENCE INC -- SEALING COMPOUND -- 8030-00-081-2341

===== Product Identification =====

Product ID:SEALING COMPOUND

MSDS Date:03/31/1999

FSC:8030

NIIN:00-081-2341

Status Code:A

MSDS Number: CKXQK

=== Responsible Party ===

Company Name:CHEMENCE INC

Address:6425 INDUSTRIAL WAY

City:ALPHARETTA

State:GA

ZIP:30201

Country:US

Info Phone Num:404-664-6624

Emergency Phone Num:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtec Ind/Phone:(800)424-9300

CAGE:0ZDS4

=== Co

ntractor Identification ===

Company Name:CHEMENCE INC

Address:6425 INDUSTRIAL WAY

City:ALPHARETTA

State:GA

ZIP:30201

Country:US

Phone:404-664-6624

CAGE:0ZDS4

===== Composition/Information on Ingredients =====

Ingred Name:POLYETHYLENE GLYCOL DIMETHACRYLATE

CAS:25852-47-5

= Wt:93.

Ingred Name:CUMENE HYDROPEROXIDE

CAS:80-15-9

RTECS #:MX2450000

= Wt:3.

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:SACCHARIN

CAS:81-07-2

RTECS #:DE4200000

= Wt:3.

EPA Rpt Qty:100 LBS

DOT Rpt Q

ty:100 LBS

Ingred Name:N,N-DIALKYL TOLUIDINE
= Wt:1.

===== Hazards Identification =====

Effects of Overexposure:PROLONGED SKIN CONTACT MAY RESULT IN DERMATITIS
IN SENSITIVE PERSONS. WILL IRRITATE
EYES ON CONTACT.

===== First Aid Measures =====

First Aid:WASH WITH SOAP AND WATER FOR SKIN CONTACT. FOR EYE CONTACT.
FLUSH WITH PLENTY OF
WATER. FOR INGESTION, DO NOT INDUCE VOMITING. CONTACT PHYSICIAN.

=====

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>100.C, 212.F
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, WATER
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:IRRITATE ORGANIC VAPORS

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precaution
s:STORE IN A COOL DRY PLACE AND OUT OF
DIRECT SUNLIGHT.
Other Precautions:KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NEEDED FOR NORMAL USE.
Ventilation:ENSURE ADEQUATE ROOM VENTILATION FOR COMFORTABLE WORKING
CONDITIONS.
Protective Gloves:POLYETHYLENE OR RUBBER GLOVES.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:BARRIER CREAMS RECOMMENDED.
Supplemental Safety and Health

===== Phys

ical/Chemical Properties =====

Boiling Pt:>204.4C, 400.F
B.P. Text:@ 760MM
Vapor Pres:.01
Vapor Density:1.01
Spec Gravity:1.1
VOC Pounds/Gallon:134
Evaporation Rate & Reference:VERY LOW
Solubility in Water:INSOLUBLE
Appearance and Odor:GREEN, MILD ORGANIC LIQUID
Percent Volatiles by Volume:12.5%
Corrosion Rate:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTAMINATION
Stability Condition to Avoid:TE
MPERATURES IN EXCESS OF 150 DEGREES F
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL OR INCINERATE IN ACCORDANCE WITH EPA
AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this informatio
n to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.