

SHERWIN-WILLIAMS CO THE -- POLYURETHANE COATING, 37925 UNTINTED PART 1 --  
8010-01-260-0911

===== Product Identification =====

Product ID:POLYURETHANE COATING, 37925 UNTINTED PART 1

MSDS Date:09/21/2000

FSC:8010

NIIN:01-260-0911

Status Code:A

Kit Part:Y

MSDS Number: CKYPC

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

City:CLEVELAND

State:OH

ZIP:44115-104

2

Country:US

Info Phone Num:216-566-2242

Emergency Phone Num:216-566-2917

Preparer's Name:BOBBY STOKES

CAGE:54636

=== Contractor Identification ===

Company Name:SC JOHNSON AND SON INC

Address:1525 HOWE ST

Box:City:RACINE

State:WI

ZIP:53403-2236

Country:US

Phone:800-725-6737

CAGE:32204

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ACETATE

CAS:123-86-4

RTECS #:AF7350000

= Wt:25.

OSHA PEL:710 MG/M3;150 PPM

ACGIH TLV:713 MG/M3;150 PPM

ACGIH STEL:950 MG/M3

;200 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:1,6-HEXAMETHYLENE DIISOCYANATE  
CAS:822-06-0  
RTECS #:MO1740000  
= Wt:1.  
ACGIH TLV:0.034 MG/M3;.005 PPM  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:HEXAMETHYLENE DIISOCYANATE POLYMER  
CAS:28182-81-2  
RTECS #:NQ9170000  
= Wt:75.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:EXPOSURE MAY BE BY INHALATION AND/OR  
SKIN OR E  
YE CONTACT, DEPENDING ON CONDITION OF USE. TO MINIZE  
EXPOSURE FOLLOW RECOMMENDATIONS FOR PROPER USE, VENTILATION, AND  
PERSONAL PROTECTIVE EQUIPMENT.IRRIAT ION OF EYES, SKIN, AND  
RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME  
OVEREXPOSURE MAY RESULTS IN UNCONSCIOUSNESS AND POSSIBLE DEATH.  
Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF  
COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR  
SPRAY MISTS. REDNESS AND ITCHING OR BURN  
ING SENSATION MAY INDICATE  
EYE OR EXCESSIVE SKIN EXPOSURE.  
Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

===== First Aid Measures =====

First Aid:INHALED---IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE  
BREATHING. KEEP WARM AND QUIET. SKIN---WASH AFFECTED AREA  
THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND  
LAUNDRER BEFORE RE-USE. E YES---FLUSH EYES WITH LARGE AMOUNTS OF  
WATER FOR 15 MINUTES. GET MEDICAL AT

TENTION. SWALLOWED---GET  
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:=35.C, 95.F

Lower Limits:1.4

Upper Limits:7.6

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING

SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY  
BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER  
MAY BE USED TO COOL CLOSED CO NTAIN

RS TO PREVENT PRESSURE BUILD-UP

AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME  
HEAT.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE

FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED

CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO

HOT SURFACES REQUIRES SPECIA L PRECAUTIONS. DURING EMERGENCY

CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A  
HEALTH HAZARD.

===== Accidental  
Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND  
REMOVE WITH INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:CONTENTS ARE FLAMMABLE. KEEP AWAY FROM  
HEAT, SPARKS, AND OPEN FLAME. DURING USE AND UNTIL ALL VAPORS ARE  
GONE: KEEP AREA VENTILATED-DO NOT SMOKE-EXTINGUISH ALL FLAMES,  
PILOT LIGHTS, AND HEATERS-TURN O FF STOVES, ELECTRIC TOOLS AND  
APPLIAN

CES, AND ANY OTHER SOURCES OF IGNITION.

Other Precautions:INTENTIONAL MIUSE BY DELIBERATELY CONCENTRATING AND

INHALING THE CONTENTS CAN BE HARMFUL OR FATAL. KEEP CONTAINER

CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVE CONTAINERS WITH

APPROPRIATE LABELING. KEEP OUT OF THE REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE NOT CONTROLLED BELOW APPLICABLE  
LIMITS BY VENTILATION, WEAR PROPERLY FITTED ORGANIC

VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR DUST.  
Ventilation:LOCAL EXHAUST PREFERRABLE. GENERAL EXHAUST ACCEPTABLE IF  
EXPOSURE TO MATERIALS IS MAINTAINED BELOW APPLIC EXPOSURE LIMITS  
Protective Gloves:AS RECOMMENDED BY GLOVE SUPPLIER  
Eye Protection:SAFETY SPECTACLES WITH UNPERFORATED SIDESHIELDS  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:>123.9C, 255.F  
B.P. Text:255-264 F  
Vapor Density:> AIR  
Spec Gravity:1  
.06  
VOC Pounds/Gallon:264  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:30

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
Hazardous Decomposition Products:BY FIRE: CARBON DIOXIDE, CARBON  
MONOXIDE, OXIDES OF NITROGEN, POSSIBILITY OF HYDROGEN CYANIDE.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE FROM THIS PRODUCT MAY BE HAZARDOUS AS  
DEFINE  
D UNDER THE RESOURCE CONSERVATION AND RECOVERY ACT 40 CFR  
261. WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE THE  
APPLICABLE EPA HAZARDOUS WASTE NUMBERS.INCINERATE IN APPROVED  
FACILITY. DO NOT INCINERATE CLOSED CONTAINER.

===== Regulatory Information =====

SARA Title III Information:SARA 313 ( 40 CFR 372. 65C SUPPLIER  
NOTIFICATION  
State Regulatory Information:

===== Other Information =====

Disclaimer

(provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.