

PACIFIC WEST CHEMICAL CORP -- POLYURETHANE AEROSOL COLORS -- 8010-01-435-2130

=====
Product Identification
=====

Product ID:POLYURETHANE AEROSOL COLORS

MSDS Date:06/29/2000

FSC:8010

NIIN:01-435-2130

Status Code:A

MSDS Number: CKYPX

=== Responsible Party ===

Company Name:PACIFIC WEST CHEMICAL CORP

Address:337 SUMMIT DR

Box:183

City:CORTE MADERA

State:CA

ZIP:94925-0183

Country:US

Info Phone Num:415-

924-4560

Emergency Phone Num:999-999-9999

Preparer's Name:HENRY SIMMONS

CAGE:58977

=== Contractor Identification ===

Company Name:PACIFIC WEST CHEMICAL CORP

Address:337 SUMMIT DR

Box:183

City:CORTE MADERA

State:CA

ZIP:94925-0183

Country:US

Phone:415-924-4560

CAGE:58977

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ACETATE

CAS:123-86-4

RTECS #:AF7350000

= Wt:5.

OSHA PEL:710 MG/M3;150 PPM

ACGIH TLV:713 MG/M3;150 PPM

ACGIH STEL:950 MG/M3;200 PPM

EPA Rpt

Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE
CAS:1330-20-7
RTECS #:ZE2100000
= Wt:13.
ACGIH TLV:434 MG/M3;100 PPM
ACGIH STEL:651 MG/M3;150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:MINERAL SPIRITS
CAS:64475-85-0
RTECS #:PY8240000
< Wt:5.

Ingred Name:ACETONE
CAS:67-64-1
RTECS #:AL3150000
= Wt:35.
OSHA PEL:2400 MG/M3;1000 PPM
ACGIH TLV:1780 MG/M3;750 PPM
ACGIH STEL:2380 MG/M3;1000 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:T
X2275000
= Wt:15.
OSHA PEL:1800 MG/M3;1000 PPM

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TI4300000
< Wt:5.

Ingred Name:N-BUTANE
CAS:106-97-8
RTECS #:EJ4200000
= Wt:10.
ACGIH TLV:1900 MG/M3;800 PPM

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. IRRITATION OF
THE RESPIRATORY TRACT, OR NERVOUS SYSTEM, DEPRESSION-CHACTERIZED BY
HEADACHE, DIZZINESS, NAUSEA

, OR POSSIBLE UNCONSCIOUSNESS. SKIN AND
EYE CONTACT: PRIMARY IRRITATION. PROLONGED OR REPEATED CONTACT TO
SKIN MAY CAUSE DERMATITIS- EXERCISE DUE CARE.

===== First Aid Measures =====

First Aid:VAPORS: REMOVE FROM EXPOSURE AND RESTORE BREATHING, SEEK
MEDICAL ATTENTION. SPLASH: (SKIN) WASH AFFECTED AREA, REMOVE
CONTAMINATED CLOTHING, SEE PHYSICIAN IF ANY IRRITATION PERSISTS.
SPLASH: (EYES) FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES AND
TAKE TO A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:=-26.C, -14.8F
Lower Limits:.7%
Upper Limits:12.8%
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE, BUT WATER
SPRAY MAY BE USED TO COOL CONTAINERS EXPOSED TO HEAT OR FIRE TO
PREVENT PRESSURE BUILD UP.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE DUE TO
PRESSURE FROM EXTREME HEAT OR FIRE. AEROSOL SPRAY IS EXTREMELY
FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION: FLAMES,
SPARKS, STATIC ELECTRICITY AND ELECTRICAL. VENTILATE AREA AND SOAK UP
WITH INERT ABSORBENT USING NON-SPARKING TYPE TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120 DEG F. DO NOT
STORE OR USE NEAR HEAT, SPARKS, OR FLAME.
Other Precautions:DO NOT GET IN EYES. DO NOT BREATHE VAPORS. AVOID SKIN
CONTACT. DO NOT TAKE INTERNALLY. SMOKING WHILE USING THIS PRODUCT
MUST BE STRICTLY PROHIBITED. IN ADDITION TO ALL OTHER HAZARDS AND
PRECAUTIONS - DUST FROM SANDING THE DRY PAINT FILM SHOULD BE
TREATED AS A NUISANCE DUST WITH A TLV OF 10MG/CUBIC METER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OUTDOORS. WE RECOMMENDED AN APPROVED PARTICULATE

FILTER TO REMOVE ANY AIRBORNE OVERSPRAY IN RESTRICTED AREAS WITH POOR VENTILATION AND CLOSE TO THE T.L.V. INDOORS: A NIOSH APPROVED RESPIRATOR WITH ORG ANIC VAPOR CARTRIDGE IS RECOMMENDED.

Ventilation:ALL APPLICATION AREAS SHOULD BE ADEQUATELY VENTILATED IN ORDER TO KEEP THE INGREDIENTS IN SECTION II BELOW THEIR EXPOSURE LIMITS.

Protective Gloves:IMPERVIOUS GLOVES ARE RECOMMENDED TO PREVENT SKIN CONTACT.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS IS RECOMMENDED TO PREVENT SKIN CONTACT.

Other Protective Equipment:EYE WASH FOUNTAIN AND SAFETY SHOWER. IMPERVIOUS APRON TO PREVENT SKIN CONTACT IS RECOMMENDED.

Work Hygienic Practices:AVOID PROLONGED OR REPEATED CONTACT. DO NOT BREATHE THE VAPORS. WASH CONTAMINATED CLOTHING PRIOR TO RE-USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=-23.3C, -10.F

Vapor Density:>AIR

Spec Gravity:.7

Evaporation Rate & Reference:>N-BUTYL ACETATE

Solu

bility in Water:NEGLIGIBLE

Appearance and Odor:OPAQUE LIQUID/ SOLVENT BASE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH TEMPERATURE

Hazardous Decomposition Products:CO, CO2,HCL, AND POSSIBLY TRACES OF PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability

y of this information to their particular situation.