

AKRON PAINT AND VARNISH INC -- TYPE II WALKWAY DARK GULL GRAY, G-8130 --
8010-00-641-0426

===== Product Identification =====

Product ID:TYPE II WALKWAY DARK GULL GRAY, G-8130

MSDS Date:03/29/2000

FSC:8010

NIIN:00-641-0426

Status Code:A

MSDS Number: CKYSL

=== Responsible Party ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Info Phone Num:216-773-8911

Emergency Phone Num:(800)424-9300

Pre

parer's Name:HENRY SIMMONS

Chemtrec Ind/Phone:(800)424-9300

CAGE:70228

=== Contractor Identification ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Phone:216-773-8911

CAGE:70228

===== Composition/Information on Ingredients =====

Ingred Name:LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM)

CAS:64742-89-8

Minumum % Wt:15.

Maxumum % Wt:40.

Ingred Name:CRYSTALLINE SILICA

Minumum % Wt:15.

Maxumum % Wt:40.

Ingr

ed Name:XYLENE
CAS:1330-20-7
RTECS #:ZE2100000
Minumum % Wt:.5
Maxumum % Wt:1.5
ACGIH TLV:434 MG/M3;100 PPM
ACGIH STEL:651 MG/M3;150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:EYES: CAN CAUSE REDNESS, IRRITATION, SWELLING
AND BLURRED VISION. SKIN: PROLONGED OR
REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS
BREATHING:EXCESSIVE INHALATION OF VAPORS A ND/OR SPRAY MIST CAN

CAUSE RESPIRATORY IRRITATION,
DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS AND
EVEN
ASPHYXIATION. SWALLOWING: CAN CAUSE GASTROINTESTINAL IRRITATION,
NAUSEA, VO MITING
AND DIARRHEA; ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL
PNEUMONITIS
WHICH COULD BE FATAL.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. LIFT
EYELIDS OCCASIONALLY,
GET PROMPT MEDICAL ATTEN
TION. SKIN: WASH THOROUGHLY WITH SOAP AND
WATER, REMOVE
CONTAMINATED CLOTHING PROMPTLY; WASH CLOTHING BEFORE REUSE. CONSULT A
PHYSICIAN IF
IRRITATION PERSISTS.SWALLOWING: SINCE THIS PRODUCT MAY CONTAIN
MATERIALS, WHICH CAN
CAUSE LUNG DAMAGE IF ASPIRATED INTO THE LUNGS, THE DECISION WHETHER T O
INDUCE
VOMITING MUST BE MADE BY A PHYSICIAN AFTER CAREFUL CONSIDERATION OF ALL
MATERIALS
INGESTED. INHALATION: MOVE AFFECTED PERSON TO FRESH AIR. IF BREATHING
HAS STOPPED,
GIVE ARTI

FICIAL RESPIRATI ON.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:=10.C, 50.F

Lower Limits:0.9%

Upper Limits:12.3%

Extinguishing Media:CARBON-DIOXIDE-DRY CHEMICAL-FOAM-WATER FOG USE
WATER FOR COOLING MATERIAL STORED IN VICINITY OF FIRE

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WITH A
FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER OR POSITIVE
PRESSURE MODE. WEAR PROTECTIVE CLOTHING.

Unusual Fire/Ex

plosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY
TRAVEL ALONG THE GROUND TO AN IGNITION SOURCE SOME DISTANCE FROM
MATERIAL HANDLING POINT. IGNITION SOURCES INCLUDE PILOT LIGHTS,
SMOKING, HEATERS, ELECTRIC MOTORS, SPARKS FROM ELECTRICAL SWITCHES
AND STATIC DISCHARGES.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: ABSORB LIQUID WITH RAGS, FLOOR
ABSORBENT, VERMICULITE OR OTHER

ABSORBENT MATERIAL AND TRANSFER TO HOOD

. LARGE SPILL: ELIMINATE ALL
IGNITION

SOURCES?DIKE AREA OF SPILL TO PREVENT SPREADIN G?VENTILATE AREA IF
INDOORS---PUMP

LIQUID INTO SALVAGE TANK?REMAINING LIQUID MAY BE TAKEN UP WITH SAND,
FLOOR

ABSORBENT OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT DROP CONTAINERS. AVOID HEAT,
SPARKS, AND OPEN FLAME. STORE LARGE QUANTITIES

ONLY IN BUILDINGS DESIGNED TO COMPLY

WITH OSHA 1910.106. NEVER USE

PRESSURE TO EMPTY.

AVOID BREATHING SANDING DUST. D O NOT HANDLE UNTIL THE MANUFACTURERS
SAFETY

PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

Other Precautions:THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE
ACCURATE BUT IS NOT

WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS
ARE

ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFO RMATION IS CURRENT,
APPLICABLE,

AND SUITABLE TO THEIR CIRCUMSTANCES.

===== Exposur

e Controls/Personal Protection =====

Respiratory Protection:IN OUTDOOR OR OPEN AREAS WITH UNRESTRICTED VENTILATION APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICULATES AND VAPOR.

Ventilation:PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CONCENTRATION BELOW CURRENT APPLICABLE OSHA PERMISSIBLE EXPOSURE LIMIT.

Protective Gloves:WEAR RESISTANT GLOVES SUCH AS: NITRILE RUBBER.

Eye Protection:CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED.

Other Protective Equipment:NORMAL PROTECTIVE CLOTHING. WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=115.6C, 240.F

B.P. Text:240-285F

Vapor Pres:HEAVIER THAN AIR

Spec Gravity:1.318

VOC Grams/Liter:3.35

Appearance and Odor:LIQUID AND GRAY

Percent Volatiles by Volume:53.44

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZERS (E.G. NITRIC ACID)

Stability Condition to Avoid:KEEP AWAY FROM HEAT AND OPEN FLAME

Hazardous Decomposition Products:MAY FORM CARBON MONOXIDE AND DIOXIDE, VARIOUS HYDROCARBONS, ETC

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

===== Regulatory Information =====

=====

SARA Title III Information:THIS PRODUCT CONTAINS THE FOLLOWING TOXIC
CHEMICALS SUBJECT TO THE REPORTINNG REQUIREMENTS OF SECTION 313 OF
THE EMERGENCY PLANNING AND COMMUNITY RIGHT ACT OF 1986 AND 40 CFR
372: XYLENE- CASS NUMBER 1330-20-7, 1.19 PERCENT. SARA TITLE III
SECTION 313: PROP 65 (CARCINOGEN): PROP 65 (TETRATOGENIC): PROP 65
(BOTH CARCINOGEN AND TETRATOGENIC).

State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situatio
n.