

EASTMAN KODAK COMPANY -- KODAK SUPRALIFE ALKALINE BATTERY SIZE: KD (1.5V) IEC-LR20
-- 6135-00-900-2139

===== Product Identification =====

Product ID:KODAK SUPRALIFE ALKALINE BATTERY SIZE: KD (1.5V) IEC-LR20

MSDS Date:03/03/1992

FSC:6135

NIIN:00-900-2139

Status Code:A

MSDS Number: CKZSH

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone

Num:7167225151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:POTASSIUM HYDROXIDE (AQUEOUS SOLUTION CONCENTRATION: 37% -
43%) (AQUEOUS SOLUTION PH: 11.5-12.0)

RTECS #:PS1006506

Fraction by Wt: 5%

Ingred Name:MERCURY

CAS:7439-97-6

RTE

CS #:OV4550000
Fraction by Wt: .001%
OSHA PEL:SEE TABLE Z-2
ACGIH TLV:0.025 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

===== Hazards Identification =====

Medical Cond Aggravated by Exposure:

===== First Aid Measures =====

First Aid:SKIN: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF SYMPTOMS ARE PRESENT AFTER FLUSHING, GET MEDICAL ATTENTION. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. BATTERY INGESTION: OBTAIN IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:USE AN EXTINGUISHING MEDIUM APPROPRIATE FOR THE SURROUNDING FIRE.
Fire Fighting Procedures:USE A POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS IF BATTERIES ARE INVOLVED IN A FIRE. FULL PROTECTIVE CLOTHING IS NECESSARY.
Unusual Fire/Explosion Hazard:BATTERIES MAY RELEASE TOXIC MERCURY VAPORS AND/OR IRRITATING POTASSIUM HYDROXIDE FUMES IF EXPOSED TO FIRE OR HIGH TEMPERATURES. BATTERIES MAY VENT IF EXPOSED TO EXCESSIVE HEAT OR FIRE.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE BATTERIES IN A MANNER THAT ALLOWS TERMINALS TO SHORT CIRCUIT. STORE BATTERIES IN A COOL (BELOW 70F), DRY AREA THAT IS SUBJECT TO LITTLE TEMPERATURE CHANGE. DO NOT PLACE NEAR HEATING EQUIPMENT, NOR EXPOSE TO DIRECT SUNLIGHT FOR LONG

PERIODS. ELEVATED
TEMPS CAN RESULT IN REDCED BATTERY SERVICE LIFE.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

**LITHIUM-X: (CLASS D EXTINGUISHING MEDIA) IS EFFECTIVE ON FIRES
INVOLVING ONLY A FEW POWER CELLS.

===== Physical/Chemical Properties =====

HCC:N1

Solubility in Water:INSOLUBLE

Appearance and Odor:9V BATTERY

===== Stability and Reactivity Data =====

Stability Indicato

r/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:STATIC,SPARKS,FIRE.DO NOT CHARGE.DO NOT
REVERSE POLARITY.AVOID PHYSICAL DAMAGE.

Hazardous Decomposition Products:BATTERIES NORMALLY EVOLVE HYDROGEN GAS
WHICH IS EXPLOSIVE OR FLAMMABLE WITH AIR.

===== Toxicological Information =====

Toxicological Information:ALKALINE BATTERIES ARE NOT DESIGNED TO BE
RECHARGED. CHARGING AN ALKALINE BATTERY MAY RESULT IN ELECTROLYTE
L
EAKAGE AND/OR VENTING. NEVER DISASSEMBLE A BATTERY. SHOULD A
BATTERY UNINTENTIONALLY BE CRUSHED THUS RELEASING ITS CONTENTS,
RUBBER GLOVES MUST BE USED TO HANDLE ALL BATTERY COMPONENTS. IN
THE EVENT OF SKIN OR EYE EXPOSURE TO THE ELECTROLYT REFER TO FIRST
AID INFORMATION.*

===== Ecological Information =====

Ecological:*MORE THAN A MOMENTARY SHORT CIRCUIT WILL GENERALLY REDUCE
THE BATTERY SERVICE LIFE. EXTENDED SHORT CIRCUITING CREATES H

IGH

TEMPERATURES IN THE CELL. HIGH TEMPERATURES CAN CAUSE SKIN BURNS
AND CAUSE THE CELL TO VENT.**

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT LOCAL, STATE AND FEDERAL ENVIRONMENTAL
PROTECTION AUTHORITIES FOR THE
MOST CURRENT REGULATIONS REGARDING DISPOSAL OF BATTERIES. DO NOT
INCINERATE OR
EXPOSE BATTERIES TO FIRE.

===== MSDS Transport Information =====

Transport Information:**THE USE OF OLD
D AND NEW BATTERIES OR BATTERIES
OF VARYING SIZES AND TYPES IN THE SAME BATTERY ASSEMBLY SHOULD BE
AVOIDED. THE BATTERIES ELECTRICAL CHARACTERISTICS AND
CAPABILITIES VARY AND DAMAGE MAY RESULT TO THE BATTERIES OR
ELECTRICAL EQUIPMENT.***

===== Regulatory Information =====

SARA Title III Information:THE USE OF OLD AND NEW BATTERIES OR
BATTERIES OF VARYING SIZES AND TYPES IN THE SAME BATTERY ASSEMBLY
SHOULD BE AVOIDED. THE BATTERIES EL
ECTRICAL CHARACTERISTICS AND
CAPABILITIES VARY AND DAMAGE MAY RESULT TO THE BATTERIES OR
ELECTRICAL EQUIPMENT. USE NICKEL PLATED STEEL (OR STAINLESS STEEL)
FOR POWER TERMINAL CONTACTS. DO NOT DIRECTLY SOLDER TO THE
BATTERY. MAY CAUSE VENTING AND/OR EXPLOSION. AVOID ENCASING
BATTERIES IN AIRTIGHT COMPARTMENTS. FLAMMABLE HYDROGEN GAS,
NORMALLY GENERATED, CAN FORM EXPLOSIVE MIXTURES. PROVISIONS FOR
VENTING MUST BE PROVIDED. NEVER COMPLETELY ENCAPSULATE A BATTER
Y.

TO DO SO WILL INHIBIT THE SA
State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should se

ek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.