

PK INSULATION MFG CO INC -- QUIK-COTE FINISHING CEMENT -- 5640-00-226-4540

===== Product Identification =====

Product ID:QUIK-COTE FINISHING CEMENT

MSDS Date:02/14/1990

FSC:5640

NIIN:00-226-4540

Status Code:A

MSDS Number: CLBKH

=== Responsible Party ===

Company Name:PK INSULATION MFG CO INC

Address:2417 DAVIS BLVD

City:JOPLIN

State:MO

ZIP:64804

Country:US

Info Phone Num:417-781-6380

Emergency Phone Num:0000000000

CAGE:3P006

=== Contractor Identification ===

Co

Company Name:PK INSULATION MFG. CO., INC.

Address:2417 DAVIS BLVD

Box:City:JOPLIN

State:MO

ZIP:64804

Country:US

Phone:417-781-6380

CAGE:3P006

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL WOOL FIBER

CAS:7782-42-5

RTECS #:MD9659600

ACGIH TLV:10 MG/M3

Ingred Name:CEMENT, PORTLAND

CAS:65997-15-1

RTECS #:VV8770000

ACGIH TLV:10 MG/M3

Ingred Name:BENTONITE COLLODIAL CLAY

CAS:1302-78-9

RTECS #:CT9450000

ACGIH TLV:10 MG/M3

Ingred Name:CALCIUM CARBONATE

CAS:1

317-65-3
RTECS #:EV9580000
ACGIH TLV:10 MG/M3

Ingred Name:RUST INHIBITOR
CAS:7632-00-0
RTECS #:RA1225000
ACGIH TLV:10 MG/M3
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

Health Hazards Acute and Chronic:MINERAL WOOL FIBER AND NUISANCE DUST
MAY CAUSE TRANSITORY MECHANICAL IRRITATION TO EYES, SKIN OR UPPER
RESPIRATORY TRACT. ALTHOUGH CURRENT STUDIES DO NOT ESTABLISH
MINERAL WOOL TO BE A HEALTH HAZARD I ARC CONTINUES TO C
LARIFY THE
FIBER IN CATEGORY 2B. CEMENT, CLAY AND LIMSTONE CONTAIN A SMALL
AMOUNT OF CRYSTALLINE SILICA. THERE IS LIMITED EVIDENCE OF
CARCINOGENICITY OF CRYSTALLINE SILICA IN HUMANS. IARC HAS
CLASSIFIED CRYSTALLINE SILICA IN CATEGORY 2A. PROLONGED INHALATION
OF MINERAL DUST MAY REDUCE LING FUNCTION. THIS MSDS WILL BE UPDATED
AS MEW MEDICAL FINDINGS ARE PUBLISHED.

Medical Cond Aggravated by Exposure:

===== First Aid Measures =====

F
irst Aid:EYES: FLUSH WITH WATER. DO NOT RUB. IF IRRITATION CONTINUES
CONSULT A PHYSICIAN. SKIN: WASH PARTICLES FROM SKIN WITH DOAP AND
WATER, DO NOT RUB. INHALATION: REMOVE TO FRESH AIR. INGESTION:
CONSULT A P HYSICIAN.

===== Fire Fighting Measures =====

Extinguishing Media:NON COMBUSTIBLE. MATERIALS COMPATIBLE WITH CO2,
WATER OR DRY CHEMICAL EXTINGUISHING MEDIA.

===== Accidental Release Measures =====

Spill Relea

se Procedures:AVOID CREATING DUST. USE VACCUM OR WET
CLEAN-UP TO MINIMIZE AIRBORNE DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED DUST RESPIRATOR.

Ventilation:LOCAL EXHAUST OR MECHANICAL VENTILATION.

Protective Gloves:GLOVES

Eye Protection:TIGH FITTING GOGGLES

Other Protective Equipment:WEAR LONG SLEEVED, LOOSE FITTING CLOTHING
CLOSED AT THE NECK AND MINIMIZE SKIN EXPOSURE. WASH WORK CLOTHS
SPERATE FROM OTHER CLOTHING

.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Appearance and Odor:DRY GRANDULAR MIXTURE NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:INERT SOLID WASTE. TO LANDFILL IN ACCORDANCE
WITH LOCAL, STATE AND FEDERAL REGULATION
S.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibi

lity for the suitability of this information to their particular situation.