

CENTURY LUBRICANTS CO, NFO TECHNOLOGIES DIV -- CHEMPLEX 1381 -- 6850-00-281-4033

===== Product Identification =====

Product ID:CHEMPLEX 1381

MSDS Date:07/18/1997

FSC:6850

NIIN:00-281-4033

Status Code:A

MSDS Number: CLDFX

=== Responsible Party ===

Company Name:CENTURY LUBRICANTS CO, NFO TECHNOLOGIES DIV

Address:2140 S. 88TH STREET

City:KANSAS CITY

State:KS

ZIP:66111-8701

Country:US

Info Phone Num:9

13-422-4022/ 800-800-6457

Emergency Phone Num:913-791-3645

Resp. Party Other MSDS Num.:DOC 498 188002-AA

Preparer's Name:M.D. HART

CAGE:0BF03

=== Contractor Identification ===

Company Name:CENTURY LUBRICANTS CO, NFO TECHNOLOGIES DIV

Address:2140 S. 88TH STREET

Box:City:KANSAS CITY

State:KS

ZIP:66111-8701

Country:US

Phone:913-422-4022/ 800-800-6457

CAGE:0BF03

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

Contract Num:SP0450-01-M-ZC30
CAGE:66172

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICA THICKNER
OSHA PEL:20 MPPCF (DUST)

Ingred Name:ZINC COMPOUND
CAS:7440-66-6
RTECS #:ZG8600000
< Wt:80.
ACGIH TLV:5 MG/M3
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CHRONIC: NONE EXPECTED.
Explanation of Carcinog
enicity:NOT LISTED.
Effects of Overexposure:EYES: NONE EXPECTED. SKIN: PROLONGED OR
REPEATED CONTCAT MAY CAUSE MILD IRRITATION. INHALATION: NONE
EXPECTED. INGESTION: NONE EXPECTED.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH WITH WATER. SEE PHYSICIAN. SKIN: WASH WITH SOAP
AND WATER. IF HIGH PRESSURE, GET IMMEDIATE MEDICAL ATTENTION.
INHALTION: REMOVE FROM CONTAMINATED AREA. COMMENTS: TREAT ACCORDING
TO PERSON'S CONDITION AND S
PECIFICS OF EXPOSURE. DO NOT HANDLE
NEAR HEAT, FLAMES OR SPARKS.

=====
Fire Fighting Measures
=====

Flash Point:=101.7C, 215.F
Autoignition Temp:Autoignition Temp Text:UNK
Lower Limits:UNK
Upper Limits:UNK
Extinguishing Media:DRY CHEMICAL, COA2, WATER SPRAY, FOAM.
Fire Fighting Procedures:AVOID BREATHING VAPORS. USE BREATHING
APPARATUS IN CONFINED AREAS. COOL EXPOSED CONTAINERS WITH
WATERSPRAY.
Unusual Fire/Explosion Hazard:SILICON DIOXIDE, CARBON

OXIDES,
FORMALDEHYDE, UNVENTED ORGANIC COMPOUNDS.

===== Accidental Release Measures =====

Spill Release Procedures:ADD ABSORBENT TO SPILL AREA. KEEP SILICONE PRODUCTS OUT OF SEWERS AND WATERWAYS. ADVISE AUTHORITIES IF THEY DO NOT ENTER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE NEAR HEAT, FLAMES, SPARKS. DO NOT WELD OR HEAT EMPTY CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED.
Ventilation:GEREAL ADEQUATE. USE LOCAL MECHANICAL TO INSURE TLV'S NOT SURPASSED WHERE APPLICABLE.
Protective Gloves:CHEMICAL RESISTANT DESIRABLE.
Eye Protection:GOGGLES OR FACESHIELD DESIRABLE.
Other Protective Equipment:NONE NORMALLY NEEDED.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V5
Boiling Pt:=315.6C,
600.F
Vapor Pres:NIL
Vapor Density:>1
Spec Gravity:>1.0
Evaporation Rate & Reference: