

MOBILE PAINT MANUFACTURING CO INC -- DODE24607-CL ALKYD-SOFT WHITE, 0080159 --
8010-01-344-5089

===== Product Identification =====

Product ID:DODE24607-CL ALKYD-SOFT WHITE, 0080159

MSDS Date:11/22/1994

FSC:8010

NIIN:01-344-5089

Status Code:A

MSDS Number: CLFGP

== Responsible Party ==

Company Name:MOBILE PAINT MANUFACTURING CO INC

Box:717

City:THEODORE

State:AL

ZIP:36582

Country:US

Info Phone Num

:334-443-6110

Emergency Phone Num:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtrec Ind/Phone:(800)424-9300

CAGE:88633

== Contractor Identification ==

Company Name:MOBILE PAINT MANUFACTURING CO INC

Box:717

City:THEODORE

State:AL

ZIP:36582

Country:US

Phone:334-443-6110

CAGE:88633

===== Composition/Information on Ingredients =====

Ingred Name:BARIUM SULFATE

CAS:7727-43-7

RTECS #:CR0600000

= Wt:35.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:TITANIUM DIOXIDE

CAS:13463

-67-7

RTECS #:XR2275000

= Wt:25.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Effects of Overexposure:INHALATION

ALATION: AESTHETIC, EXCESSIVE CAN CAUSE

IRRITATION OF THE RESPIRATORY TRACT, OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUS, COMA AND EVEN ASPHYXIATION. SKIN AND EYE CONTACT-SKIN, MODERATE IRRITATION, DEFATTING, DERMATITIS, MAY BE A SENSITIZER IN SOME INDIVIDUALS. EYES: SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION, MAY BE A SENSITIZER IN SOME INDIVIDUALS. SKIN ABSORPTION-LIQUID CAN BE ABSORBED

THROUGH THE SKIN IN

RESULTING IN SYMPTOMS SIMILAR TO THE INHALATION EFFECTS ABOVE. INGESTION-GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

Medical Cond Aggravated by Exposure:EXPOSURE TO PETROLEUM SOLVENTS MAY AGGRAVATE PREEXISTING DERMATITIS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF BREATHING IS DIFFICULT. RESTORE BREATHING IF NECESSARY, TREAT SYMPTOMATICALLY,

CONSULT A PHYSICIAN. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER, REMOVE AND LAUNDER CONTAMINATED CLOTHING, CONSULT A PHYSICIAN IF NEEDED. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. TAKE TO A PHYSICIAN FOR MEDICAL TREATMENT. INGESTION: DRINK 1 TO 2 GLASSES OF WATER TO DILUTE, DO NOT INDUCE VOMITING. GET MEDICAL HELP IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:=37.8C

, 100.F
100-109F

Lower Limits:0.9%

Upper Limits:7.0%

Extinguishing Media: FOAM, ALCOHOL FOAM, CO₂, DRY CHEMICAL

Fire Fighting Procedures:DURING EMERGENCY CONDITIONS OVEREXPOSURES TO

DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT IMMEDIATELY APPARENT, OBTAIN MEDICAL ATTENTION. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, SPARKS, AND OPEN FLAME.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE TO EXTREME HEAT, APPLICATION TO HOT SURFACES REQUIR

ES SPECIAL PRECAUTIONS.

FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SP RAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES IF IGNITION (FLAME, HOT SURFACES, AND ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS, VENTILATE AREA, CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPA

RKING TOO LS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES ONLY IN BUILDINGS DESIGNED TO COMPLY WITH SHE 1910.106. KEEP CLOSURES TIGHT AND CONTAINER UPRIGHT TO PREVENT LEAKAGE. DO NOT STORE OR USE NEAR HEAT, SPA RKS OR FLAME. NEVER USE PRESSURE TO EMPTY. DRUM MUST NOT BE WASHED OUT OR USED FOR OTHER PURPOSES.

Other Precautions:DO NOT GET IN EYES. AVOID SKIN CONTACT. CAN CAUSE

ALLERGIC RESPIRATORY REACTION, PREVENT PROLONGED OR REPEATED BREATHING OF VAPORS OR SPRAY MIST. AVOID BREATHING OF SANDING DUST, WASH CONTAMINATED CLO THING THOROUGHLY, WASH SKIN THOROUGHLY WITH SOAP AND WATER AFTER HANDLING. CLOSE CONTAINER AFTER EACH USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE, WHEN EXPOSURE EXCEED OCCUPATIONAL EXPOSURE LIMITS SECTION 11. USE EI

THER AN ATMOSPHERE-SUPPLYING RESPIRATOR FOR
ORGANIC VAPORS IN COMPLIANCE WITH 29 CFR 1910.134, WITH PROVISION
FOR MIST REMOVAL IF CONDITIONS SO INDICATE.
Ventilation: ALL APPLICATION AREAS SHOULD BE VENTILATED IN ACCORDANCE TO
OSHA REGULATION 29 CFR 1910.54, 1910.104, 1910.108. REMOVE
DECOMPOSITION PRODUCTS DURING WELDING.

Protective Gloves: RECOMMENDED

Eye Protection: SAFETY EYEWEAR INCLUDING SPLASH GUARDS OR SIDE SHIELDS
RECOMMENDED.

Other Protective Equipment: USE PROTECTIVE

OUTER-WEAR AND PREVENT

PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

Work Hygienic Practices: AVOID BREATHING VAPORS AND CONTACT WITH SKIN.
WASH SKIN THOROUGHLY BEFORE BREAKS AND MEALS AND AT END OF WORK
PERIOD.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=148.9C, 300.F

Vapor Density:>AIR

Spec Gravity:1.8

VOC Pounds/Gallon:374

VOC Grams/Liter:3.12

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in

Water: NEGLIGIBLE

Appearance and Odor: TYPICAL PAINT SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZING MATERIALS

Stability Condition to Avoid: HIGH TEMPERATURES

Hazardous Decomposition Products: MAY PRODUCE HAZARDOUS WHEN HEATED TO
DECOMPOSITION

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND
FEDERAL REGULATIONS. IN

CINERATE IN APPROVED FACILITY, DO NOT
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsi
lity for the suitability of this information to their
particular situation.