

AMERICAN SAFETY TECHNOLOGIES INC -- MS-7C BASE COMPONENT -- 8010-01-397-3987

=====
Product Identification
=====

Product ID:MS-7C BASE COMPONENT

MSDS Date:07/15/1998

FSC:8010

NIIN:01-397-3987

Status Code:A

Kit Part:Y

MSDS Number: CLFNJ

=== Responsible Party ===

Company Name:AMERICAN SAFETY TECHNOLOGIES INC

Address:565 EAGLE ROCK AVE

City:ROSELAND

State:NJ

ZIP:07068

Country:US

Info Phone Num:973-403

-2600

Emergency Phone Num:1-800-424-9300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:88444

=== Contractor Identification ===

Company Name:AMERICAN SAFETY TECHNOLOGIES INC

Address:565 EAGLE ROCK AVE

Box:City:ROSELAND

State:NJ

ZIP:07068

Country:US

Phone:973-403-2600

CAGE:88444

=====
Composition/Information on Ingredients
=====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

< Wt:5.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:EPOXY

RESIN
CAS:25068-38-6
Code:F
RTECS #:CE6880000
Minumum % Wt:10.
Maxumum % Wt:25.

Ingred Name:CALCIUM MAGNESUM SILICATE
CAS:14807-96-6
Code:F
RTECS #:WW2710000
Minumum % Wt:10.
Maxumum % Wt:25.
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:2 MG/M3

Ingred Name:ALUMINO-SILICATE MINERAL
Minumum % Wt:30.
Maxumum % Wt:45.

Ingred Name:AROMATIC NAPHTHA
CAS:64742-95-6
Code:F
RTECS #:WF3400000
Minumum % Wt:5.
Maxumum % Wt:10.

Ingred Name:METHYL N-AMYL KETONE
CAS:110-43-0
RTECS #:MJ5075000
Minumum % Wt:5.
Maxumum % Wt:10.
OSHA PEL:465 MG/M3;100 PPM
ACGIH TLV:233 MG/M3;50 PPM

Ingred Name:1-METHOXY-2-PROPANOL
CAS:107-98-2
RTECS #:UB7700000
< Wt:5.
ACGIH TLV:369 MG/M3;100 PPM
ACGIH STEL:553 MG/M3;150 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:NONE
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:EYES: IRRITANT. SKIN: MAY CAUSE
MODERATE IRRITATION AND SENSITIZATION. INHALATION: VAPORS MAY CAUSE
HEADACHES, NAUS

EA, DIZZINESS AND RESPIRATORY IRRITATION. INGESTION:

CONTAINS MATERIALS THAT MAY BE SLIGHTLY TOXIC.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, SENSITIZATION AND DERMATITIS.

Medical Cond Aggravated by Exposure:ALLERGY, ECZEMA AND OTHER SKIN CONDITIONS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. SKIN: WASH CONTACT AREA WITH MILD SOAP AND WATER.

INH

ALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING (CONTAINS SOLVENT). GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:=-38.C, 100.4F

Autoignition Temp:Autoignition Temp Text:NONE

Lower Limits:1.62

Upper Limits:11.8

Extinguishing Media:DRY CHEMICAL, CHEMICAL FOAM OR CARBON DIOXIDE.

Fire Fighting Procedures:WEAR COMPLETE PERSONAL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS

WHERE POTENTIAL FOR

EXPOSURE TO VAPORS OR PRODUCTS OF COMBUSTION EXISTS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE (DUE TO BUILD UP OF PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH CONTAMINATED AREA WITH WATER.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID ALL PERSONAL CONTACT. DO NOT
E

XCEED 110 F/43 C IN STORAGE AREA.

Other Precautions:A SAFETY SHOWER AND EYE WASH FACILITY SHOULD BE AVAILABLE TO EMPLOYEES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR.

Ventilation:VENTILATION AND LOCAL EXHAUST ARE RECOMMENDED.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:CHEMICAL SPLASH PROOF GOGGLES.

Other Protective Equipment:COVERALLS, APRON AND IMPERVIOUS FOOT COVERING ARE RECOMMENDED.

Work Hygien

ic Practices:NONE
Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

Boiling Pt:=116.C, 240.8F
Melt/Freeze Pt:M.P/F.P Text:NONE
Decomp Temp:Decomp Text:NONE
Vapor Pres:8MMHG@68F/20C
Vapor Density:HEAVIER
Spec Gravity:1.5
Evaporation Rate & Reference:0.7 (BUTYL ACETATE=1)
Solubility in Water:SLIGHT
Appearance and Odor:VISCOUS LIQUID, SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/M
aterials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:EXCESSIVE HEAT.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND
ALDEHYDES. HAZARDOUS
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN A LICENSED HAZARDOUS WASTE
FACILITY IN ACCORDANCE WITH APPLICABLE LAWS.

Disclaimer (provided with this information by the compiling agencies):
This i
nformation is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.