View NSN Online: https://aerobasegroup.es/nsn/8010-01-302-3607

Product ID:FORMULA 150 PRIMER (MIL P 24441) CONVERTER 5748 MSDS Date:09/19/1999 FSC:8010 NIIN:01-302-3607 Status Code:A **MSDS Number: CLJHC** === Responsible Party === Company Name: INTERNATIONAL PAINT INC. INTERNATIONAL Address:6001 ANTOINE DR **City:HOUSTON** S tate:TX ZIP:77091 Country:US Info Phone Num:800-589-1267/800-854-6813 Emergency Phone Num: (800) 424-9300 Preparer's Name: HENRY SIMMONS Chemtrec Ind/Phone:(800)424-9300 CAGE:69827 === Contractor Identification === Company Name: INTERNATIONAL PAINT INC Address:6001 ANTOINE DRIVE Box:City:HOUSTON State:TX ZIP:77091 Country:US Phone:713-684-1244 CAGE:028S6 Company Name: INTERNATIONAL PAINT INC. INTERNATIONAL Address:6001 ANTOINE DR Box:City:HOUSTON State:TX ZIP:77091 Country:US Phone:800-589-1267/800-8

54-6813 CAGE:69827

Ingred Name:EPOXY RESIN CAS:25068-38-6 RTECS #:CE6880000 Minumum % Wt:25. Maxumum % Wt:50.

Ingred Name:AROMATIC HYDROCARBONS CAS:64742-95-6 RTECS #:WF3400000 Minumum % Wt:10. Maxumum % Wt:25.

Ingred Name:TRIMETHYLBENZENE CAS:25551-13-7 RTECS #:DC3220000 Minumum % Wt:1. Maxumum % Wt:11. ACGIH TLV:123 MG/M3;25 PPM

Ingred Name:MAGNESIUM SILICATE HYDRATE CAS:14807-96-6 RTECS #:WW2710000 Minumum % Wt:1. Maxum um % Wt:10. OSHA PEL:SEE TABLE Z-3 ACGIH TLV:2 MG/M3

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Effects of Overexposure:INHALATION: CAUSES NOSE AND THROAT IRRITATION. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. EYE CONTACT-CAUSES EYE IRRITATION SKIN CONTACT-CAUSES SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION OR SKIN SENSITIZATION. INGESTION-HARMFUL IF SWAL LOWED.

First Aid:INHALATION- REMOVE TO FRESH AIR. IF DISCOMFORT IS PRESENT OR BREATHING IS ABSENT GET MEDICAL ATTENTION IMMEDIATELY. EYE CONTACT- FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR 15 MINUTES UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. SKIN CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER. USE SOAP IF AVAILABLE. REMOVE SEVERELY CONTAMINATED CLOTHING (INCLUDING SHOES) A ND WASH BEFOR E USE. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INGESTION-IF SWALLOWED, DO NOT INDUCE VOMITING. KEEP AT **REST. GET PROMPT MEDICAL ATTENTION.** Flash Point:=46.1C, 115.F Lower Limits:1 Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL. Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT, SPARKS, ELECTRICAL EQUIPMENT AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. IN THE ABSENCE OF ELECTRICITY. A WATER SPRAY (A FOG NOZZLE IS PREFERRED) MAY BE USED TO COOL CONTAINERS. DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE TOXIC. 

Spill Release Procedures: CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. ABSORB SPILL WITH INERT MATERIAL, THEN PLACE IN A CHEMICAL WASH CONTAINER. (E.G., DRY SAND OR EARTH), THEN PLACE IN A CHEMICAL WASTE CO NTAINER.

Handling and Storage Precautions: KEEP CONTAINER CLOSED. LOOSEN CLOSURE CAUTIOUSLY BEFORE OPENING. STORE IN A COOL DRY PLACE. WELL VENTILATED PLACE AWAY FROM INCOMPATIBLE MATERIALS. KEEP AWAY FROM HEAT, SPARKS, AND FLAMES. PROTECT MAT ERIAL FROM DIRECT SUNLIGHT. GROUND AND BOND CONTAINERS WHEN TRANSFERRING MATERIALS.

**Respiratory Prote** 

ction:DO NOT BREATHE THE VAPORS OR SPRAY MIST. IF YOU EXPERIENCE EYE WATERING, HEADACHE OR DIZZINESS OF IF AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE ABOVE APPLICABLE LIMITS, WEAR AN APPROPRIATE, PRO PERLY FITTED RESPIRATOR (NIOSH APPROVED) DURING AND AFTER APPLICATION. FOLLOW RESPIRATOR MANUFACTURE'S DIRECTIONS FOR RESPIRATOR USE. Ventilation:PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN. TO KEEP THE TLV OF THE HAZARDOUS INGREDIENTS BELOW THE LIMITS SPE CIFIED IN SECTION TWO. Protective Gloves:WEAR CHEMICAL RESISTENT GLOVES. Eye Protection:SAFETY GLASSES, CHEMICAL GOGGLES AND/OR A FACE SHIELD SHOULD BE WORN

Other Protective Equipment: AS NEEDED, USE BODY PROTECTION TO AVOID CONTACT WITH PRODUCT.

Supplemental Safety and Health

Boiling Pt:=117.2C, 243.F Vapor Density:> AIR Spec Gravity:1.398 Evaporation Rate & amp; Reference:SLOWER/ ETHER Appearance and Odor:LIQUID

====

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION AS IN WELDING. FUMES MAY PRODUCE CARBON DIOXIDE AND CARBON DIOXIDE MONOXIDE.

Toxicological Information:THERE IS NO DATA AVAILABLE ON THE PRODUCT ITSELF. NOTICE: REPORTS HAVE ASOCIATED REPEATED AND PROLONGED

OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAWMAGE. INTENTION AL MISUE BY DELIBERATELY CONCENTRATING THE CONTENTS MAY BE HARMFUL OR FATAL.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE UNOPENED CONTAINERS.

SARA Title III Information:TS

```
CA - COMPONENTS OF THIS PRODUCT ARE LISTED
ON THE TSCA INVENTORY. CERCLA - WE RECOMMEND YOU LOCAL AUTHORITIES
TO DETERMINE IF THERE MAY BE OTHER LOCAL REPORTING REQUIREMENTS.
SARA TITLE III ? NONE KNOWN UNLESS CHEMICALS ARE SPECIFIED BELOW.
SECTION 302 REPORTABLE INGREDIENTS
State Regulatory Information:CALIFORNIA PROPOSITION 65: NONE KNOWN
UNLESS SPECIFIED BELOW. WARNING: THIS PRODUCT CONTAINS A CHEMICAL
```

KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Disclaimer

(provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.