

===== Product Identification =====

Product ID:ANTISEIZE COMPOUND MIL-PRF-907E

MSDS Date:08/01/1999

FSC:8030

NIIN:00-286-5453

Status Code:A

MSDS Number: CLJLC

=== Responsible Party ===

Company Name:MAKOOR PRODUCTS CO INC

Box:492

City:RIVERHEAD

State:NY

ZIP:11901

Country:US

Info Phone Num:631-727-4445

Emergency Phone Num:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtrec Ind/Phone:(8

00)424-9300

CAGE:TO443

=== Contractor Identification ===

Company Name:MAKOOR PRODUCTS CO INC

Box:492

City:RIVERHEAD

State:NY

ZIP:11901

Country:US

Phone:631-727-4445

CAGE:TO443

===== Composition/Information on Ingredients =====

Ingred Name:PETROLATUM

CAS:8009-03-8

RTECS #:SE6780000

= Wt:70.

Ingred Name:COPPER

CAS:7440-50-8

RTECS #:GL5325000

= Wt:20.

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:GRAPHITE

CAS:7782-42-5

RTECS #:MD96596

00  
= Wt:10.  
OSHA PEL:SEE TABLE Z-3  
ACGIH TLV:2 MG/M3

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Effects of Overexposure:EYE CONTACT: IN CASE OF ACCIDENTAL EYE CONTACT  
FLUSH WITH WARM FOR 5 TO 10 MINUTES. IF IRRITATION PERSIST GET  
MEDICAL ATTENTION. SKIN CONTACT: NOT IRRITATING INHALATION: NOT  
LIKELY INGESTION: NOT H ARMFUL, MAY CAUSE DIARRHEA.

===== Fire Fighting Measures =====  
=====

Flash Point:=232.2C, 450.F

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP AND DISPOSE AS PERMITTED BY LOCAL  
ORDINANCE

===== Handling and Storage =====

Other Precautions:NONE REQUIRED

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN SITUATION WHERE VAPOR CONCENTRATIONS MAY  
EXCEED THE RECOMMENDED EXPOSURE LIMITS, A NIOSH-APPROVED ORGANIC

VAPOR CARTRIDGE RESPIRATOR SHOULD BE WORN. USE SELF-CONTAINED  
SUPPLIED-AIR RESPIRATOR FOR E Mergencies.

Ventilation:GENERAL DILUTION OR MECHANICAL VENTILATION/EXPLOSION-PROOF  
LOCAL EXHAUST TO KEEP VAPOR BELOW RECOMMENDED EXPOSURE LIMITS

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:EYE WASH STATION.BARRIER CREAMS SPECIFIC FOR  
PETROLEUM-BASED MATERIALS MAY BE USED WHEN GLOVES ARE IMPRACTIC

AL.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.

WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health

EMPTY CONTAINERS MAY CONTAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE TO HEAT, FLAME; THEY MAY EXPLODE. DO NOT USE PRESSURE TO EMPTY DRUM OR DRUM MAY RUPTURE WITH EXPLOSIVE FORCE.

===== Physical/Chemical Properties =====

==

Boiling Pt:>260.C, 500.F

Spec Gravity:1.3

Solubility in Water:INSOLUBLE

Appearance and Odor:GRAYFISH PASTE, ODOR BLAND

===== Stability and Reactivity Data =====

MAY REACT WITH STRONG ALKALIS OR STRONG ACIDS, OXIDIZING AGENTS.

Stability Condition to Avoid:MAY REACT WITH STRONG ALKALIS OR STRONG ACIDS, OXIDIZING AGENTS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

o

f Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.