

HERAEUS KULZER INC -- 46185, DENSTONE -- 6520-00-585-3486

=====  
Product Identification  
=====

Product ID:46185, DENSTONE  
MSDS Date:01/18/1996  
FSC:6520  
NIIN:00-585-3486  
Status Code:A  
MSDS Number: CLJNT  
=== Responsible Party ===  
Company Name:HERAEUS KULZER INC  
Address:4315 S LAFAYETTE BLVD  
City:SOUTH BEND  
State:IN  
ZIP:46614-2517  
Country:US  
Info Phone Num:219-291-0661  
Emergency Phone Num:219-291-0661  
Resp. Party Other MSDS Num.:M001  
Chemtrec Ind/Phone:(800)424-9300  
CAGE:95551  
=== Contractor Identification ===  
Company Name:HERAEUS KULZER INC  
Address:4315 S LAFAYETTE BLVD  
Box:City:SOUTH BEND  
State:IN  
ZIP:46614-2517  
Country:US  
Phone:219-291-0661  
CAGE:95551

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CALCIUM SULFATE  
CAS:7778-18-9  
RTECS #:WS6920000  
Minumum % Wt:90.  
Maxumum % Wt:100.  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3

=====  
===== Hazards Identification =====  
=====

LD50 LC50 Mixture:NO DATA PROVIDED BY MANUFACTURER  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:UNKNOWN IARC:NO  
Health Hazards Acute and Chronic:ACUTE: EYES-PARTICLES MAY CAUSE  
IRRITATION. MIXED MATERIAL MAY DEVELOP ENOUGH HEAT TO CAUSE BURNS  
IF LARGE AMOUNT COME IN CONTACT WITH SKIN DURING HARDENING. CHONIC,  
OTHER: PROLONGED EXPOSURE MAY CAU SE LUNG DISEAS

E.  
Explanation of Carcinogenicity:NONE OF THE CHEMICALS ARE LISTED AS A  
CARCINOGEN OR POTENTIAL CARCINOGEN BY IARC.  
Effects of Overexposure:PARTICLES MAY CAUSE IRRITATION. MIXED MATERIALS  
MAY DEVELOP ENOUGH HEAT TO CAUSE BURNS IF LARGE AMOUNTS COME INTO  
CONTACT WITH SKIN DURING HARDENING.  
Medical Cond Aggravated by Exposure:PRE-EXISTING UPPER RESPIRATORY AND  
LUNG DISEASE SUCH AS BUT NOT LIMITED TO, BRONCHITIS, EMPHYSEMA AND  
ASTHMA.

=====  
===== First Aid Measures  
=====

First Aid:SKIN-WASH PROMPTLY WITH WATER. IF IRRITATION OCCURS, CONTACT  
PHYSICIAN. INGESTION-PRODUCT MAY HARDEN ON CONTACT WITH WATER. MAY  
RESULT IN OBSTRUCTION IF INGESTED. SEE PHYSICIAN. EYES-REMOVE  
CONTACT LE NSES. RINSE EYES WITH PLENTY OF RUNNING WATER FOR 10-15  
MINUTES, INCLUDING UNDER EYELIDS. IF IRRITATION OCCURS, CONTACT  
PHYSICIAN. INHALATION: REMOVE TO FRESH AIR.

=====  
===== Fire Fighting Measures =====  
=====

Extingu  
ishing Media:NON-COMBUSTIBLE MATERIALS.  
Fire Fighting Procedures:NONE.  
Unusual Fire/Explosion Hazard:NONE KNOWN

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures:SWEEP OR VACUUM SPILLED MATERIAL INTO A WASTE  
CONTAINER FOR DISPOSAL. AVOID CREATING EXCESSIVE DUST.  
Neutralizing Agent:NO DATA PROVIDED BY MANUFACTURER

=====  
===== Handling and Storage =====  
=====

Handling and Storage Precautions:BE SURE PROPER VENTILATION AND

RESPIRATORY AND EYE PROTECTION ARE USED UNDER DUSTING CONDITIONS.  
Other Precautions:NO DATA PROVIDED BY MANUFACTURER

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH APPROVED RESPIRATOR AS APPROPRIATE FOR  
NUISANCE DUST, ESPECIALLY WHEN DRY GRINDING. EXCESSIVE PARTICULATE  
IN THE WORK PLACE SHOULD BE AVOIDED. WET GRINDERS SHOULD BE USED.

Ventilation:PROVIDE GENERAL VENTILATION AND LOCAL EXHAUST TO MEET TLV  
REQUIREMENTS.

Protective

Gloves:YES.

Eye Protection:YES.

Other Protective Equipment:NONE

Work Hygienic Practices:WEAR A MASK WHILE EXPOSED TO DUST.

Supplemental Safety and Health

NO DATA PROVIDED BY MANUFACTURER

=====  
===== Physical/Chemical Properties =====

HCC:T6

Boiling Pt:B.P. Text:NA

Vapor Pres:MMHG: NA

Vapor Density:(AIR=1):NA

Spec Gravity:(H2O=1):2.3

pH:NA

Evaporation Rate & Reference:(ETHER=1): NA

Solubility in Water:SLIGHT, 0.2% @ 40C

Appearance and Odor:FINE POWDER IN VARIOUS COLOR

S - LOW ODOR

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACIDS.

Stability Condition to Avoid:NONE.

Hazardous Decomposition Products:NONE.

Conditions to Avoid Polymerization:WILL NOT OCCUR

=====  
===== Toxicological Information =====

Toxicological Information:OSHA PERMISSABLE EXPOSURE LIMIT: NONE. ACGIH  
THRESHOLD EXPOSURE LIMIT: NONE. OTHER EXPOSURE LIMIT: NONE.

=====  
===== Ecological Info

rmation =====

Ecological:NO DATA PROVIDED BY MANUFACTURER

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:NO DATA PROVIDED BY MANUFACTURER

===== Regulatory Information =====

SARA Title III Information:DIE KEEN GREEN AND BLUE CONTAIN CHROMIUM III

COMPOUND AT 0.17-0.25%. THIS CHROMIUM COMPOUND AS CHROMIUM IS CONSIDERED TO BE TOXIC AND SUBJECT TO SARA TITLE III, SECTION 311, 312 AND 313.

Federal Regulatory Information:NO DATA PROVIDED BY MANUFACTURER

State Regulatory Information:NO DATA PROVIDED BY MANUFACTURER

===== Other Information =====

=====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.