LASTING PAINTS INC LA ARCH A/SG P BSE FS 2-250 8010-00-597-8195
Product ID:LA ARCH A/SG P BSE FS 2-250 MSDS Date:12/02/1985 FSC:8010 NIIN:00-597-8195 Status Code:A MSDS Number: CLKNY === Responsible Party === Company Name:LASTING PAINTS INC. Address:200 S FRANKLINTOWN RD City:BALTIMORE State:MD ZIP:21223-2038 Country:US Emergency Phone Num:410-947-6306 Preparer's Name:ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300 CAGE :35178 === Contractor Identification === Company Name:LASTING PAINTS INC. Address:200 S FRANKLINTOWN RD Box:City:BALTIMORE State:MD ZIP:21223-2038 Country:US CAGE:35178
Ingred Name:ALIPHATIC DISTILLATE (STODDARD) CAS:8052-41-3 Code:F RTECS #:WJ8925000 = Wt:25.5 OSHA PEL:2900 MG/M3;500 PPM ACGIH TLV:525 MG/M3;100 PPM ===================================

Effects of Overexposure:VAPOR HARMFUL. M

NOSE AND THROAT IRRITATION. Medical Cond Aggravated by Exposure:EXCESSIVE INHALATION BY PERSONS WITH PRE-EXISTING RESPIRATORY CONDITIONS COULD HAVE THE PROBLEM ADDITIONALLY AGGRAVATED.
======================================
First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. (EYES): FLUSH WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES . (SKIN):
WASH AFFECTED AREAS WITH SOAP AND WATER. INGESTION: DRINK 1 OR 2 GLASSES O F WATER TO DILUTE. DO NOT INDUCE VOMITING.
======================================
Flash Point Method:CALC Flash Point:=43.3C, 110.F Autoignition Temp:Autoignition Temp Text:NONE Lower Limits:NONE
Upper Limits:NONE Extinguishing Media:FOAM CO2 DRY CHEMICAL WATER FOG USE ANY CLASS B APPROVED FIRE EXTINGUISHER.
Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD UP AND EXPLOSION. Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.
======== Accidental Release Measures =========
Spill Release Procedures:USE SCOOP ON LARGE SPILLS AND ABSORBENT MATERIAL ON SMALL SPILLS.
======================================
Handling and Storage Precautions:KEEP CLOSURE TIGHT AND CONTAINER UPRIGHT TO PREVE
NT LEAKAGE. Other Precautions:AVOID EYE AND SKIN CONTACT AND CONSTANT BREATHING OF VAPOR OR SPRAY MIST.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE AIR LINE TYPE RESPIRATOR. Ventilation:VENTILATION SHOULD ALSO BE PROVIDED. Protective Gloves:USE NEOPRENE OR OTHER IMPERVIOUS TYPE GLOVES. Eye Protection:USE GOGGLES OR SIDE SHIELD SPECTACLES. Other Protective Equipment:HAVE EYE WASH STATION AND SAFETY SHOWERS

SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAN CAUSE EYE, SKIN,

AY AFFECT THE BRAIN OR NERVOUS

AVAILABLE.
Work Hygienic Pract

ices:WASH HANDS BEFORE EATING OR USING WASHROOM. Supplemental Safety and Health ========= Physical/Chemical Properties ============ Boiling Pt:B.P. Text:323.00 TO390.00 DEG F Melt/Freeze Pt:M.P/F.P Text:NONE Decomp Temp:Decomp Text:NONE Vapor Density:HEAVIER Evaporation Rate & Deference: SLOWER THAN ETHER Appearance and Odor:NONE Percent Volatiles by Volume:44.89% ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YE OXIDIZING AGENTS. Stability Condition to Avoid: HEAT AND OPEN FLAME. Hazardous Decomposition Products: CARBON MONOXIDE AND OTHER ORGANIC MATERIALS MAY BE FORMED DURING COMBUSTION. Conditions to Avoid Polymerization: WILL NOT OCCUR.

======= Disposal Considerations =============

Waste Disposal Methods:DISPOSAL SHOULD BE DONE IN ACCORDANCE WITH FEDERAL STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This informati on is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.