View NSN Online: https://aerobasegroup.es/nsn/8010-00-935-7079

LHB INDUSTRIES

-- SPRAY PAINT (AEROSOL)

MSDS Safety Information

_____ FSC: 8010 NIIN: 00-935-7079 MSDS Date: 10/02/1997 MSDS Num: CLMXB Product ID: SPRAY PAINT (AEROSOL) MFN: 01 **Responsible Party** Cage: 0FTT5 Name: LHB INDUSTRIES Address: 8833 FLEISCHER PLACE City: ST. LOUIS MO 63134 Info Phone Number: 314-522-3141 Emergency Phone Number: 800-424-9300 Preparer's Name: ERNEST CARTER Chemtrec IND/Phone: (800)424-9300 Review Ind: Y Published: Y _____ Contractor Summary ______ Cage: 0FTT5 Name: LHB INDUSTRIES Address: 8833 FLEISCHER PLACE City: ST. LOUIS MO 63134 Phone: 314-522-3141 _____ Item Description Information _____ _____ Item Manager: GSA Item Name: LACQUER Type/Grade/Class: COMPOSITION L Unit of Issue: PT UI Container Qty: 0 _____ Ingredients ______ Cas: 67-64-1 RTECS #: AL3150000 Name: ACETONE Percent by Wt: 32.48 OSHA PEL: 2400 MG/M3;1000 PPM ACGIH TLV: 1780 MG/M3;750 PPM ACGIH STEL: 2380 MG/M3;1000 PPM EPA Rpt Qty: 5000 LBS DOT Rpt Qty: 5000 LBS

---Cas: 108-88-3 RTECS #: XS5250000 Name: TOLUENE Percent by Wt: 32.26 **OSHA PEL: SEE TABLE Z-2** ACGIH TLV: 188 MG/M3;50 PPM ACGIH STEL: NOT ESTABLISHED EPA Rpt Qty: 1000 LBS DOT Rpt Qty: 1000 LBS -----Cas: 74-98-6 RTECS #: TX2275000 Name: PROPANE Percent by Wt: 10.74 OSHA PEL: 1800 MG/M3;1000 PPM -----Cas: 115-10-6 RTECS #: PM4780000 Name: DIMETHYL ETHER Percent by Wt: 6.71 -----Cas: 111-15-9 RTECS #: KK8225000 Name: 2 -ETHOXYETHYL ACETATE Percent by Wt: 2.23 OSHA PEL: 540 M/M3;100 PPM ACGIH TLV: 27 MG/M3:5 PPM ACGIH STEL: NOT ESTABLISHED -----Cas: 71-36-3 RTECS #: EO1400000 Name: 1-BUTANOL Percent by Wt: 2.23 OSHA PEL: 300 MG/M3;100 PPM ACGIH TLV: NOT ESTABLISHED ACGIH STEL: C152 MG/M3;C50 PPM EPA Rpt Qty: 5000 LBS DOT Rpt Qty: 5000 LBS _____ Health Hazards Data

Route Of Entry I

nds - Inhalation: YES Skin: YES Ingestion: YES Carcinogenicity Inds - NTP: NO IARC: NO OSHA: NO Effects of Exposure: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. IN CONFINED AREAS VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITATION TO SKIN AND RESPIRATORY TRACT. OVEREXPOSURE MAY RESULT IN LIGHT H EADEDNESS, STAGGERING GAIT, GIDDINESS AND POSSIBLE NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. Signs And Symptions Of Overexposure: IRRITATION TO EYES, THROAT, AND RESPIRATORY TRACT, MAY CAUSE HEADACHES, NAUSEA, AND VOMITING. Medical Cond Aggravated By Exposure: RESPIRATORY ALIMENTS. First Aid: FOR CONTACT WITH SKIN OR CLOTHES WASH WITH SOAP AND WATER. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES AND CONTACT A PHYSICIAN. IF SWALLOWED, DO NOT INDUCE VOMITING. GET IMMED IATE MEDICAL A ID. IF INHALED, REMOVE TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION IF NECESSARY AND GET MEDICAL AID. _____ Handling and Disposal _____ Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA. MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS. Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE&LOCAL REGULATIONS. Hand ling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN! CAUTION-CONTENTS UNDER PRESSURE. DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120 F/48.9 C. AVOID BREATHING SPRAY, MIST OR VAPOR. AVOID CONTACT WITH EYES OR SKIN. Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL MISUSE BY CONCENTRATING VAPORS MAY BE HARMFUL OR FATAL. _____ Fire

and Explosion Hazard Information

Flash Point Method: TCC Flash Point: =-5.4C, 22.F Autoignition Temp: =350.C, 662.F Lower Limits: 2.2% Upper Limits: 18.8% Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY. Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING OF CONTAINERS. WATER MAY BE INEFFECTIVE. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COO L. Unusual Fire/Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPERATURES CONTAINERS MAY RUPTURE OR BURST. DO NOT EXPOSE AEROSOLS TO TEMPERATURES ABOVE 120 DEG F. ______ **Control Measures** _____ Respiratory Protection: USE NIOSH/MSHA APPROVED MASK ABOVE TLV. Ventilation: LOCAL EXHAUST PREFERRED Protective G loves: TO PROTECT SKIN. Eye Protection: CHEMICAL SPLASH GOGGLES. Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH STATION. Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK, OR SMOKE WHILE USING PRODUCT. Physical/Chemical Properties _____ Vapor Pres: 70@68 F/20 C Vapor Density: >1.522 Spec Gravity: 0.905 PAINT VOC Pounds/Gallon: 7.55 VOC Gr ams/Liter: 422 Evaporation Rate & amp; Reference: (BU AC=1) Solubility in Water: INSOLUBLE Appearance and Odor: BLACK/PAINT _____ Reactivity Data _____

Stability Indicator: YES Hazardous Decomposition Products: CARBON MONOXIDE. Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: WILL NOT OCCUR.

MSDS Transport Informatio

Transportation Information

Responsible Party Cage: 0FTT5 Trans ID NO: 159159 Product ID: SPRAY PAINT (AEROSOL) MSDS Prepared Date: 10/02/1997 Review Date: 10/04/2001 **MFN: 1** Multiple KIT Number: 0 Unit Of Issue: PT Container QTY: 0 _____ **Detail DOT Information** _____ DOT PSN Code: DTJ Symbols: D DOT Proper Shipping Name: CONSUMER COMMODITY Hazard Class: ORM-D Label: NONE Non Bulk Pack: 156,306 **Bulk Pack: NONE** Max Qty Pass: 30KGGROSS Max Qty Cargo: 30KGGROSS Vessel Stow Req: A _____ Detail IMO Information _____ IMO PSN Code: AKH IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ? IMDG Page Number: SEE 9022 UN Number: 195 0 UN Hazard Class: 9? IMO Packaging Group: -Subsidiary Risk Label: -EMS Number: 2-13 _____ Detail IATA Information _____ IATA PSN Code: HDW IATA UN ID Num: 8000 IATA Proper Shipping Name: CONSUMER COMMODITY + IATA UN Class: 9 IATA Label: MISCELLANEOUS Packing Note Passenger: 910 Max Quant Pass: 25KG G Max Quant Cargo: 25KG G Packaging Note Cargo: 910 Exceptions: A112 _____

Detail AFI Information

_____ AFI PSN Code: HEB AFI Proper Shipping Name: CONSUMER COMMODITY AFI Hazard Class: 9 AFI UN ID NUM: UN8000 **Special Provisions: P5** Back Pack Reference: A13.13 _____ HAZCOM Label _____ Product ID: SPRAY PAINT (AEROSOL) Cage: 0FTT5 **Company Name: LHB INDUSTRIES** Street: 8833 FLEISCHER PLACE Citv: ST. LOUIS MO Zipcode: 63134 Health Emergency Phone: 800-424-9300 Label Required IND: Y Date Of Label Review: 10/04/2001 Status Code: A Origination Code: G Hazard And Precautions: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. IN CONFINED AREAS VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITATION TO S KIN AND RESPIRATORY TRACT. OVEREXPOSURE MAY RESULT IN LIGHT HEADEDNESS, STAGGERING GAIT, GIDDINESS AND POSSIBLE NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. ______ Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said informat ion to have any application, use or

viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.