

HUMCO HOLDING GROUP, INC. -- PETROLEUM JELLY, PN-011 -- 6505-00-133-8025

===== Product Identification =====

Product ID:PETROLEUM JELLY, PN-011
MSDS Date:07/21/1997
FSC:6505
NIIN:00-133-8025
Status Code:A
MSDS Number: CLPCG
=== Responsible Party ===
Company Name:HUMCO HOLDING GROUP, INC.
Address:7400 ALUMAX DRIVE
City:TEXARKANA
State:TX
ZIP:75501
Country:US
Info Phone Num:903-831-7808
Emergency Phone Num:800-424-9300
Chemtrec Ind/Phone:(800)424-9300
CAGE:TO364
=== Contractor Identification ===
Company Name:HUMCO HOLDING GROUP, INC
Address:7400 ALUMAX DRIVE
Box:City:TEXARKANA
State:TX
ZIP:75501
Country:US
Phone:903-831-7808
CAGE:TO364

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM WHITE U.S.P.
CAS:8009-03-8
RTECS #:SE6780000
Other REC Limits:NONE
OSHA PEL:5MG/M3 OIL MIST TWA
ACGIH TLV:NONE

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingest

ion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:POTENTIAL HEALTH HAZARDS: SKIN:

NON-IRRITATING. EYES: MAY BE SLIGHTLY IRRITATING TO THE EYES.

INHALATION: OIL MIST CONCENTRATION OF 50 MG/M3 CAN CAUSE SHORTNESS

OF BREATH, COUGHING OR WHEEZING. INGESTION: INGESTION OF A LARGE

DOSE MAY HAVE A LAXATIVE EFFECT AND CAUSE CRAMPS AND DIARRHEA. RISK OF ASPIRATION.

Explanation of Carcinogenicity:NO INGREDIENTS LISTED IN THIS SECTION.

Medical

Conditions Aggravated by Exposure:PRE-EXISTING EYE, SKIN AND

RESPIRATORY DISORDERS AND ASTHMA.

===== First Aid Measures =====

First Aid:SKIN: IN CASE OF SKIN CONTACT REMOVE CONTAMINATED CLOTHING,

WASH AFFECTED AREA WITH SOAP AND WATER. EYE: IN CASE OF EYE

CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER, KEEPING

EYELIDS WIDE OPEN. INHALATION: IF OIL MIST INHALED REMOVE PATIENT

TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION.

IF

BREATHING IS DIFFICULT, OXYGEN CAN BE GIVEN BY A QUALIFIED

OPERATOR. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING UNLESS

ADVISED BY A PHYSICIAN DUE TO RISK OF ASPIRATION. GET PROMPT

MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:204.4C, 400.F

Extinguishing Media:SMALL FIRE: USE CARBON DIOXIDE OR DRY CHEMICAL.

LARGE FIRE: USE ALCOHOL FOAM. NOTE: NORMAL FIRE FIGHTING FOAMS THAT ARE SUITABLE

FOR GASOLINE OR HYDROCARBON (FIRE/EXPLOSION HAZARD.)

Fire Fighting Procedures:USE NIOSH-APPROVED SELF-CONTAINED BREATHING

APPARATUS AND FULL PROTECTIVE EQUIPMENT . USE WATER TO KEEP FIRE

EXPOSED TANKS AND CONTAINERS COOL. WATER OR FOAM MAY CAUSE FROTHING

OF MOLTEN MATERIAL. DO NOT ENTER FIRE AREA WITHOUT PROPER PERSONAL

PROTECTIVE EQUIPMENT TO INCLUDE A SELF-CONTAINED BREATHING

APPARATUS.

Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHEN

BURNING. EXTINGUISH

UISHING MEDIA (CON'T): FIRES WILL BREAK DOWN AND
WILL NOT EXTINGUISH FIRES. WATER SPRAY WILL REDUCE THE INTENSITY OF
THE FLAMES.

===== Accidental Release Measures =====

Spill Release Procedures:ALWAYS WEAR THE PROPER PERSONAL PROTECTIVE
EQUIPMENT. ISOLATE THE SPILL AREA AND CONTAIN. ONLY TRAINED
PERSONNEL FITTED WITH THE PROPER PERSONAL PROTECTIVE EQUIPMENT
SHOULD BE ALLOWED TO ENTER THE SPI LL SITE. COLLECT THE SPILL IN A
WASTE CONTAINER FOR
DISPOSAL. FLUSH THE SPILL AREA THOROUGHLY WITH
WATER. SPILL CAN CAUSE VERY SLICK SURFACES!

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F (49C) KEEP
AWAY FROM SOURCES OF INGNITION AND OXIDIZING MATERIALS. ALWAYS USE
IN A WELL VENTILATED AREA.

Other Precautions:KEEP AWAY FROM CHILDREN!

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A NIOSH-APPROVED RESPIRA
TOR APPROPRIATE FOR
THE EXPOSURE OF CONCERN . IF SURROUNDING ATMOSPHERE CONTAINS AN OIL
MIST OF 50 MG/M3 OR GREATER THEN A FULL FACE AIR SUPPLIED
RESPIRATOR IS RECOMM ENDED.

Ventilation:ALWAYS USE IN A WELL-VENTILATED AREA.

Protective Gloves:IMPERVIOUS GLOVES FOR PROLONGED OR HOT EXPOSURES .

Eye Protection:ANSI APPROVED CHEMICAL SAFETY GOGGLES . (SUPP SFTY)

Other Protective Equipment:EYE WASH AND DELUGE SHOWER MEETING ANSI
DESIGN CRITERIA . APRON AND SLIP RESISTANT WORK BOOTS IF
CLEANING
LARGE SPILLS.

Work Hygienic Practices:FOLLOWING GENERALLY RECOGNIZED SAFETY PRACTICES
AND SOUND WORK METHODS SHOULD BE USED WHEN HANDLING THIS PRODUCT IN
LARGE OR SMALL QUANTITIES.

Supplemental Safety and Health

EYE PROTECTION (CON'T) : NONE NEEDED WHEN USED IN JELLY FORM. IF IN
LIQUID FORM USE CHEMICAL GOGGLES.

===== Physical/Chemical Properties =====

Boiling Pt:=343.3C, 650.F

Vapor Pres:1 MMHG @ 20C

Vapor Density:1 (AIR=1)

Spec Gravity:0.

86 (H2O=1)
Evaporation Rate & Reference:NONE
Solubility in Water:INSOLUBLE
Appearance and Odor:YELLOWISH, TRANSLUCENT JELLY. ODOR: NONE.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NORMALLY STABLE. KEEP AWAY FROM HEAT,
SPARKS AND FLAME.
Hazardous Decomposition Products:CARBON MONOXIDE, WTER VAPOR AND
UNIDENTIFIED ORGANIC COMPOUNDS.

===== T
oxicological Information =====

Toxicological Information:N/P.

===== Ecological Information =====

Ecological:N/P.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE ACCORDING TO FEDERAL, STATE AND LOCAL
REGULATIONS.

===== MSDS Transport Information =====

Transport Information:N/P.

===== Regulatory Information =====

SARA Title
III Information:N/P.
Federal Regulatory Information:N/P.
State Regulatory Information:N/P.

===== Other Information =====

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be ac

curate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.