Product ID:"285" ROSIN FLUX CORED SOLDER MSDS Date:12/11/1998 FSC:3439 NIIN:01-391-8478 Status Code:A MSDS Number: CLPQD === Responsible Party === Company Name: EAGLE-PICHER TECHNOLOGIES, LLC Address:3820-SOUTH HANCOCK EXPRESSWAY Box:5234 City:COLORADO SPRINGS State:CO ZIP:80911-1231 Country:US Info Phone Num:719-392-4266 **Emergency Phone Num:(8** 00) 424-9300 Resp. Party Other MSDS Num.:"285" CORE Chemtrec Ind/Phone:(800)424-9300 CAGE:50120 === Contractor Identification === Company Name: EAGLE-PICHER TECHNOLOGIES, LLC Address:3820-SOUTH HANCOCK EXPRESSWAY Box:5234 City:COLORADO SPRINGS State:CO ZIP:80911-1231 Country:US Phone:719-392-4266 CAGE:50120 Company Name:WHEELER BROS INC Address:384 DRUM AVE Box:737 City:SOMERSET State:PA ZIP:15501-0737 Country:US Phone:814-443-7000 Contract Num:SP0400-01-AA-F84-0265 CAGE:55683

====== Com

position/Information on Ingredients =========

Ingred Name:LEAD CAS:7439-92-1 RTECS #:OF7525000 OSHA PEL:0.05 MG/M3 ACGIH TLV:0.15 MG/M3 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:TIN CAS:7440-31-5 RTECS #:XP7320000 OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3

Ingred Name:SILVER CAS:7440-22-4 RTECS #:VW3500000 OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:BISMUTH CAS:7440-69-9 RTECS #:EB2600000

Ingred Name:ANTIMONY CAS:7440-36-0 RTECS #:CC4025000 OSHA PE L:0.5 MG/M3 ACGIH TLV:0.5 MG/M3 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ROSIN CAS:8050-09-7 RTECS #:VL0480000 < Wt:3.

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES Health Hazards Acute and Chronic:TARGET ORGANS: INGESTION OF LEAD METAL CAN AFFECT KIDNEYS, GASTROINTESTINAL, REPRODUCTIVE AND NEUROLOGICAL SYSTEMS. ACUTE- INHALATION: OVERE

XPOSURE TO LEAD MAY RESULT IN
CENTRAL NERVOUS SYSTEM DISORD ERS CHARACTERIZED BY DROWSINESS,
SEIZURES, COMA AND DEATH. EXPOSURE OF THIS MAGNITUDE IS UNLIKELY.
SKIN CONTACT: NONE. SKIN ABSORPTION: NONE. EYE CONTACT: NONE.
INGESTION: NOT LIKELY TO OCCUR, BUT WOU LD HAVE SIMILAR EFFECTS AS
INHALATION. CHRONIC: REPEATED INHALATION OR INGESTION OF LEAD CAN
RESULT IN SYSTEMIC POISONING.
Effects of Overexposure: TARGET ORGANS: INGESTION OF LEAD METAL CAN
AFFECT KIDNEYS, GASTR
OINTESTINAL, REPRODUCTIVE AND NEUROLOGICAL
SYSTEMS. ACUTE- INHALATION: OVEREXPOSURE TO LEAD MAY RESULT IN
CENTRAL NERVOUS SYSTEM DISORD ERS CHARACTERIZED BY DROWSINESS,
SEIZURES, COMA AND DEATH. EXPOSURE OF THIS MAGNITUDE IS UNLIKELY.
SKIN CONTACT: NONE. SKIN ABSORPTION: NONE. EYE CONTACT: NONE.
INGESTION: NOT LIKELY TO OCCUR, BUT WOU LD HAVE SIMILAR EFFECTS AS
INHALATION, CHRONIC: REPEATED INHALATION OR INGESTION OF LEAD CAN

RESULT IN SYSTEMIC POISONING.

Medical Con

d Aggravated by Exposure:LEAD: DISEASES OF THE BLOOD AND BLOOD-FORMING ORGANS, KIDNEYS, NERVES AND POSSIBLY REPRODUCTIVE SYSTEMS.

First Aid:EYE: FOR BURNS FLUSH IMMEDIATELY WITH COOL WATER. SKIN: FOR BURNS FLUSH IMMEDIATELY WITH COOL WATER. INHALATION: REMOVE PERSON FROM EXPOSURE TO FUMES. INGESTION: IF THOUGHT TO BE OVEREXPOSED, THE PERS ON SHOULD HAVE A BLOOD LEAD ANALYSIS DONE. SEEK MEDICAL ASSISTAN

CE FOR FURTHER TREATMENT, OBSERVATION AND SUPPORT IF NEEDED.

Flash Point Method:TOC

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS IF THIS MATERIAL IS IN THE VICINITY OF A FIRE.

Unusual Fire/Explosion Hazard: FLUX IN CORED SOLDER MAY IGNITE WHEN THE SOLDER MELTS IN A FIRE.

Spill Release Procedures: MELTED SOLDER WILL SOLIDIFY ON

COOLING AND CAN BE SCRAPED UP. USE CAUTION TO AVOID BREATHING FUMES IF A GAS TORCH IS USED TO CUT UP LARGE PIECES.

Handling and Storage Precautions:STORE AWAY FROM SOURCES OF SULFUR. WASH HANDS AFTER HANDLING SOLDER CONTAINING LEAD BEFORE EATING OR SMOKING. AVOID BREATHING SMOKE/FUMES GENERATED DURING SOLDERING. DO NOT PLACE FLUX CORED SOLDER INT O A HOT SOLDER POT BECAUSE THE FLUX MAY IGNITE.

Other Pre

cautions:USE OF STRONG ACID FLUXES MAY RESULT IN LIBERATION OF TOXIC LEAD CHLORINE FUMES. CAUTION: EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE. OBSERVE ALL LABEL PRECAUTIONS.

Respiratory Protection: WHEN VENTILATION IS NOT SUFFICIENT TO REMOVE FUMES FROM THE BREATHING ZONE, A NIOSH APPROVED RESPIRATOR SHOULD BE WORN.

Ventilation: PROVIDE ADEQUATE VENTILATION (GENERAL AND/OR LOCAL) IF NECESSARY TO MEET EXPOSU

RE REQUIREMENTS. LOCAL EXHAUST VENTILATION IS PREFERRED

Protective Gloves: USUALLY NOT REQUIRED

Eye Protection: WHEN SOLDERING, USE GOGGLES OR FACE SHIELD

Other Protective Equipment:NONE

Work Hygienic Practices: WASH HANDS THOROUGHLY AFTER HANDLING SOLDER CONTAINING LEAD BEFORE EATING OR SMOKING.

Supplemental Safety and Health

DO SOLDERING IN A WELL VENTILAED AREA.

HCC:N1 Spec Gravity:>1 Solubility in Water:0 Appearance and Odor:SILVER-GRAY METAL IN WIRE, RIBBON OR PREFORMED SHAPES W/ A CORE OF FLUX;NO ODOR

Stability Indicator/Materials to Avoid:YES STRONG ACID, STRONG OXIDIZERS. Stability Condition to Avoid:NONE Hazardous Decomposition Products:WHEN HEATED TO SOLDERING TEMPERATURES THE SOLVENT IN THE FLUX WILL BOIL AWAY AND CARRY UP DROPLETS OF ROSIN AND THERMAL DEGRADATION PRODUCTS SUCH AS ALIPHATIC ALDEHYDES, ACIDS AND TERP

## ENES. NO LEAD IS Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:SOLDER CAN BE RECLAIMED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its us

e. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.