

SHERWIN-WILLIAMS CO THE -- MIL-PRF-24635B,TYPEII, CLASS 1 ENAMEL, SILICONE ALKYD COPOLY -- 8010-01-396-6805

=====  
===== Product Identification =====

Product ID:MIL-PRF-24635B,TYPEII, CLASS 1 ENAMEL, SILICONE ALKYD COPOLY

MSDS Date:11/29/2000

FSC:8010

NIIN:01-396-6805

Status Code:A

MSDS Number: CLPYZ

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Info Phone Num:216-566-2902/216-566-2917

Emergency Phone Num:216-566-2917

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:54636

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:800-251-2486/216-566-2242

CAGE:54636

=====  
===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:64742-88-7

Code:F

= Wt:16.

Ingred Name:LIGHT AROMATIC HYDROCARBONS

CAS:64742-95-6

Code:F

RTECS #:WF3400000

= Wt:2.

Ingred Name:1,3,5-TRIMETHYLBENZENE

CAS:108-67-8

RTECS #:OX6825000

= Wt:2.

Ingred Name:1,2,4-TRIMETHYLBENZENE

CAS:95-63-6

RTECS #:DC3325000

= Wt:3.

Ingred Name:COBALT 2-ETHYLHEXANOATE (1:2)

CAS:136-52-7

= Wt:.2

Ingred Name:1-METHOXY-2-PROPANOL ACETATE

CAS:108-65-6

Code:F

RTECS #:AI8925000

= Wt:4.

Ingred Name:CALCIUM CARBONATE

CAS:471-34-1

RTECS #:FF9335000

= Wt:9.

=====  
===== Hazard

s Identification =====

Health Hazards Acute and Chronic:EXPOSURE MAY BE BY INHALATION AND/OR SKIN OR EYE CONTACT, DEPENDING ON CONDITIONS OF USE. TO MINIMIZE EXPOSURE, FOLLOW RECOMMENDATIONS FOR PROPER USE, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT.

Effects of Overexposure:IRRITATION OF EYES, SKIN AND RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION, EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH. HEADACHE, DIZZINESS, N

AUSEA, AND LOSS OF CO ORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE.

===== First Aid Measures =====

First Aid:IF INHALED: REMOVE FROM EXPOSURE. RESTORE BREATHING.KEEP WARM AND QUIET.IF ON SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER.REMOVE CONTAMINATED CLOTHING. IF IN EYES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES.GET MEDICAL ATTENTION. IF SWALLOWED: GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:=-37.8C, 100.F

Lower Limits:0.7%

Upper Limits:13.1%

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING

SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER

MAY BE USED TO COOL CLOSED CO NTAINERS TO PREVENT PRESSURE BUILD UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIA L PRECAUTIONS. DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH H

AZARD.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.VENTILATE AND REMOVE WITH INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND APROPRIATE LABELING. CONTENTS ARE COMBUSTIBLE. KEEP AWAY FROM HEAT AND OPEN FLAMES. CONSULT NFPA CODE. USE APPR

OPRIATE BONDING AND

GROUNDING PROCEDURES. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST MATERIALS IN SECTION II. WHEN SANDING OR ABRADING THE DRIED FILM, WEAR A DUST/MI

ST RESPIRATOR APPROVED BY NIOSH/MSHA FOR DUST WHICH MAY BE GENERATED FROM THIS PRODUCT, UNDERLYING PAINT, OR THE ABRASIVE.

Ventilation:USE ONLY WITH ADEQUATE VENTILATION.

Protective Gloves:WEAR GLOVES WHICH ARE RECOMMENDED BY GLOVE SUPPLIER

Eye Protection:WEAR SAFETY SPECTACLES WITH UNPERFORATED SIDESHIELDS.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

Boiling Pt.=201.7C, 395.F

B.P. Text:284-395 F

Vapor Density:HEAVIER

Spec Gravity:1.

10

VOC Pounds/Gallon:328

VOC Grams/Liter:2.74

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:39%

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE,

AND LOCAL REGULATIONS REGARDING POLLUTION.

=====  
===== Regulatory Information =====

SARA Title III Information:108-88-3, TOLUENE, 1% MAX; 1330-20-7, XYLENE, 1% MAX; 95-63-6, 1,2,4-TRIMETHYLBENZENE, 8% MAX.; COBALT COMPOUND, .2% BY WEIGHT.

State Regulatory Information:SARA 313 (40 CFR 372.65 C) SUPPLIER NOTIFICATION

=====  
===== Other Information =====

Disclaimer (provided with this information by the compiling agencies ):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.